

NAME

EVP_SIGNATURE-DSA – The EVP_PKEY DSA signature implementation

DESCRIPTION

Support for computing DSA signatures. See **EVP_PKEY-DSA** (7) for information related to DSA keys.

Signature Parameters

The following signature parameters can be set using **EVP_PKEY_CTX_set_params()**. This may be called after **EVP_PKEY_sign_init()** or **EVP_PKEY_verify_init()**, and before calling **EVP_PKEY_sign()** or **EVP_PKEY_verify()**.

“digest” (**OSSL_SIGNATURE_PARAM_DIGEST**) <UTF8 string>

“properties” (**OSSL_SIGNATURE_PARAM_PROPERTIES**) <UTF8 string>

The settable parameters are described in **provider-signature** (7).

The following signature parameters can be retrieved using **EVP_PKEY_CTX_get_params()**.

“algorithm-id” (**OSSL_SIGNATURE_PARAM_ALGORITHM_ID**) <octet string>

“digest” (**OSSL_SIGNATURE_PARAM_DIGEST**) <UTF8 string>

The gettable parameters are described in **provider-signature** (7).

SEE ALSO

EVP_PKEY_CTX_set_params (3),

EVP_PKEY_sign (3),

EVP_PKEY_verify (3),

provider-signature (7),

COPYRIGHT

Copyright 2020–2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the Apache License 2.0 (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <<https://www.openssl.org/source/license.html>>.