

**NAME**

Text::Iconv – Perl interface to iconv() codeset conversion function

**SYNOPSIS**

```
use Text::Iconv;
$converter = Text::Iconv->new("fromcode", "tocode");
$converted = $converter->convert("Text to convert");
```

**DESCRIPTION**

The **Text::Iconv** module provides a Perl interface to the **iconv()** function as defined by the Single UNIX Specification.

The **convert()** method converts the encoding of characters in the input string from the *fromcode* codeset to the *tocode* codeset, and returns the result.

Settings of *fromcode* and *tocode* and their permitted combinations are implementation-dependent. Valid values are specified in the system documentation; the **iconv(1)** utility should also provide a **-I** option that lists all supported codesets.

**Utility methods**

**Text::Iconv** objects also provide the following methods:

**retval()** returns the return value of the underlying **iconv()** function for the last conversion; according to the Single UNIX Specification, this value indicates “the number of non-identical conversions performed.” Note, however, that iconv implementations vary widely in the interpretation of this specification.

This method can be called after calling **convert()**, e.g.:

```
$result = $converter->convert("lorem ipsum dolor sit amet");
$retval = $converter->retval;
```

When called before the first call to **convert()**, or if an error occurred during the conversion, **retval()** returns **undef**.

**get\_attr()**: This method is only available with GNU libiconv, otherwise it throws an exception. The **get\_attr()** method allows you to query various attributes which influence the behavior of **convert()**. The currently supported attributes are *trivialp*, *transliterate*, and *discard\_ilseq*, e.g.:

```
$state = $converter->get_attr("transliterate");
```

See **iconvctl(3)** for details. To ensure portability to other iconv implementations you should first check for the availability of this method using **eval {}**, e.g.:

```
eval { $conv->get_attr("trivialp") };
if ($@)
{
    # get_attr() is not available
}
else
{
    # get_attr() is available
}
```

This method should be considered experimental.

**set\_attr()**: This method is only available with GNU libiconv, otherwise it throws an exception. The **set\_attr()** method allows you to set various attributes which influence the behavior of **convert()**. The currently supported attributes are *transliterate* and *discard\_ilseq*, e.g.:

```
$state = $converter->set_attr("transliterate");
```

See **iconvctl(3)** for details. To ensure portability to other iconv implementations you should first check for the availability of this method using **eval {}**, cf. the description of **set\_attr()** above.

This method should be considered experimental.

## ERRORS

If the conversion can't be initialized an exception is raised (using **croak()**).

### Handling of conversion errors

*Text::Iconv* provides a class attribute **raise\_error** and a corresponding class method for setting and getting its value. The handling of errors during conversion depends on the setting of this attribute. If **raise\_err or** is set to a true value, an exception is raised; otherwise, the **convert()** method only returns **undef**. By default **raise\_error** is false. Example usage:

```
Text::Iconv->raise_error(1);      # Conversion errors raise exceptions
Text::Iconv->raise_error(0);      # Conversion errors return undef
$a = Text::Iconv->raise_error();  # Get current setting
```

### Per-object handling of conversion errors

As an experimental feature, *Text::Iconv* also provides an instance attribute **raise\_error** and a corresponding method for setting and getting its value. If **raise\_err or** is **undef**, the class-wide settings apply. If **raise\_error** is 1 or 0 (true or false), the object settings override the class-wide settings.

Consult **iconv(3)** for details on errors that might occur.

### Conversion of undef

Converting **undef**, e.g.,

```
$converted = $converter->convert(undef);
```

always returns **undef**. This is not considered an error.

## NOTES

The supported codesets, their names, the supported conversions, and the quality of the conversions are all system-dependent.

## AUTHOR

Michael Piotrowski <mxp@dynamalabs.de>

## SEE ALSO

**iconv(1)**, **iconv(3)**