

NAME

vdpa-dev – vdpa device configuration

SYNOPSIS

vdpa dev [*OPTIONS*] { *COMMAND*| **help** }

OPTIONS := { -V[*ersion*] }

vdpa dev show [*DEV*]

vdpa dev help

vdpa dev add name *NAME* **mgmtdev** *MGMTDEV*

vdpa dev del *DEV*

DESCRIPTION

vdpa dev show - display vdpa device attributes

DEV - specifies the vdpa device to show. If this argument is omitted all devices are listed.

Format is:

VDPA_DEVICE_NAME

vdpa dev add - add a new vdpa device.

name *NAME*

Name of the new vdpa device to add.

mgmtdev *MGMTDEV*

Name of the management device to use for device addition.

vdpa dev del - Delete the vdpa device.

DEV - specifies the vdpa device to delete.

EXAMPLES

vdpa dev show

Shows the all vdpa devices on the system.

vdpa dev show foo

Shows the specified vdpa device.

vdpa dev add name foo mgmtdev vdpasim_net

Add the vdpa device named foo on the management device vdpasim_net.

vdpa dev del foo

Delete the vdpa device named foo which was previously created.

SEE ALSO

vdpa(8), **vdpa-mgmtdev(8)**,

AUTHOR

Parav Pandit <parav@nvidia.com>