

**NAME**

**npm-install-ci-test** – Install a project with a clean slate and run tests

**Synopsis**

```
npm install-ci-test
```

```
alias: npm ci
```

**Description**

This command runs **npm ci** followed immediately by **npm test**.

**Configuration**

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not
edit manually --> <!-- see lib/utils/config/definitions.js -->
```

**audit**

- Default: true
- Type: Boolean

When "true" submit audit reports alongside the current npm command to the default registry and all registries configured for scopes. See the documentation for `npm help audit` for details on what is submitted.

```
<!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->
```

**ignore-scripts**

- Default: false
- Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as **npm start**, **npm stop**, **npm restart**, **npm test**, and **npm run-script** will still run their intended script if **ignore-scripts** is set, but they will *not* run any pre- or post-scripts. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

**script-shell**

- Default: '/bin/sh' on POSIX systems, 'cmd.exe' on Windows
- Type: null or String

The shell to use for scripts run with the **npm exec**, **npm run** and **npm init <pkg>** commands. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->
```

**See Also**

- `npm help install-test`
- `npm help ci`
- `npm help test`