#### **NAME**

vlc, qvlc, svlc, nvlc, rvlc, cvlc - the VLC media player

#### **SYNOPSIS**

vlc [OPTIONS] [ITEMS]...

## **DESCRIPTION**

This manual page documents briefly the VLC multimedia player and server.

#### **OPTIONS**

**VLC** follows the usual GNU command line syntax, with long options starting with two dashes ('-'). For a precise description of options, please use "vlc —help".

The complete list of **VLC** options depends on what plugins are installed because they automatically add their own options. Please use "vlc —longhelp —advanced" for a complete list of available options.

#### **ITEMS**

**VLC** recognizes several URL-style items:

## \*.mpg, \*.vob, \*.avi, \*.mp3, \*.ogg, \*.opus

Various multimedia file formats

#### dvd://[<device>][@<raw device>][#[<title>][:[<chapter>][:<angle>]]]

DVD device (for instance dvd:///dev/dvd). The raw device is optional and must have been prepared beforehand.

## $vcd://[<device>][@{E|P|E|T|S}[<number>]]$

VCD device (for instance vcd:///dev/cdrom).

## udp://[@[<multicast address>][:<local port>]]

UDP stream, such as one sent by VLS or another VLC. Usually "udp://" is enough.

# http://<server address>[:<server port>]/[<file>]

HTTP stream

# rtsp://<server address>[:<server port>]/<stream name>

RTSP Video On Demand stream

## vlc://<command>

Execute a playlist command. Commands are: **pause** (pause execution of other items), and **quit** (close VLC).

# **ENVIRONMENT VARIABLES**

The following environment variables may affect VLC:

# DISPLAY

The X11 display server address.

# http\_proxy

The HTTP proxy server URL.

# OSSAUDIO\_DEV

The default audio output device, used by the OSSv4 output plugin.

## VLC\_DATA\_PATH

The directory containing VLC run-time data files (e.g. /usr/share/vlc).

Feb 14, 2005

## VLC\_PLUGIN\_PATH

An extra directory to load VLC plugins from.

# VLC\_VERBOSE

The level of verbosity for log messages (0: silent, 1: error/info, 2: warning, 3: debug).

## XDG\_CACHE\_DIR XDG\_CONFIG\_DIR XDG\_DATA\_DIR

The directories to store user cached data, user configuration files and user data files respectively.

# $\label{locuments_dir} \begin{tabular}{ll} xdg\_download\_dir & xdg\_music\_dir & xdg\_pictures\_dir & xdg\_video\_dir & xdg\_video\_di$

The directories to fetch or store user text files, downloads, music, pictures (i.e. snapshots), and video respectively.

# XDG\_SESSION\_COOKIE

The unique identifier of the desktop session, used by the PulseAudio output plugin.

#### **SEE ALSO**

Online documentation: http://www.videolan.org/doc/

#### **AUTHOR**

This manual page was written by Sam Hocevar <sam@zoy.org>, for the Debian GNU/Linux system (but may be used by others).

Feb 14, 2005