NPM-PREFIX(1) NPM-PREFIX(1)

NAME

```
npm-prefix - Display prefix
```

Synopsis

```
npm prefix [-g]
```

Note: This command is unaware of workspaces.

Description

Print the local prefix to standard output. This is the closest parent directory to contain a **package.json** file or **node_modules** directory, unless **-g** is also specified.

If $-\mathbf{g}$ is specified, this will be the value of the global prefix. See npm help **config** for more detail.

Example

```
npm prefix
/usr/local/projects/foo
npm prefix -g
/usr/local
```

Configuration

<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

global

Default: falseType: Boolean

Operates in "global" mode, so that packages are installed into the **prefix** folder instead of the current working directory. See npm help folders for more on the differences in behavior.

- packages are installed into the {prefix}/lib/node_modules folder, instead of the current working directory.
- bin files are linked to {prefix}/bin
- man pages are linked to {prefix}/share/man

```
<!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->
```

<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->

See Also

- · npm help root
- npm help bin
- npm help folders
- · npm help config
- · npm help npmrc

undefined NaN 1