

NAME

flatpak-remotes – List remote repositories

SYNOPSIS

flatpak remotes [OPTION...]

DESCRIPTION

Lists the known remote repositories, in priority order.

By default, both per-user and system-wide installations are shown. Use the **--user**, **--system** or **--installation** options to change this.

OPTIONS

The following options are understood:

-h, --help

Show help options and exit.

--user

Show the per-user configuration.

--system

Show the default system-wide configuration.

--installation=NAME

Show a system-wide installation by NAME among those defined in /etc/flatpak/installations.d/. Using **--installation=default** is equivalent to using **--system**.

-d, --show-details

Show more information for each repository in addition to the name. Equivalent to **--columns=all**.

--show-disabled

Show disabled repos.

-v, --verbose

Print debug information during command processing.

--ostree-verbose

Print OSTree debug information during command processing.

--columns=FIELD,...

Specify what information to show about each ref. You can list multiple fields, or use this option multiple times.

Append :s[tart], :m[iddle], :e[nd] or :f[ull] to column names to change ellipsization.

FIELDS

The following fields are understood by the **--columns** option:

name

Show the name of the remote

title

Show the title of the remote

url

Show the URL of the remote

filter

Show the path to the client-side filter of the remote.

collection

Show the collection ID of the remote

priority

Show the priority of the remote

options

 Show options

comment

 Show comment

description

 Show description

homepage

 Show homepage

icon

 Show icon

all

 Show all columns

help

 Show the list of available columns

Note that field names can be abbreviated to a unique prefix.

EXAMPLES

\$ flatpak remotes --user --show-details

testrepo Test Repository http://209.132.179.91/repo/ no-gpg-verify

SEE ALSO

flatpak(1), flatpak-remote-add(1), flatpak-remote-delete(1)