

NAME

jlink – assemble and optimize a set of modules and their dependencies into a custom runtime image

SYNOPSIS

jlink [*options*] **--module-path** *modulepath* **--add-modules** *module* [, *module*...]

options Command-line options separated by spaces. See **jlink Options**.

modulepath

The path where the **jlink** tool discovers observable modules. These modules can be modular JAR files, JMOD files, or exploded modules.

module The names of the modules to add to the runtime image. The **jlink** tool adds these modules and their transitive dependencies.

DESCRIPTION

The **jlink** tool links a set of modules, along with their transitive dependences, to create a custom runtime image.

Note:

Developers are responsible for updating their custom runtime images.

JLINK OPTIONS

--add-modules *mod* [, *mod*...]

Adds the named modules, *mod*, to the default set of root modules. The default set of root modules is empty.

--bind-services

Link service provider modules and their dependencies.

-c = {0|1|2} or **--compress**={0|1|2}

Enable compression of resources:

- 0: No compression
- 1: Constant string sharing
- 2: ZIP

--disable-plugin *pluginname*

Disables the specified plug-in. See **jlink Plug-ins** for the list of supported plug-ins.

--endian {**little**|**big**}

Specifies the byte order of the generated image. The default value is the format of your system's architecture.

-h or **--help**

Prints the help message.

--ignore-signing-information

Suppresses a fatal error when signed modular JARs are linked in the runtime image. The signature-related files of the signed modular JARs aren't copied to the runtime image.

--launcher *command=module* or **--launcher** *command=module/main*

Specifies the launcher command name for the module or the command name for the module and main class (the module and the main class names are separated by a slash (/)).

--limit-modules *mod* [, *mod*...]

Limits the universe of observable modules to those in the transitive closure of the named modules, **mod**, plus the main module, if any, plus any further modules specified in the **--add-modules** option.

--list-plugins

Lists available plug-ins, which you can access through command-line options; see **jlink Plug-ins**.

-p or **--module-path** *modulepath*

Specifies the module path.

If this option is not specified, then the default module path is `$JAVA_HOME/jmods`. This directory contains the `java.base` module and the other standard and JDK modules. If this option is specified but the `java.base` module cannot be resolved from it, then the `jlink` command appends `$JAVA_HOME/jmods` to the module path.

--no-header-files

Excludes header files.

--no-man-pages

Excludes man pages.

--output *path*

Specifies the location of the generated runtime image.

--save-opts *filename*

Saves `jlink` options in the specified file.

--suggest-providers [*name*, ...]

Suggest providers that implement the given service types from the module path.

--version

Prints version information.

@filename

Reads options from the specified file.

An options file is a text file that contains the options and values that you would typically enter in a command prompt. Options may appear on one line or on several lines. You may not specify environment variables for path names. You may comment out lines by prefixing a hash symbol (#) to the beginning of the line.

The following is an example of an options file for the `jlink` command:

```
#Wed Dec 07 00:40:19 EST 2016
--module-path mlib
--add-modules com.greetings
--output greetingsapp
```

JLINK PLUG-INS

Note:

Plug-ins not listed in this section aren't supported and are subject to change.

For plug-in options that require a *pattern-list*, the value is a comma-separated list of elements, with each element using one of the following forms:

- *glob-pattern*
- **glob:***glob-pattern*
- **regex:***regex-pattern*
- **@filename**
 - *filename* is the name of a file that contains patterns to be used, one pattern per line.

For a complete list of all available plug-ins, run the command `jlink --list-plugins`.

Plugin compress

Options

--compress={0|1|2}[:**filter**=*pattern-list*]

Description

Compresses all resources in the output image.

- Level 0: No compression
- Level 1: Constant string sharing
- Level 2: ZIP

An optional *pattern-list* filter can be specified to list the pattern of files to include.

Plugin **include-locales**

Options

```
--include-locales=langtag[,langtag]*
```

Description

Includes the list of locales where *langtag* is a BCP 47 language tag. This option supports locale matching as defined in RFC 4647. Ensure that you add the module `jdk.localedata` when using this option.

Example:

```
--add-modules jdk.localedata --include-locales=en,ja,*-IN
```

Plugin **order-resources**

Options

```
--order-resources=pattern-list
```

Description

Orders the specified paths in priority order. If *@filename* is specified, then each line in *pattern-list* must be an exact match for the paths to be ordered.

Example:

```
--order-resources=/module-info.class,@classlist,/java.base/java/lang/
```

Plugin **strip-debug**

Options

```
--strip-debug
```

Description

Strips debug information from the output image.

JLINK EXAMPLES

The following command creates a runtime image in the directory **greetingsapp**. This command links the module **com.greetings**, whose module definition is contained in the directory **mllib**.

```
jlink --module-path mllib --add-modules com.greetings --output greetingsapp
```

The following command lists the modules in the runtime image **greetingsapp**:

```
greetingsapp/bin/java --list-modules
com.greetings
java.base@11
java.logging@11
org.astro@1.0
```

The following command creates a runtime image in the directory **compressedrt** that's stripped of debug symbols, uses compression to reduce space, and includes French language locale information:

```
jlink --add-modules jdk.localedata --strip-debug --compress=2 --include-locales=fr --output compressedrt
```

The following example compares the size of the runtime image **compressedrt** with **fr_rt**, which isn't stripped of debug symbols and doesn't use compression:

```
jlink --add-modules jdk.localedata --include-locales=fr --output fr_rt

du -sh ./compressedrt ./fr_rt
23M      ./compressedrt
```

```
36M      ./fr_rt
```

The following example lists the providers that implement `java.security.Provider`:

```
jlink --suggest-providers java.security.Provider
```

Suggested providers:

```
java.naming provides java.security.Provider used by java.base
java.security.jgss provides java.security.Provider used by java.base
java.security.sasl provides java.security.Provider used by java.base
java.smartcardio provides java.security.Provider used by java.base
java.xml.crypto provides java.security.Provider used by java.base
jdk.crypto.cryptoki provides java.security.Provider used by java.base
jdk.crypto.ec provides java.security.Provider used by java.base
jdk.crypto.mscapi provides java.security.Provider used by java.base
jdk.security.jgss provides java.security.Provider used by java.base
```

The following example creates a custom runtime image named `mybuild` that includes only `java.naming` and `jdk.crypto.cryptoki` and their dependencies but no other providers. Note that these dependencies must exist in the module path:

```
jlink --add-modules java.naming,jdk.crypto.cryptoki --output mybuild
```

The following command is similar to the one that creates a runtime image named `greetingsapp`, except that it will link the modules resolved from root modules with service binding; see the `Configuration.resolveAndBind` method.

```
jlink --module-path mlib --add-modules com.greetings --output greetingsapp
```

The following command lists the modules in the runtime image `greetingsapp` created by this command:

```
greetingsapp/bin/java --list-modules
com.greetings
java.base@11
java.compiler@11
java.datatransfer@11
java.desktop@11
java.logging@11
java.management@11
java.management.rmi@11
java.naming@11
java.prefs@11
java.rmi@11
java.security.jgss@11
java.security.sasl@11
java.smartcardio@11
java.xml@11
java.xml.crypto@11
jdk.accessibility@11
jdk.charsets@11
jdk.compiler@11
jdk.crypto.cryptoki@11
jdk.crypto.ec@11
jdk.crypto.mscapi@11
jdk.internal.opt@11
jdk.jartool@11
jdk.javadoc@11
jdk.jdeps@11
jdk.jfr@11
```

```
jdk.jlink@11
jdk.localedata@11
jdk.management@11
jdk.management.jfr@11
jdk.naming.dns@11
jdk.naming.rmi@11
jdk.security.auth@11
jdk.security.jgss@11
jdk.zipfs@11
org.astro@1.0
```