

NAME

tracker3-status – Provide status and statistics on the data indexed

SYNOPSIS

```
tracker3 status
tracker3 status [[expression1]...]
tracker3 status --stat [-a] [[expression1]...]
```

DESCRIPTION

Display the status of the current index and data set. A summary of recorded failures during file metadata indexing is also displayed.

Providing a search expression will list the full details of the recorded failures matching the filename.

With the **--stat** option, displays statistics about the RDF classes and how many of each exist for data set that has been indexed. For example, "10 Folders".

OPTIONS

--stat[=*expression*]
By default, only common and useful classes are shown, e.g. "nfo:Document" or "nfo:Folder", for a full set of statistics, see the **--all** option.

If one or more *expression* arguments is given, the statistics returned are filtered to only show information those RDF types matching *expression* (case folded and matching accented variants). The RDF classes are detailed by the Nepomuk otology specification. A list of possible classes matching *expression*, see **tracker3 sparql -c**.

-a, --all

Display statistics about ALL RDF classes that exist in the database. Without this option only the common RDF classes will be shown, for example "nfo:Document" and "nfo:FileDataObject".

This option is implied if search terms are provided to filter ALL possible statistics.

SEE ALSO

tracker3-daemon(1), **tracker3-sparql(1)**, **tracker3-info(1)**.

- <http://nepomuk.semanticdesktop.org/>
- <http://www.w3.org/TR/rdf-sparql-query/>