

NAME

Dpkg::Control::FieldsCore – manage (list of official) control fields

DESCRIPTION

The module contains a list of fieldnames with associated meta-data explaining in which type of control information they are allowed. The types are the CTRL_* constants exported by Dpkg::Control.

FUNCTIONS

`$f = field_capitalize($field_name)`

Returns the field name properly capitalized. All characters are lowercase, except the first of each word (words are separated by a hyphen in field names).

`field_is_official($fname)`

Returns true if the field is official and known.

`field_is_allowed_in($fname, @types)`

Returns true (1) if the field `$fname` is allowed in all the types listed in the list. Note that you can use type sets instead of individual types (ex: CTRL_FILE_CHANGES | CTRL_CHANGELOG).

`field_allowed_in(A|B, C)` returns true only if the field is allowed in C and either A or B.

Undef is returned for non-official fields.

`field_transfer_single($from, $to, $field)`

If appropriate, copy the value of the field named `$field` taken from the `$from` Dpkg::Control object to the `$to` Dpkg::Control object.

Official fields are copied only if the field is allowed in both types of objects. Custom fields are treated in a specific manner. When the target is not among CTRL_PKG_SRC, CTRL_PKG_DEB or CTRL_FILE_CHANGES, then they are always copied as is (the X- prefix is kept). Otherwise they are not copied except if the target object matches the target destination encoded in the field name. The initial X denoting custom fields can be followed by one or more letters among “S” (Source: corresponds to CTRL_PKG_SRC), “B” (Binary: corresponds to CTRL_PKG_DEB) or “C” (Changes: corresponds to CTRL_FILE_CHANGES).

Returns undef if nothing has been copied or the name of the new field added to `$to` otherwise.

`field_transfer_all($from, $to)`

Transfer all appropriate fields from `$from` to `$to`. Calls **field_transfer_single()** on all fields available in `$from`.

Returns the list of fields that have been added to `$to`.

`field_ordered_list($type)`

Returns an ordered list of fields for a given type of control information. This list can be used to output the fields in a predictable order. The list might be empty for types where the order does not matter much.

`($source, $version) = field_parse_binary_source($ctrl)`

Parse the **Source** field in a binary package control stanza. The field contains the source package name where it was built from, and optionally a space and the source version enclosed in parenthesis if it is different from the binary version.

Returns a list with the `$source` name, and the source `$version`, or undef or an empty list when `$ctrl` does not contain a binary package control stanza. Neither `$source` nor `$version` are validated, but that can be done with **Dpkg::Package::pkg_name_is_illegal()** and **Dpkg::Version::version_check()**.

`field_list_src_dep()`

List of fields that contains dependencies-like information in a source Debian package.

field_list_pkg_dep()

List of fields that contains dependencies-like information in a binary Debian package. The fields that express real dependencies are sorted from the stronger to the weaker.

field_get_dep_type(\$field)

Return the type of the dependency expressed by the given field. Can either be “normal” for a real dependency field (Pre-Depends, Depends, ...) or “union” for other relation fields sharing the same syntax (Conflicts, Breaks, ...). Returns undef for fields which are not dependencies.

field_get_sep_type(\$field)

Return the type of the field value separator. Can be one of FIELD_SEP_UNKNOWN, FIELD_SEP_SPACE, FIELD_SEP_COMMA or FIELD_SEP_LINE.

field_register(\$field, \$allowed_types, %opts)

Register a new field as being allowed in control information of specified types. %opts is optional

field_insert_after(\$type, \$ref, @fields)

Place field after another one (\$ref) in output of control information of type \$type.

field_insert_before(\$type, \$ref, @fields)

Place field before another one (\$ref) in output of control information of type \$type.

CHANGES**Version 1.01 (dpkg 1.21.0)**

New function: **field_parse_binary_source()**.

Version 1.00 (dpkg 1.17.0)

Mark the module as public.