

**NAME**

flatpak-config – Manage configuration

**SYNOPSIS**

**flatpak config** [OPTION...]

**flatpak config** [OPTION...] **—set** KEY VALUE

**flatpak config** [OPTION...] **—unset**|**—get** KEY

**DESCRIPTION**

The flatpak config command shows or modifies the configuration of a flatpak installation. The following keys are supported:

*languages*

The languages that are included when installing Locale extensions. The value is a semicolon-separated list of two-letter language codes, or one of the special values \* or all. If this key is unset, flatpak defaults to including the *extra-languages* key and the current locale.

*extra-languages*

This key is used when languages is not set, and it defines extra locale extensions on top of the system configured languages. The value is a semicolon-separated list of locale identifiers (language, optional locale, optional codeset, optional modifier) as documented by **setlocale**(3) (for example, en;en\_DK;zh\_HK.big5hkscs;uz\_UZ.utf8@cyrillic).

For configuration of individual remotes, see **flatpak-remote-modify**(1). For configuration of individual applications, see **flatpak-override**(1).

**OPTIONS**

The following options are understood:

**—h, —help**

Show help options and exit.

**—list**

Print all keys and their values.

**—set**

Set key KEY to VALUE.

**—unset**

Unset key KEY.

**—get**

Print value of KEY.

**—user**

Configure per-user installation.

**—system**

Configure system-wide installation.

**—installation=NAME**

Configure the system-wide installation specified by NAME among those defined in /etc/flatpak/installations.d/. Using **—installation=default** is equivalent to using **—system**.

**—v, —verbose**

Print debug information during command processing.

**—ostree-verbose**

Print OSTree debug information during command processing.

**EXAMPLES**

**\$ flatpak config —set languages "sv;en;fi"**

**SEE ALSO****flatpak(1), flatpak-remote-modify(1), flatpak-override(1)**