### **NAME**

ppdpo – ppd message catalog generator (deprecated)

## **SYNOPSIS**

```
ppdpo [ -D name[=value] ] [ -I include-directory ] [ -o output-file ] source-file
```

## DESCRIPTION

**ppdpo** extracts UI strings from PPDC source files and updates either a GNU gettext or macOS strings format message catalog source file for translation. **This pr ogram is deprecated and will be removed in a future release of CUPS.** 

## **OPTIONS**

**ppdpo** supports the following options:

**-D** *name*[=*value*]

Sets the named variable for use in the source file. It is equivalent to using the #define directive in the source file.

-I include-directory

Specifies an alternate include directory. Multiple-*I* options can be supplied to add additional directories.

**−o** output-file

Specifies the output file. The supported extensions are .po or .po.gz for GNU gettext format message catalogs and .strings for macOS strings files.

## **NOTES**

PPD files are deprecated and will no longer be supported in a future feature release of CUPS. Printers that do not support IPP can be supported using applications such as **ippeveprinter**(1).

## **SEE ALSO**

ppdc(1), ppdhtml(1), ppdi(1), ppdmerge(1), ppdcfile(5), CUPS Online Help (http://localhost:631/help)

# **COPYRIGHT**

Copyright © 2021-2022 by OpenPrinting.