

NAME

getpcaps – display process capabilities

SYNOPSIS

getpcaps [optional args] *pid*...

DESCRIPTION

getpcaps displays the capabilities on the processes indicated by the *pid* value(s) given on the command line. *Apid* of 0 displays the capabilities of the process that is running **getpcaps** itself.

The capabilities are displayed in the **cap_from_text**(3) format.

Optional arguments:

--help or **--usage**

Displays usage information and exits.

--ugly or **--legacy**

Displays output in a somewhat ugly legacy format.

--verbose

Displays usage in a legacy-like format but not quite so ugly in modern default terminal fonts.

--iab Displays IAB tuple capabilities from the process. The output format here is the text format described in **cap_iab**(3). Double quotes encase the regular process capabilities and square brackets encase the IAB tuple. This format is also used by **captree**(8).

REPORTING BUGS

Please report bugs via:

https://bugzilla.kernel.org/buglist.cgi?component=libcap&list_id=1090757

SEE ALSO

capsh(1), **cap_from_text**(3), **cap_iab**(3), **capabilities**(7), **captree**(8), **getcap**(8), and **setcap**(8).

AUTHOR

This manual page was originally written by Robert Bihlmeyer <robbe@debian.org>, for the Debian GNU/Linux system (but may be used by others).