

NAME

`grub-syslinux2cfg` – transform syslinux config into grub.cfg

SYNOPSIS

grub-syslinux2cfg [*OPTION...*] *FILE*

DESCRIPTION

Transform syslinux config into GRUB one.

-c, --cwd=DIR

current directory of syslinux [default is parent directory of input file].

-i, --islinux

assume input is an islinux configuration file.

-o, --output=FILE

write output to FILE [default=stdout].

-p, --pxlinux

assume input is a pxlinux configuration file.

-r, --root=DIR

root directory of the syslinux disk [default=/].

-s, --syslinux

assume input is a syslinux configuration file.

-t, --target-root=DIR

root directory as it will be seen on runtime [default=/].

-T, --target-cwd=DIR

current directory of syslinux as it will be seen on runtime [default is parent directory of input file].

-v, --verbose

print verbose messages.

-, --help

give this help list

--usage

give a short usage message

-V, --version

print program version

Mandatory or optional arguments to long options are also mandatory or optional for any corresponding short options.

REPORTING BUGS

Report bugs to <bug-grub@gnu.org>.

SEE ALSO

grub-menulst2cfg(8)

The full documentation for **grub-syslinux2cfg** is maintained as a Texinfo manual. If the **info** and **grub-syslinux2cfg** programs are properly installed at your site, the command

info grub-syslinux2cfg

should give you access to the complete manual.