NAME
npm-logout – Log out of the registry

Synopsis
npm logout [−−registry=<url>] [−−scope=<@scope>]

Note: This command is unaware of workspaces.

Description
When logged into a registry that supports token−based authentication, tell the server to end this token's session. This will invalidate the token everywhere you're using it, not just for the current environment.

When logged into a legacy registry that uses username and password authentication, this will clear the credentials in your user configuration. In this case, it will *only* affect the current environment.

If −−**scope** is provided, this will find the credentials for the registry connected to that scope, if set.

Configuration
<!−− AUTOGENERATED CONFIG DESCRIPTIONS START −−> <!−− automatically generated, do not edit manually −−> <!−− see lib/utils/config/definitions.js −−>

registry
• Default: "https://registry.npmjs.org/"

• Type: URL

The base URL of the npm registry. <!−− automatically generated, do not edit manually −−> <!−− see lib/utils/config/definitions.js −−>

scope
• Default: the scope of the current project, if any, or ""

• Type: String

Associate an operation with a scope for a scoped registry.

Useful when logging in to or out of a private registry:

```
# log in, linking the scope to the custom registry
npm login −−scope=@mycorp −−registry=https://registry.mycorp.com

# log out, removing the link and the auth token
npm logout −−scope=@mycorp
```

This will cause **@mycorp** to be mapped to the registry for future installation of packages specified according to the pattern **@mycorp/package** .

This will also cause **npm init** to create a scoped package.

```
# accept all defaults, and create a package named "@foo/whatever",
# instead of just named "whatever"
npm init −−scope=@foo −−yes
```
<!−− automatically generated, do not edit manually −−> <!−− see lib/utils/config/definitions.js −−>

<!−− AUTOGENERATED CONFIG DESCRIPTIONS END −−>

See Also
• npm help adduser

• npm help registry

- npm help config
- npm help whoami