

NAME

init-d-script — interpreter for short and simple init.d scripts

DESCRIPTION

Generic init.d script framework to reduce the redundant code in `/etc/init.d/`. The goal is to create an init.d script that is Debian and LSB compliant. When the Debian policy conflicts with the LSB, the Debian policy takes precedence.

This is a simple example on how `init-d-script` can be used to start and stop a daemon with PID file support:

```
#!/bin/sh /lib/init/init-d-script
### BEGIN INIT INFO
# Provides:          atd
# Required-Start:    $syslog $time $remote_fs
# Required-Stop:     $syslog $time $remote_fs
# Default-Start:     2 3 4 5
# Default-Stop:      0 1 6
# Short-Description: run at jobs
# Description:       Debian init script to start the daemon
#                   running at jobs.
### END INIT INFO
DAEMON=/usr/sbin/atd
```

The following variables affect behaviour of an init script:

DAEMON	Path to daemon being started. If the init script is not supposed to start any kind of daemon, it should be set to “none” and the functions <code>do_start_override()</code> , <code>do_stop_override()</code> and <code>do_status_override()</code> should be defined instead.
DAEMON_ARGS	Additional arguments, passed to daemon during start.
DESC	Full name or short description of the daemon, printed on screen. If unset, this variable defaults to the “NAME” value.
NAME	Additional environment variables are sourced from <code>/etc/default/\${NAME}</code> . If unset, this variable defaults to the basename of the “DAEMON” value.
COMMAND_NAME	If this variable is set, it is used as argument to the <code>--name</code> option of <code>start-stop-daemon(8)</code> . It may be useful if the value of the “NAME” variable is longer than the command name length supported by the running kernel. If the value is verbatim “none”, the command name will not be used to match the processes. If unset, this variable defaults to the “NAME” value.
PIDFILE	Path to file where the process identifier of the started daemon will be stored during start. If the value is verbatim “none”, the process identifier will not be stored in any file. If this variable is not set, it gets a sensible default value, so it is rarely necessary to set this variable explicitly.
RELOAD_SIGNAL	Signal number or name (without the SIG prefix) that will be sent to the process on reload . If the daemon performs reload action upon receiving a SIGHUP signal, this variable should be set to “1” or “HUP”.

The variables `RELOAD_ARGS`, `START_ARGS` and `STOP_ARGS` are additional arguments, passed to `start-stop-daemon(8)` during reload, start and stop actions, to override the default options.

Additionally, it is possible to change the behaviour of the resulting shell script by overriding some of the internal functions. To do so, define function with an `_override` suffix. So, for example, to override the `do_status()` function, one should define a `do_status_override()` function. The *exception* to this

rule is the **do_reload()** function, whose override should be defined as-is, *without* the above-mentioned suffix.

Here is a control flow chart that explains what functions are called and when:

```

/etc/init.d/script start
do_start
do_start_prepare # no-op
do_start_cmd     # start-stop-daemon is called here
do_start_cleanup # no-op

/etc/init.d/script stop
do_stop
do_stop_prepare # no-op
do_stop_cmd     # start-stop-daemon is called here
do_stop_cleanup # no-op

/etc/init.d/script status
do_status

/etc/init.d/script reload
do_reload
do_usage
exit 3

/etc/init.d/script force-reload
do_force_reload
do_reload # if overridden
do_restart
do_restart_prepare
do_stop_cmd
do_start_cmd
do_restart_cleanup

/etc/init.d/script restart
do_force_restart
/etc/init.d/script try-restart
if do_status; then
do_restart
do_restart_prepare
do_stop_cmd # start-stop-daemon is called here
do_start_cmd # start-stop-daemon is called here
do_restart_cleanup

/etc/init.d/script <arg>
do_unknown <arg>
exit 3

/etc/init.d/script
do_usage

```

As can be seen, by default, the script does not support the **reload** action; it should be implemented by the script writer by defining a **do_reload()** function.

If `do_reload()` is not defined but `do_reload_cmd()` is, the latter will be called on **reload**, after `do_reload_prepare()` and before `do_reload_cleanup()`.

SEE ALSO

`inittab(8)`, `service(8)`, `update-rc.d(8)`.

AUTHORS

Petter Reinholdtsen <pere@debian.org>