

NAME

XtAppError, XtAppSetErrorHandler, XtAppSetWarningHandler, XtAppWarning – low-level error handlers

SYNTAX

```
#include <X11/Intrinsic.h>

void XtAppError(XtAppContext app_context, const char *message);

XtErrorHandler XtAppSetErrorHandler(XtAppContext app_context, XtErrorHandler handler);

XtErrorHandler XtAppSetWarningHandler(XtAppContext app_context, XtErrorHandler handler);

void XtAppWarning(XtAppContext app_context, const char *message);
```

ARGUMENTS

<i>app_context</i>	Specifies the application context.
<i>message</i>	Specifies the nonfatal error message that is to be reported.
<i>handler</i>	Specifies the new fatal error procedure, which should not return, or the nonfatal error procedure, which usually returns.
<i>message</i>	Specifies the message that is to be reported.

DESCRIPTION

The **XtAppError** function calls the installed error procedure and passes the specified message.

The **XtAppSetErrorHandler** function registers the specified procedure, which is called when a fatal error condition occurs.

The **XtAppSetWarningHandler** registers the specified procedure, which is called when a nonfatal error condition occurs.

The **XtAppWarning** function calls the installed nonfatal error procedure and passes the specified message.

SEE ALSO

XtAppGetErrorDatabase(3), XtAppErrorMsg(3)
X Toolkit Intrinsics – C Language Interface
Xlib – C Language X Interface