

NAME

dh_autotools-dev_restoreconfig – restore config.sub and config.guess

SYNOPSIS

dh_autotools-dev_restoreconfig [*debhelper options*]

DESCRIPTION

Deprecated: dh_autotools-dev_updateconfig and dh_autotools-dev_restoreconfig are deprecated and replaced by **dh_update_autotools_config**(1) and **dh_clean**(1) from debhelper. Please replace all uses of dh_autotools-dev_updateconfig with dh_update_autotools_config and then remove any use of dh_autotools-dev_restoreconfig.

dh_autotools-dev_restoreconfig restores the original **config.sub** and **config.guess** files that have been backed up by dh_autotools-dev_updateconfig under the names **config.sub.dh-orig** and **config.guess.dh-orig**.

EXAMPLES

dh_autotools-dev_restoreconfig is usually called indirectly in a rules file via the dh command.

```
%:
    dh $@ --with autotools_dev
```

It can also be directly called in the clean rule.

```
clean:
    dh_testdir
    dh_testroot
    [ ! -f Makefile ] || $(MAKE) clean
    dh_autotools-dev_restoreconfig
    dh_clean
```

SEE ALSO

debhelper(7), **dh**(1).

This program is meant to be used together with debhelper.

AUTHOR

Fabian Greffrath <fabian+debian@greffrath.com>