

## NAME

openssl-spkcac, spkcac – SPKAC printing and generating utility

## SYNOPSIS

**openssl spkcac** [**-help**] [**-in filename**] [**-out filename**] [**-key keyfile**] [**-keyform PEM|DER|ENGINE**] [**-passin arg**] [**-challenge string**] [**-pubkey**] [**-spkcac spkacname**] [**-spksect section**] [**-noout**] [**-verify**] [**-engine id**]

## DESCRIPTION

The **spkcac** command processes Netscape signed public key and challenge (SPKAC) files. It can print out their contents, verify the signature and produce its own SPKACs from a supplied private key.

## OPTIONS

### **-help**

Print out a usage message.

### **-in filename**

This specifies the input filename to read from or standard input if this option is not specified. Ignored if the **-key** option is used.

### **-out filename**

Specifies the output filename to write to or standard output by default.

### **-key keyfile**

Create an SPKAC file using the private key in **keyfile**. The **-in**, **-noout**, **-spksect** and **-verify** options are ignored if present.

### **-keyform PEM|DER|ENGINE**

Whether the key format is PEM, DER, or an engine-backed key. The default is PEM.

### **-passin password**

The input file password source. For more information about the format of **arg** see “Pass Phrase Options” in **openssl**(1).

### **-challenge string**

Specifies the challenge string if an SPKAC is being created.

### **-spkcac spkacname**

Allows an alternative name form the variable containing the SPKAC. The default is “SPKAC”. This option affects both generated and input SPKAC files.

### **-spksect section**

Allows an alternative name form the section containing the SPKAC. The default is the default section.

### **-noout**

Don’t output the text version of the SPKAC (not used if an SPKAC is being created).

### **-pubkey**

Output the public key of an SPKAC (not used if an SPKAC is being created).

### **-verify**

Verifies the digital signature on the supplied SPKAC.

### **-engine id**

Specifying an engine (by its unique **id** string) will cause **spkcac** to attempt to obtain a functional reference to the specified engine, thus initialising it if needed. The engine will then be set as the default for all available algorithms.

## EXAMPLES

Print out the contents of an SPKAC:

```
openssl spkcac -in spkcac.cnf
```

Verify the signature of an SPKAC:

```
openssl spkac -in spkac.cnf -noout -verify
```

Create an SPKAC using the challenge string “hello”:

```
openssl spkac -key key.pem -challenge hello -out spkac.cnf
```

Example of an SPKAC, (long lines split up for clarity):

```
SPKAC=MIG5MGUwXDANBgkqhkiG9w0BAQEFAANLADBIAkEA\
1cCoq2Wa3Ixs47uI7FPVwHVIPDx5yso105Y6zpozam135a\
8R0CpoRvkkigIyXfcCjiVi5oWk+6FfPaD03uPFoQIDAQAB\
FgVoZWxsbszANBgkqhkiG9w0BAQQFAANBAFpQtY/FoJdWkJ\
h1bEIYuc2EeM2KHTWPEepWYeawvHD0gQ3DngSC75YCWnnD\
dq+NQ3F+X4deMx9AaEglZtULwV4=
```

## NOTES

A created SPKAC with suitable DN components appended can be fed into the **ca** utility.

SPKACs are typically generated by Netscape when a form is submitted containing the **KEYGEN** tag as part of the certificate enrollment process.

The challenge string permits a primitive form of proof of possession of private key. By checking the SPKAC signature and a random challenge string some guarantee is given that the user knows the private key corresponding to the public key being certified. This is important in some applications. Without this it is possible for a previous SPKAC to be used in a “replay attack”.

## SEE ALSO

**ca** (1)

## COPYRIGHT

Copyright 2000–2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at <https://www.openssl.org/source/license.html>.