

NAME

devlink-dpipe – devlink dataplane pipeline visualization

SYNOPSIS

devlink [*OPTIONS*] **dpipe** { **table** | **header** } { *COMMAND* | **help** }

OPTIONS := { -V[*ersion*] }

devlink dpipe table show *DEV* [**name** *TABLE_NAME*]

devlink dpipe table set *DEV* **name** *TABLE_NAME*

devlink dpipe table dump *DEV* **name** *TABLE_NAME*

devlink dpipe header show *DEV*

devlink dpipe help

DESCRIPTION

devlink dpipe table show - display devlink dpipe table attributes

name *TABLE_NAME*

Specifies the table to operate on.

devlink dpipe table set - set devlink dpipe table attributes

name *TABLE_NAME*

Specifies the table to operate on.

devlink dpipe table dump - dump devlink dpipe table entries

name *TABLE_NAME*

Specifies the table to operate on.

devlink dpipe header show - display devlink dpipe header attributes

name *TABLE_NAME*

Specifies the table to operate on.

EXAMPLES

devlink dpipe table show pci/0000:01:00.0

Shows all dpipe tables on specified devlink device.

devlink dpipe table show pci/0000:01:00.0 **name** mlxsw_erif

Shows mlxsw_erif dpipe table on specified devlink device.

devlink dpipe table set pci/0000:01:00.0 **name** mlxsw_erif **counters_enabled** true

Turns on the counters on mlxsw_erif table.

devlink dpipe table dump pci/0000:01:00.0 **name** mlxsw_erif

Dumps content of mlxsw_erif table.

devlink dpipe header show pci/0000:01:00.0

Shows all dpipe headers on specified devlink device.

SEE ALSO

devlink(8), **devlink-dev(8)**, **devlink-monitor(8)**,

AUTHOR

Jiri Pirko <jiri@mellanox.com>