

NAME

fsck.minix – check consistency of Minix filesystem

SYNOPSIS

fsck.minix [options] *device*

DESCRIPTION

fsck.minix performs a consistency check for the Linux MINIX filesystem.

The program assumes the filesystem is quiescent. **fsck.minix** should not be used on a mounted device unless you can be sure nobody is writing to it. Remember that the kernel can write to device when it searches for files.

The *device* name will usually have the following form:

/dev/hda[1–63]	IDE disk 1
/dev/hdb[1–63]	IDE disk 2
/dev/sda[1–15]	SCSI disk 1
/dev/sdb[1–15]	SCSI disk 2

If the filesystem was changed, i.e., repaired, then **fsck.minix** will print "FILE SYSTEM HAS BEEN CHANGED" and will **sync(2)** three times before exiting. There is *no* need to reboot after check.

WARNING

fsck.minix should **not** be used on a mounted filesystem. Using **fsck.minix** on a mounted filesystem is very dangerous, due to the possibility that deleted files are still in use, and can seriously damage a perfectly good filesystem! If you absolutely have to run **fsck.minix** on a mounted filesystem, such as the root filesystem, make sure nothing is writing to the disk, and that no files are "zombies" waiting for deletion.

OPTIONS

-l, --list

List all filenames.

-r, --repair

Perform interactive repairs.

-a, --auto

Perform automatic repairs. This option implies **--repair** and serves to answer all of the questions asked with the default. Note that this can be extremely dangerous in the case of extensive filesystem damage.

-v, --verbose

Be verbose.

-s, --super

Output super-block information.

-m, --uncleared

Activate MINIX-like "mode not cleared" warnings.

-f, --force

Force a filesystem check even if the filesystem was marked as valid. Marking is done by the kernel when the filesystem is unmounted.

-h, --help

Display help text and exit.

-V, --version

Print version and exit.

DIAGNOSTICS

There are numerous diagnostic messages. The ones mentioned here are the most commonly seen in normal usage.

If the device does not exist, **fsck.minix** will print "unable to read super block". If the device exists, but is not a MINIX filesystem, **fsck.minix** will print "bad magic number in super-block".

EXIT STATUS

The exit status returned by **fsck.minix** is the sum of the following:

0

No errors

3

Filesystem errors corrected, system should be rebooted if filesystem was mounted

4

Filesystem errors left uncorrected

7

Combination of exit statuses 3 and 4

8

Operational error

16

Usage or syntax error

AUTHORS

[Linus Torvalds](mailto:torvalds@cs.helsinki.fi) <torvalds@cs.helsinki.fi>. Exit status values by [Rik Faith](mailto:faith@cs.unc.edu) <faith@cs.unc.edu>

Added support for filesystem valid flag: [Dr. Wettstein](mailto:greg%wind.uucp@plains.nodak.edu) <greg%wind.uucp@plains.nodak.edu>.

Check to prevent fsck of mounted filesystem added by [Daniel Quinlan](mailto:quinlan@yggdrasil.com)

<quinlan@yggdrasil.com>. Minix v2 fs support by [Andreas Schwab](mailto:schwab@issan.informatik.uni-dortmund.de)

<schwab@issan.informatik.uni-dortmund.de>, updated by [Nicolai Langfeldt](mailto:Nicolai.Langfeldt@math.uio.no)

<janl@math.uio.no>. Portability patch by [Russell King](mailto:rmk@ecs.soton.ac.uk) <rmk@ecs.soton.ac.uk>.

SEE ALSO

fsck(8), **fsck.ext2(8)**, **mkfs(8)**, **mkfs.ext2(8)**, **mkfs.minix(8)**, **reboot(8)**

REPORTING BUGS

For bug reports, use the issue tracker at <https://github.com/util-linux/util-linux/issues>.

AVAILABILITY

The **fsck.minix** command is part of the util-linux package which can be downloaded from

[Linux Kernel Archive](https://www.kernel.org/pub/linux/utils/util-linux/) <<https://www.kernel.org/pub/linux/utils/util-linux/>>.