

NAME

flatpak-build-sign – Sign an application or runtime

SYNOPSIS

flatpak build-sign [OPTION...] LOCATION ID [BRANCH]

DESCRIPTION

Signs the commit for a specified application or runtime in a local repository. LOCATION is the location of the repository. ID is the name of the application, or runtime if **--runtime** is specified. If BRANCH is not specified, it is assumed to be "master".

Applications can also be signed during build-export, but it is sometimes useful to add additional signatures later.

OPTIONS

The following options are understood:

-h, --help

Show help options and exit.

--gpg-sign=KEYID

Sign the commit with this GPG key. This option can be used multiple times.

--gpg-homedir=PATH

GPG Homedir to use when looking for keyrings

--runtime

Sign a runtime instead of an app.

--arch=ARCH

The architecture to use. See **flatpak --supported-arches** for architectures supported by the host.

-v, --verbose

Print debug information during command processing.

--ostree-verbose

Print OSTree debug information during command processing.

EXAMPLES

```
$ flatpak build-sign --gpg-sign=D8BA6573DDD2418027736F1BC33B315E53C1E9D6 /some/repo  
org.my.App
```

SEE ALSO

ostree(1), **flatpak(1)**, **flatpak-build-export(1)**, **flatpak-build(1)**,