

NAME

roff2html – transform roff code into html mode

SYNOPSIS

roff2html [*groffer-option* ...] [--] [*filespec* ...]

roff2html -h

roff2html --help

roff2html -v

roff2html --version

The options **-v** and **--version** print the version information of the program to standard output and exit. The options **-h** and **--help** print a usage information of the program to standard output and stop the program instantly.

All other options are assumed to be **groffer** options. They are internally passed to **groffer**. They override the behavior of the program. The options are optional, they can be omitted.

The *filespec* arguments correspond to the *filespec* arguments of **groffer**. So they are either the names of existing, readable files or – for standard input, or the name of a man page or a **groffer**(1) man page search pattern. If no *filespec* is specified standard input is assumed automatically.

DESCRIPTION

roff2html transforms *roff* code into *html* mode. Print the result to standard output.

There are more of these programs for generating other formats of *roff* input.

roff2dvi(1)

is for *dvi* mode.

roff2pdf(1)

outputs *pdf* mode.

roff2ps(1)

prints *PostScript* format to standard output.

roff2text(1)

generates text output in the **groff** device *latin1*.

roff2x(1)

prints the output in the **groff** device **X** that is suitable for programs like **gxditview**(1) or **xditview**(1).

AUTHORS

roff2html was written by Bernd Warken <groff-bernd.warken-72@web.de>.

SEE ALSO

groff(1), **groffer**(1), **roff2dvi**(1), **roff2pdf**(1), **roff2ps**(1), **roff2text**(1), **roff2x**(1), **gxditview**(1).