

NAME

npm-bugs – Report bugs for a package in a web browser

Synopsis

```
npm bugs [<pkgname> [<pkgname> ...]]
```

aliases: issues

Description

This command tries to guess at the likely location of a package's bug tracker URL or the **mailto** URL of the support email, and then tries to open it using the **--browser** config param. If no package name is provided, it will search for a **package.json** in the current folder and use the **name** property.

Configuration

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not
edit manually --> <!-- see lib/utils/config/definitions.js -->
```

browser

- Default: OS X: **"open"**, Windows: **"start"**, Others: **"xdg-open"**
- Type: null, Boolean, or String

The browser that is called by npm commands to open websites.

Set to **false** to suppress browser behavior and instead print urls to terminal.

Set to **true** to use default system URL opener. <!-- automatically generated, do not edit manually -->
<!-- see lib/utils/config/definitions.js -->

registry

- Default: **"https://registry.npmjs.org/"**
- Type: URL

The base URL of the npm registry. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->
```

See Also

- npm help docs
- npm help view
- npm help publish
- npm help registry
- npm help config
- npm help npmrc
- npm help package.json