

NAME**npm-restart** – Restart a package**Synopsis**

npm restart [-- <args>]

Description

This restarts a project. It is equivalent to running **npm run-script restart**.

If the current project has a **"restart"** script specified in **package.json**, then the following scripts will be run:

1. prerestart
2. restart
3. postrestart

If it does *not* have a **"restart"** script specified, but it does have **stop** and/or **start** scripts, then the following scripts will be run:

1. prerestart
2. prestop
3. stop
4. poststop
5. prestart
6. start
7. poststart
8. postrestart

Configuration

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS START --> <!-- automatically generated, do not
edit manually --> <!-- see lib/utils/config/definitions.js -->
```

ignore-scripts

- Default: false
- Type: Boolean

If true, npm does not run scripts specified in package.json files.

Note that commands explicitly intended to run a particular script, such as **npm start**, **npm stop**, **npm restart**, **npm test**, and **npm run-script** will still run their intended script if **ignore-scripts** is set, but they will *not* run any pre- or post-scripts. <!-- automatically generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

script-shell

- Default: '/bin/sh' on POSIX systems, 'cmd.exe' on Windows
- Type: null or String

The shell to use for scripts run with the **npm exec**, **npm run** and **npm init <pkg>** commands. <!-- auto-generated, do not edit manually --> <!-- see lib/utils/config/definitions.js -->

```
<!-- AUTOGENERATED CONFIG DESCRIPTIONS END -->
```

See Also

- npm help run-script
- npm help scripts
- npm help test
- npm help start
- npm help stop
- npm help restart