

NAME

openssl-passwd, passwd – compute password hashes

SYNOPSIS

```
openssl passwd [-help] [-crypt] [-1] [-apr1] [-aixmd5] [-5] [-6] [-salt string] [-in file] [-stdin]
[-noverify] [-quiet] [-table] [-rand file...] [-writerand file] {password}
```

DESCRIPTION

The **passwd** command computes the hash of a password typed at run-time or the hash of each password in a list. The password list is taken from the named file for option **-in file**, from stdin for option **-stdin**, or from the command line, or from the terminal otherwise.

OPTIONS**-help**

Print out a usage message.

-crypt

Use the **crypt** algorithm (default).

-1 Use the MD5 based BSD password algorithm **1**.

-apr1

Use the **apr1** algorithm (Apache variant of the BSD algorithm).

-aixmd5

Use the **AIX MD5** algorithm (AIX variant of the BSD algorithm).

-5

-6 Use the **SHA256** / **SHA512** based algorithms defined by Ulrich Drepper. See <https://www.akkadia.org/drepper/SHA-crypt.txt>.

-salt *string*

Use the specified salt. When reading a password from the terminal, this implies **-noverify**.

-in *file*

Read passwords from *file*.

-stdin

Read passwords from **stdin**.

-noverify

Don't verify when reading a password from the terminal.

-quiet

Don't output warnings when passwords given at the command line are truncated.

-table

In the output list, prepend the cleartext password and a TAB character to each password hash.

-rand *file...*

A file or files containing random data used to seed the random number generator. Multiple files can be specified separated by an OS-dependent character. The separator is **;** for MS-W indows, **,** for OpenVMS, and **:** for all others.

[-writerand *file*]

Writes random data to the specified *file* upon exit. This can be used with a subsequent **-rand** flag.

EXAMPLES

```
% openssl passwd -crypt -salt xx password
xxj31ZMTZzkVA
```

```
% openssl passwd -1 -salt xxxxxxxxx password
$1$xxxxxxxxx$UYCIxa628.9qXjpQCjM4a.
```

```
% openssl passwd -apr1 -salt xxxxxxxxx password
```

```
$apr1$xxxxxxxx$dxHfLAsjHkDRmG83UXe8K0
```

```
% openssl passwd -aixmd5 -salt xxxxxxxx password  
xxxxxxxx$8Oaipk/GPKhC64w/YVeFD/
```

COPYRIGHT

Copyright 2000–2021 The OpenSSL Project Authors. All Rights Reserved.

Licensed under the OpenSSL license (the “License”). You may not use this file except in compliance with the License. You can obtain a copy in the file LICENSE in the source distribution or at [<https://www.openssl.org/source/license.html>](https://www.openssl.org/source/license.html).