

**NAME**

update-default-ispell – update default ispell dictionary

**SYNOPSIS**

```
update-default-ispell [--skip-symlinks] [--triggered]
```

**DESCRIPTION**

WARNING: Not to be used from the command line unless you know very well what you are doing.

This program is intended to be called from ispell dictionary package postinst, from **select-default-ispell** or from dictionaries-common postinst.

When called under dpkg control with the **--trigger** option the script is run normally, otherwise the dictionaries-common **update-default-ispell** trigger is enabled for later run.

With the **--skip-symlinks** option the symlinks setting is skipped. This is needed for **update-default-ispell** when called from dictionaries-common postinst, since autobuilt hashes may not yet be available.

When run normally (from the command line or with **--trigger**) this script rebuilds the info at */var/cache/dictionaries-common/ispell.db* after files under */var/lib/dictionaries-common/ispell*, reads the system default from the debconf database and unless disabled, set default symlinks in */etc/dictionaries-common* pointing to the appropriate files in */usr/lib/ispell/*.

For ispell this script also updates the system-wide setting */etc/dictionaries-common/ispell-default* and the emacs, jed, and SquirrelMail support after known info.

**OPTIONS**

<b>--skip-symlinks</b>	Do not try to set symlinks at <i>/etc/dictionaries-common</i> dir.
<b>--triggered</b>	Run all the code instead of trying to enable update-default-ispell trigger

**SEE ALSO**

The dictionaries-common policy document

**AUTHORS**

Rafael Laboissiere, Agustin Martin Domingo