

NAME

log2, log2f, log2l – base-2 logarithmic function

LIBRARY

Math library (*libm*, *-lm*)

SYNOPSIS

```
#include <math.h>
```

```
double log2(double x);
```

```
float log2f(float x);
```

```
long double log2l(long double x);
```

Feature Test Macro Requirements for glibc (see **feature_test_macros(7)**):

```
log2(), log2f(), log2l():
```

```
_ISOC99_SOURCE || _POSIX_C_SOURCE >= 200112L
```

DESCRIPTION

These functions return the base 2 logarithm of x .

RETURN VALUE

On success, these functions return the base 2 logarithm of x .

For special cases, including where x is 0, 1, negative, infinity, or NaN, see **log(3)**.

ERRORS

See **math_error(7)** for information on how to determine whether an error has occurred when calling these functions.

For a discussion of the errors that can occur for these functions, see **log(3)**.

VERSIONS

These functions were added in glibc 2.1.

ATTRIBUTES

For an explanation of the terms used in this section, see **attributes(7)**.

Interface	Attribute	Value
log2(), log2f(), log2l()	Thread safety	MT-Safe

STANDARDS

C99, POSIX.1-2001, POSIX.1-2008.

The variant returning *double* also conforms to SVr4, 4.3BSD.

SEE ALSO

cbrt(3), **clog2(3)**, **log(3)**, **log10(3)**, **sqrt(3)**