

**NAME**

sane-tamarack – SANE backend for Tamarack flatbed scanners

**DESCRIPTION**

The **sane-tamarack** library implements a SANE (Scanner Access Now Easy) backend that provides access to the following Tamarack flatbed scanners:

Artiscan 6000C  
Artiscan 8000C  
Artiscan 12000C

**DEVICE NAMES**

This backend expects device names of the form:

*special*

Where *special* is the path-name for the special device that corresponds to a SCSI scanner. The special device name must be a generic SCSI device or a symlink to such a device. The program **sane-find-scanner**(1) helps to find out the correct device. Under Linux, such a device name could be */dev/sga* or */dev/sge*, for example. See **sane-scsi**(5) for details.

**FILES**

*/etc/sane.d/tamarack.conf*

The backend configuration file (see also description of **SANE\_CONFIG\_DIR** below).

*/usr/lib/x86\_64-linux-gnu/sane/libsane-tamarack.a*

The static library implementing this backend.

*/usr/lib/x86\_64-linux-gnu/sane/libsane-tamarack.so*

The shared library implementing this backend (present on systems that support dynamic loading).

**ENVIRONMENT****SANE\_CONFIG\_DIR**

This environment variable specifies the list of directories that may contain the configuration file. On \*NIX systems, the directories are separated by a colon (':'), under OS/2, they are separated by a semi-colon (';'). If this variable is not set, the configuration file is searched in two default directories: first, the current working directory (".") and then in */etc/sane.d*. If the value of the environment variable ends with the directory separator character, then the default directories are searched after the explicitly specified directories. For example, setting **SANE\_CONFIG\_DIR** to */tmp/config:* would result in directories *tmp/config*, *.*, and */etc/sane.d* being searched (in this order).

**SANE\_DEBUG\_TAMARACK**

If the library was compiled with debug support enabled, this environment variable controls the debug level for this backend. Higher debug levels increase the verbosity of the output.

Example: `export SANE_DEBUG_TAMARACK=4`

**SEE ALSO**

**sane**(7), **sane-find-scanner**(1), **sane-scsi**(5)

**AUTHOR**

Roger Wolff