

**NAME**

grub-mknetdir – prepare a GRUB netboot directory.

**SYNOPSIS**

**grub-mknetdir** [*OPTION*...]

**DESCRIPTION**

Prepares GRUB network boot images at net\_directory/subdir assuming net\_directory being TFTP root.

**--compress=***no|xz|gz|lzo*

compress GRUB files [optional]

**--disable-shim-lock**

disable shim\_lock verifier

**--dtb=***FILE*

embed a specific DTB

**-d, --directory=***DIR*

use images and modules under DIR [default=/usr/lib/grub/<platform>]

**--fonts=***FONTs*

install FONTs [default=unicode]

**--install-modules=***MODULEs*

install only MODULEs and their dependencies [default=all]

**-k, --pubkey=***FILE*

embed FILE as public key for signature checking

**--locale-directory=***DIR* use translations under DIR

[default=/usr/share/locale]

**--locales=***LOCALES*

install only LOCALES [default=all]

**--modules=***MODULEs*

pre-load specified modules MODULEs

**--sbat=***FILE*

SBAT metadata

**--themes=***THEMES*

install THEMES [default=starfield]

**-v, --verbose**

print verbose messages.

**--core-compress=***xz|none|auto*

choose the compression to use for core image

**--net-directory=***DIR*

root directory of TFTP server

**--subdir=***DIR*

relative subdirectory on network server

**-, --help**

give this help list

**--usage**

give a short usage message

**-V, --version**

print program version

Mandatory or optional arguments to long options are also mandatory or optional for any corresponding short options.

Prepares GRUB network boot images at `net_directory/subdir` assuming `net_directory` being TFTP root.

## REPORTING BUGS

Report bugs to <bug-grub@gnu.org>.

## SEE ALSO

**grub-mkimage**(1)

The full documentation for **grub-mknetdir** is maintained as a Texinfo manual. If the **info** and **grub-mknetdir** programs are properly installed at your site, the command

**info grub-mknetdir**

should give you access to the complete manual.