

NAME

kcookiejar5 – Command line interface to the KDE HTTP cookie daemon

SYNOPSIS

kcookiejar5 [-h, --help] [-v, --version] [--shutdown] [--remove *domain*] [--remove-all] [--reload-config]

DESCRIPTION

kcookiejar5 is a command line interface to the HTTP cookie store used by KDE, a D-Bus service to store/retrieve/clean cookies.

OPTIONS

-h--help

Show help about options.

-v--version

Show version information.

--shutdown

Shut down cookie jar and the D-Bus service.

--remove *domain*

Removes cookies for *domain* from the cookie jar.

--remove-all

Removes all the cookies from the cookie jar.

--reload-config

Reloads the configuration file.

USAGE

kcookiejar5 is a command line tool to access the kded module which manages cookies in Konqueror and other KDE applications.

When started without parameters it loads the kded module to provide the D-Bus interface to store cookies.

When **kcookiejar5** is started with some parameters, it does additional tasks to the cookies jar it provides, like removing the cookies from one *domain*.

SEE ALSO

kf5options(7), *qt5options(7)*

BUGS

Please use [KDE's bugtracker](#)^[1] to report bugs.

AUTHORS

Waldo Bastian <bastian@kde.org>

Author.

Dawit Alemayehu <adawit@kde.org>

Author.

NOTES

1. KDE's bugtracker
<https://bugs.kde.org>