

FEDERAL STATE AUTONOMOUS EDUCATIONAL  
INSTITUTION OF HIGHER EDUCATION

ITMO UNIVERSITY

Report

MPI. Assignments 9, 10, 11

Parallel algorithms for the analysis and synthesis of data

Performed by  
Aleksandr Shirokov

J4133c

Accepted by  
Petr Andriushchenko

Deadline: 21.12.21

St. Petersburg  
2021

# Contents

<b>1</b>	<b>Assignments</b>	<b>2</b>
1.1	Assignment 9. MPI_Reduce. . . . .	2
1.1.1	Formulation of the problem . . . . .	2
1.1.2	Example of launch parameters and output. Detailed description of solution .	2
1.2	Assignment 10. MPI. Sending and receiving messages without blocking. Ring exchange using non-blocking operations. . . . .	3
1.2.1	Formulation of the problem . . . . .	3
1.2.2	Example of launch parameters and output. Detailed description of solution .	3
1.3	Appendix . . . . .	4

# 1 Assignments

## 1.1 Assignment 9. MPI\_Reduce.

### 1.1.1 Formulation of the problem

### 1.1.2 Example of launch parameters and output. Detailed description of solution

Code for assignment 9 is [here](#).

Compilation example: `MPIC++ -O ./CPF/8.O ASSIGNMENT8.C`

Launch example: `MPIRUN -OVERSUBSCRIBE -NP 2 ./CPF/8.O`

Let's move to the the code and explain how it works.

## 1.2 Assignment 10. MPI. Sending and receiving messages without blocking. Ring exchange using non-blocking operations.

### 1.2.1 Formulation of the problem

Complete the program ASSIGNMENT10.C. Compile and run it.  
Study the code carefully and explain how it works.

### 1.2.2 Example of launch parameters and output. Detailed description of solution

Code for assignment 10 is [here](#).

Compilation example: `MPIC++ -O ./CPF/10.o ASSIGNMENT10.C`

Launch example: `MPIRUN -OVERSUBSCRIBE -NP 10 ./CPF/10.o`

```
aptmess@improfeo: ~/ITMO/parallel_algorithms/HT/hw_mpi
(base) aptmess@improfeo:~/ITMO/parallel_algorithms/HT/hw_mpi$ mpirun --oversubscribe -np 10 ./cpf/10.o
9 (previous) -> 0 (current) -> 1 (next)
0 (previous) -> 1 (current) -> 2 (next)
1 (previous) -> 2 (current) -> 3 (next)
2 (previous) -> 3 (current) -> 4 (next)
3 (previous) -> 4 (current) -> 5 (next)
4 (previous) -> 5 (current) -> 6 (next)
5 (previous) -> 6 (current) -> 7 (next)
6 (previous) -> 7 (current) -> 8 (next)
7 (previous) -> 8 (current) -> 9 (next)
8 (previous) -> 9 (current) -> 0 (next)
(base) aptmess@improfeo:~/ITMO/parallel_algorithms/HT/hw_mpi$ _
```

Let's move to the the code and explain how it works.

```
1  #include <iostream>
2  #include "mpi.h"
3
4  using namespace std;
5  int main(int argc, char **argv)
6  {
7      int rank, size, prev, next;
8      int buf[2];
9      MPI_Init(&argc, &argv);
10     MPI_Request reqs[4];
11     MPI_Status stats[4];
12     MPI_Comm_size(MPI_COMM_WORLD, &size);
13     MPI_Comm_rank(MPI_COMM_WORLD, &rank);
14     prev = rank - 1;
15     next = rank + 1;
16     if (rank == 0) prev = size - 1;
17     if (rank == size - 1) next = 0;
18     MPI_Irecv(&buf[0], 1, MPI_INT, prev, 5, MPI_COMM_WORLD, &reqs[0]);
19     MPI_Irecv(&buf[1], 1, MPI_INT, next, 6, MPI_COMM_WORLD, &reqs[1]);
20     MPI_Isend(&rank, 1, MPI_INT, prev, 6, MPI_COMM_WORLD, &reqs[2]);
21     MPI_Isend(&rank, 1, MPI_INT, next, 5, MPI_COMM_WORLD, &reqs[3]);
22     MPI_Waitall(4, reqs, stats);
23
24     //Your code here.
25     //Here you need to display the number of the current process, and what it receives from the previous and next processes.
26     cout << buf[0] << " (previous)" << " -> " << rank << " (current)" << " -> " << buf[1] << " (next)" << '\n' << endl;
27     MPI_Finalize();
28 }
```

### Assignment 10

The overall goal of the program is that all processes exchange messages with their nearest neighbors (on the left - previous, on the right - next) in accordance with the topology of the ring.

With `MPI_WAITALL` the execution of the process is blocked until all exchange operations on the specified `REQS` identifiers (lines 18-21) are completed and if the error exists in this operations, then the error field in the `STATS` array elements will be set to the appropriate value. In lines 18–21 there are operations `MPI_Irecv` and `MPI_Isend` which are equal to previous functions `MPI_RECV` and `MPI_SEND` but in this functions the return from the function occurs immediately after the initialization of the receiving/transmitting process without waiting for the receipt/ processing of the entire message, so we can solve the problem with blocking operations in `MPI_SEND` and `MPI_RECV`. In this lines the process waiting for their nearest neighbours and save information in `int` array `BUF` and send information about yourself's rank to previous and next. The result is displayed on screens - ring topology works.

### 1.3 Appendix

The link to the source code which is placed on my [github](#).