

# CS738: Advanced Compiler Optimizations

## Flow Graph Theory

Amey Karkare

karkare@cse.iitk.ac.in

<http://www.cse.iitk.ac.in/~karkare/cs738>

Department of CSE, IIT Kanpur



# Agenda

- ▶ Speeding up DFA
- ▶ Depth of a flow graph
- ▶ Natural Loops

# Acknowledgement

Rest of the slides based on the material at

<http://infolab.stanford.edu/~ullman/dragon/w06/w06.html>

# Speeding up DFA

- ▶ Proper ordering of nodes of a flow graph speeds up the iterative algorithms: **depth-first ordering**.

# Speeding up DFA

- ▶ Proper ordering of nodes of a flow graph speeds up the iterative algorithms: **depth-first ordering**.
- ▶ “Normal” flow graphs have a surprising property — **reducibility** — that simplifies several matters.

# Speeding up DFA

- ▶ Proper ordering of nodes of a flow graph speeds up the iterative algorithms: **depth-first ordering**.
- ▶ “Normal” flow graphs have a surprising property — **reducibility** — that simplifies several matters.
- ▶ Outcome: few iterations “normally” needed.

# Depth-First Search

- ▶ Start at entry.

# Depth-First Search

- ▶ Start at entry.
- ▶ If you can follow an edge to an unvisited node, do so.



# Depth-First Search

- ▶ Start at entry.
- ▶ If you can follow an edge to an unvisited node, do so.
- ▶ If not, backtrack to your *parent* (node from which you were visited).


# Depth-First Spanning Tree (DFST)

- ▶ Root = *Entry*.


# Depth-First Spanning Tree (DFST)

- ▶ Root = *Entry*.
- ▶ Tree edges are the edges along which we first visit the node at the head.


# DFST Example




# DFST Example




# DFST Example



# DFST Example



# DFST Example






# Depth-First Node Order

- ▶ The reverse of the order in which a DFS **retreats** from the nodes.

# Depth-First Node Order

- ▶ The reverse of the order in which a DFS **retreats** from the nodes.
- ▶ Alternatively, reverse of postorder traversal of the tree.

# DF Order Example



# Four Kind of Edges

1. Tree edges.

# Four Kind of Edges

1. Tree edges.
2. **Forward edges**: node to proper descendant.

# Four Kind of Edges

1. Tree edges.
2. **Forward edges**: node to proper descendant.
3. **Retreating edges**: node to ancestor.

# Four Kind of Edges

1. Tree edges.
2. **Forward edges**: node to proper descendant.
3. **Retreating edges**: node to ancestor.
4. **Cross edges**: between two node, niether of which is an ancestor of the other.

# A Little Magic

- ▶ Of these edges, only retreating edges go from high to low in DF order.




# A Little Magic

- ▶ Of these edges, only retreating edges go from high to low in DF order.
- ▶ Most surprising: all cross edges go right to left in the DFST.


# A Little Magic

- ▶ Of these edges, only retreating edges go from high to low in DF order.
- ▶ Most surprising: all cross edges go right to left in the DFST.
  - ▶ Assuming we add children of any node from the left.


## Example: Non-Tree Edges




## Example: Non-Tree Edges



## Example: Non-Tree Edges



## Example: Non-Tree Edges



# Roadmap

- ▶ “Normal” flow graphs are “**reducible**.”

# Roadmap

- ▶ “Normal” flow graphs are “**reducible**.”
- ▶ “**Dominators**” needed to explain reducibility.



# Roadmap

- ▶ “Normal” flow graphs are “**reducible**.”
- ▶ “**Dominators**” needed to explain reducibility.
- ▶ In reducible flow graphs, loops are well defined, retreating edges are unique (and called “**back**” edges).

# Roadmap

- ▶ “Normal” flow graphs are “**reducible**.”
- ▶ “**Dominators**” needed to explain reducibility.
- ▶ In reducible flow graphs, loops are well defined, retreating edges are unique (and called “**back**” edges).
- ▶ Leads to relationship between DF order and efficient iterative algorithm.

# Dominators

- ▶ Node  $d$  **dominates** node  $n$  if every path from the *Entry* to  $n$  goes through  $d$ .

# Dominators

- ▶ Node  $d$  **dominates** node  $n$  if every path from the *Entry* to  $n$  goes through  $d$ .
- ▶ [Exercise] A forward-intersection iterative algorithm for finding dominators.

# Dominators

- ▶ Node  $d$  **dominates** node  $n$  if every path from the *Entry* to  $n$  goes through  $d$ .
- ▶ [Exercise] A forward-intersection iterative algorithm for finding dominators.
- ▶ Quick observations:


# Dominators

- ▶ Node  $d$  **dominates** node  $n$  if every path from the *Entry* to  $n$  goes through  $d$ .
- ▶ [Exercise] A forward-intersection iterative algorithm for finding dominators.
- ▶ Quick observations:
  - ▶ Every node dominates itself.

# Dominators

- ▶ Node  $d$  **dominates** node  $n$  if every path from the *Entry* to  $n$  goes through  $d$ .
- ▶ [Exercise] A forward-intersection iterative algorithm for finding dominators.
- ▶ Quick observations:
  - ▶ Every node dominates itself.
  - ▶ The entry dominates every node.


# Example: Dominators



Node	Dominators
1	
2	
3	
4	
5	




# Example: Dominators




Node	Dominators
1	1
2	
3	
4	
5	

## Example: Dominators




Node	Dominators
1	1
2	1, 2
3	
4	
5	

## Example: Dominators




Node	Dominators
1	1
2	1, 2
3	1, 2, 3
4	
5	

## Example: Dominators



Node	Dominators
1	1
2	1, 2
3	1, 2, 3
4	1, 4
5	

## Example: Dominators



Node	Dominators
1	1
2	1, 2
3	1, 2, 3
4	1, 4
5	1, 5

# Common Dominator Cases

- ▶ The test of a while loop dominates all blocks in the loop body.

# Common Dominator Cases

- ▶ The test of a while loop dominates all blocks in the loop body.
- ▶ The test of an if-then-else dominates all blocks in either branch.

# Back Edges

- ▶ An edge is a **back edge** if its head dominates its tail.



# Back Edges

- ▶ An edge is a **back edge** if its head dominates its tail.
- ▶ **Theorem:** Every back edge is a retreating edge in every DFST of every flow graph.


# Back Edges

- ▶ An edge is a **back edge** if its head dominates its tail.
- ▶ **Theorem:** Every back edge is a retreating edge in every DFST of every flow graph.
  - ▶ Proof? Discuss/Exercise

# Back Edges


- ▶ An edge is a **back edge** if its head dominates its tail.
- ▶ **Theorem:** Every back edge is a retreating edge in every DFST of every flow graph.
  - ▶ Proof? Discuss/Exercise
  - ▶ Converse almost always true, but not always.

## Example: Back Edges



Node	Dominators
1	1
2	1, 2
3	1, 2, 3
4	1, 4
5	1, 5

## Example: Back Edges



Node	Dominators
1	1
2	1, 2
3	1, 2, 3
4	1, 4
5	1, 5


# Reducible Flow Graphs

- ▶ A flow graph is **reducible** if every retreating edge in any DFST for that flow graph is a back edge.

# Reducible Flow Graphs

- ▶ A flow graph is **reducible** if every retreating edge in any DFST for that flow graph is a back edge.
- ▶ **Testing reducibility:** Take any DFST for the flow graph, remove the back edges, and check that the result is acyclic.


## Example: Remove Back Edges



Node	Dominators
1	1
2	1, 2
3	1, 2, 3
4	1, 4
5	1, 5



## Example: Remove Back Edges




Node	Dominators
1	1
2	1, 2
3	1, 2, 3
4	1, 4
5	1, 5

Remaining graph is acyclic.


# Why Reducibility?

- ▶ **Folk theorem:** All flow graphs in practice are reducible.
- ▶ **Fact:** If you use only while-loops, for-loops, repeat-loops, if-then(-else), break, and continue, then your flow graph **is** reducible.

## Example: Nonreducible Graph




## Example: Nonreducible Graph




In any DFST, one of these edges will be a retreating edge.

## Example: Nonreducible Graph



In any DFST, one of these edges will be a retreating edge.

## Example: Nonreducible Graph



In any DFST, one of these edges will be a retreating edge.

# Why Care About Back/Retreating Edges?

- ▶ Proper ordering of nodes during iterative algorithm assures number of passes limited by the number of “nested” back edges.

# Why Care About Back/Retreating Edges?

- ▶ Proper ordering of nodes during iterative algorithm assures number of passes limited by the number of “nested” back edges.
- ▶ Depth of nested loops upper-bounds the number of nested back edges.



# DF Order and Retreating Edges

- ▶ Suppose that for a RD analysis, we visit nodes during each iteration in DF order.

# DF Order and Retreating Edges


- ▶ Suppose that for a RD analysis, we visit nodes during each iteration in DF order.
- ▶ The fact that a definition  $d$  reaches a block will propagate in one pass along any increasing sequence of blocks.

# DF Order and Retreating Edges

- ▶ Suppose that for a RD analysis, we visit nodes during each iteration in DF order.
- ▶ The fact that a definition  $d$  reaches a block will propagate in one pass along any increasing sequence of blocks.
- ▶ When  $d$  arrives along a retreating edge, it is too late to propagate  $d$  from OUT to IN.


## Example: DF Order

Node 2 generates definition **d**.




## Example: DF Order

Node 2 generates definition **d**.  
Other nodes “empty” w.r.t. **d**.




## Example: DF Order

Node 2 generates definition **d**.  
Other nodes “empty” w.r.t. **d**.  
Does **d** reach node 4?




## Example: DF Order

Node 2 generates definition **d**.  
Other nodes “empty” w.r.t. **d**.  
Does **d** reach node 4?



## Example: DF Order


Node 2 generates definition **d**.  
Other nodes “empty” w.r.t. **d**.  
Does **d** reach node 4?






## Example: DF Order

Node 2 generates definition **d**.  
Other nodes “empty” w.r.t. **d**.  
Does **d** reach node 4?




## Example: DF Order

Node 2 generates definition **d**.  
Other nodes “empty” w.r.t. **d**.  
Does **d** reach node 4?



## Example: DF Order

Node 2 generates definition **d**.  
Other nodes “empty” w.r.t. **d**.  
Does **d** reach node 4?




## Example: DF Order

Node 2 generates definition **d**.

Other nodes “empty” w.r.t. **d**.

Does **d** reach node 4?




## Example: DF Order

Node 2 generates definition **d**.

Other nodes “empty” w.r.t. **d**.

Does **d** reach node 4?




## Example: DF Order

Node 2 generates definition **d**.

Other nodes “empty” w.r.t. **d**.

Does **d** reach node 4?




## Example: DF Order

Node 2 generates definition **d**.

Other nodes “empty” w.r.t. **d**.

Does **d** reach node 4?




## Example: DF Order

Node 2 generates definition **d**.

Other nodes “empty” w.r.t. **d**.

Does **d** reach node 4?





# Depth of a Flow Graph

- ▶ The **depth** of a flow graph is the greatest number of retreating edges along any acyclic path.

# Depth of a Flow Graph

- ▶ The **depth** of a flow graph is the greatest number of retreating edges along any acyclic path.
- ▶ For RD, if we use DF order to visit nodes, we converge in  $\text{depth}+2$  passes.

# Depth of a Flow Graph

- ▶ The **depth** of a flow graph is the greatest number of retreating edges along any acyclic path.
- ▶ For RD, if we use DF order to visit nodes, we converge in  $\text{depth}+2$  passes.
  - ▶  $\text{Depth}+1$  passes to follow that number of increasing segments.

# Depth of a Flow Graph


- ▶ The **depth** of a flow graph is the greatest number of retreating edges along any acyclic path.
- ▶ For RD, if we use DF order to visit nodes, we converge in  $\text{depth}+2$  passes.
  - ▶  $\text{Depth}+1$  passes to follow that number of increasing segments.
  - ▶ 1 more pass to realize we converged.

## Example: Depth = 2


## Example: Depth = 2

→  
increasing

## Example: Depth = 2




## Example: Depth = 2






## Example: Depth = 2



## Example: Depth = 2



## Similarly ...

- ▶ AE also works in depth+2 passes.

## Similarly ...

- ▶ AE also works in depth+2 passes.
  - ▶ Unavailability propagates along retreat-free node sequences in one pass.

## Similarly ...

- ▶ AE also works in depth+2 passes.
  - ▶ Unavailability propagates along retreat-free node sequences in one pass.
- ▶ So does LV if we use reverse of DF order.

## Similarly ...

- ▶ AE also works in depth+2 passes.
  - ▶ Unavailability propagates along retreat-free node sequences in one pass.
- ▶ So does LV if we use reverse of DF order.
  - ▶ A use propagates backward along paths that do not use a retreating edge in one pass.

# In General ...


- ▶ The depth+2 bound works for any monotone bit-vector framework, as long as information only needs to propagate along acyclic paths.
  - ▶ Example: if a definition reaches a point, it does so along an acyclic path.

# Why Depth+2 is Good?

- ▶ Normal control-flow constructs produce reducible flow graphs with the number of back edges at most the nesting depth of loops.
  - ▶ Nesting depth tends to be small.




## Example: Nested Loops



3 nested while loops.


# Example: Nested Loops



3 nested while loops.


depth = 3.

## Example: Nested Loops




3 nested while loops.

depth = 3.




3 nested do-while loops.

## Example: Nested Loops



3 nested while loops.  
depth = 3.



3 nested do-while loops.  
depth = 1.

# Natural Loops

- ▶ The **natural loop** of a back edge  $a \rightarrow b$  is  $\{b\}$  plus the set of nodes that can reach  $a$  without going through  $b$ .


# Natural Loops

- ▶ The **natural loop** of a back edge  $a \rightarrow b$  is  $\{b\}$  plus the set of nodes that can reach  $a$  without going through  $b$ .
- ▶ **Theorem:** two natural loops are either disjoint, identical, or nested.

# Natural Loops


- ▶ The **natural loop** of a back edge  $a \rightarrow b$  is  $\{b\}$  plus the set of nodes that can reach  $a$  without going through  $b$ .
- ▶ **Theorem:** two natural loops are either disjoint, identical, or nested.
- ▶ Proof: Discuss/Exercise

## Example: Natural Loops






## Example: Natural Loops



Natural loop  $3 \rightarrow 2$

## Example: Natural Loops



Natural loop  $5 \rightarrow 1$

# Reading Assignment

- ▶ New Dragon Book (Aho, Lam, Sethi, Ullman)
  - ▶ Chapter 9