

# CS738: Advanced Compiler Optimizations

## Points-to Analysis using Types

Amey Karkare

karkare@cse.iitk.ac.in

<http://www.cse.iitk.ac.in/~karkare/cs738>

Department of CSE, IIT Kanpur



# Reference Papers

- ▶ Bjarne Steensgaard: Points-to Analysis in Almost Linear Time. POPL 1996
- ▶ Manuvir Das: Unification-based pointer analysis with directional assignments. PLDI 2000

# Language

$S ::= x = y$

# Language

$$S ::= x = y \\ \quad | \quad x = \&y$$

# Language

$$\begin{array}{lcl} S & ::= & x = y \\ & | & x = \&y \\ & | & x = *y \end{array}$$

# Language

$$\begin{array}{lcl} S & ::= & x = y \\ & | & x = \&y \\ & | & x = *y \\ & | & x = \text{allocate}(y) \end{array}$$

# Language

$$\begin{array}{lcl} S & ::= & x = y \\ & | & x = \&y \\ & | & x = *y \\ & | & x = \text{allocate}(y) \\ & | & *x = y \end{array}$$

# Language

$S ::=$

- $x = y$
- $| \quad x = \&y$
- $| \quad x = *y$
- $| \quad x = \text{allocate}(y)$
- $| \quad *x = y$
- $| \quad x = \text{fun}(f_1, \dots, f_n) \text{ returns } r \text{ in } S^*$



# Language

$S ::=$

- $x = y$
- $| \quad x = \&y$
- $| \quad x = *y$
- $| \quad x = \text{allocate}(y)$
- $| \quad *x = y$
- $| \quad x = \text{fun}(f_1, \dots, f_n) \text{ returns } r \text{ in } S^*$
- $| \quad x = \text{p}(y_1, \dots, y_n)$

# Language

$S ::=$

- $x = y$
- $| \quad x = \&y$
- $| \quad x = *y$
- $| \quad x = \text{allocate}(y)$
- $| \quad *x = y$
- $| \quad x = \text{fun}(f_1, \dots, f_n) \text{ returns } r \text{ in } S^*$
- $| \quad x = \text{p}(y_1, \dots, y_n)$

# Steensgaard's Analysis

- ▶ Non standard Types

$s \in \text{Symbols}$

# Steensgaard's Analysis

- ▶ Non standard Types

$s \in \text{Symbols}$

# Steensgaard's Analysis

## ► Non standard Types

$s \in \text{Symbols}$

$\tau \in \text{Locations} ::= (\varphi, \alpha)$

# Steensgaard's Analysis

## ► Non standard Types

$s \in \text{Symbols}$

$\tau \in \text{Locations} ::= (\varphi, \alpha)$

$\varphi \in \text{Ids} ::= \{s_1, \dots, s_n\}$

# Steensgaard's Analysis

## ► Non standard Types

$s \in \text{Symbols}$

$\tau \in \text{Locations} ::= (\varphi, \alpha)$

$\varphi \in \text{Ids} ::= \{s_1, \dots, s_n\}$

$\alpha \in \text{Values} ::= \perp \mid \text{ptr}(\tau)$

# Steensgaard's Analysis

## ► Non standard Types

$s \in \text{Symbols}$

$\tau \in \text{Locations} ::= (\varphi, \alpha)$

$\varphi \in \text{Ids} ::= \{s_1, \dots, s_n\}$

$\alpha \in \text{Values} ::= \perp \mid \text{ptr}(\tau)$

$A$  denotes type environment.



# Steensgaard's Analysis

## ► Partial Order

$$\alpha_1 \sqsubseteq \alpha_2 \iff (\alpha_1 = \perp) \vee (\alpha_1 = \alpha_2)$$

# Steensgaard's Analysis: Typing Rules

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : (\varphi', \alpha') \quad \alpha' \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = y)}$$

# Steensgaard's Analysis: Typing Rules

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : (\varphi', \alpha') \quad \alpha' \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = y)}$$

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : \tau \quad \text{ptr}(\tau) \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = \&y)}$$

# Steensgaard's Analysis: Typing Rules

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : (\varphi', \alpha') \quad \alpha' \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = y)}$$

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : \tau \quad \text{ptr}(\tau) \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = \&y)}$$

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : (\varphi', \text{ptr}(\varphi'', \alpha'')) \quad \alpha'' \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = *y)}$$

# Steensgaard's Analysis: Typing Rules

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : (\varphi', \alpha') \quad \alpha' \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = y)}$$

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : \tau \quad \text{ptr}(\tau) \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = \&y)}$$

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : (\varphi', \text{ptr}(\varphi'', \alpha'')) \quad \alpha'' \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = *y)}$$

$$\frac{A \vdash x : (\varphi, \text{ptr}(\varphi', \alpha')) \quad A \vdash y : (\varphi'', \alpha'') \quad \alpha'' \trianglelefteq \alpha'}{A \vdash \text{welltyped}(*x = y)}$$

# Steensgaard's Analysis: Typing Rules

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : (\varphi', \alpha') \quad \alpha' \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = y)}$$

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : \tau \quad \text{ptr}(\tau) \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = \&y)}$$

$$\frac{A \vdash x : (\varphi, \alpha) \quad A \vdash y : (\varphi', \text{ptr}(\varphi'', \alpha'')) \quad \alpha'' \trianglelefteq \alpha}{A \vdash \text{welltyped}(x = *y)}$$

$$\frac{A \vdash x : (\varphi, \text{ptr}(\varphi', \alpha')) \quad A \vdash y : (\varphi'', \alpha'') \quad \alpha'' \trianglelefteq \alpha'}{A \vdash \text{welltyped}(*x = y)}$$

$$\frac{A \vdash x : \tau}{A \vdash \text{welltyped}(x = \text{allocate}(y))}$$

# Steensgaard's Analysis

- ▶ Function Definitions

# Steensgaard's Analysis

- ▶ Function Definitions
- ▶ Need a new type value:  $(\tau_1 \dots \tau_n) \rightarrow \tau$



# Steensgaard's Analysis

- ▶ Function Definitions
- ▶ Need a new type value:  $(\tau_1 \dots \tau_n) \rightarrow \tau$

# Steensgaard's Analysis

- ▶ Function Definitions
- ▶ Need a new type value:  $(\tau_1 \dots \tau_n) \rightarrow \tau$

$$A \vdash x : (\tau_1 \dots \tau_n) \rightarrow \tau$$

# Steensgaard's Analysis

- ▶ Function Definitions
- ▶ Need a new type value:  $(\tau_1 \dots \tau_n) \rightarrow \tau$

$$\begin{aligned} &A \vdash x : (\tau_1 \dots \tau_n) \rightarrow \tau \\ &\forall i \in \{1 \dots n\}. A \vdash f_i : \tau_i \end{aligned}$$

# Steensgaard's Analysis

- ▶ Function Definitions
- ▶ Need a new type value:  $(\tau_1 \dots \tau_n) \rightarrow \tau$

$$\begin{aligned} &A \vdash x : (\tau_1 \dots \tau_n) \rightarrow \tau \\ &\forall i \in \{1 \dots n\}. A \vdash f_i : \tau_i \\ &A \vdash r : \tau \end{aligned}$$

# Steensgaard's Analysis

- ▶ Function Definitions
- ▶ Need a new type value:  $(\tau_1 \dots \tau_n) \rightarrow \tau$

$$\begin{aligned} &A \vdash x : (\tau_1 \dots \tau_n) \rightarrow \tau \\ &\forall i \in \{1 \dots n\}. A \vdash f_i : \tau_i \\ &A \vdash r : \tau \\ &\forall s \in S^*. A \vdash \text{welltyped}(s) \end{aligned}$$

# Steensgaard's Analysis

- ▶ Function Definitions
- ▶ Need a new type value:  $(\tau_1 \dots \tau_n) \rightarrow \tau$

$$\frac{\begin{array}{l} A \vdash x : (\tau_1 \dots \tau_n) \rightarrow \tau \\ \forall i \in \{1 \dots n\}. A \vdash f_i : \tau_i \\ A \vdash r : \tau \\ \forall s \in S^*. A \vdash \text{welltyped}(s) \end{array}}{A \vdash \text{welltyped}(x = \text{fun}(f_1, \dots, f_n) \text{ returns } r \text{ in } S^*)}$$

# Steensgaard's Analysis

## ► Function Calls

$$A \vdash x : \tau$$

$$\tau = (\varphi, \alpha)$$

# Steensgaard's Analysis

## ► Function Calls

$$A \vdash x : \tau$$

$$\tau = (\varphi, \alpha)$$



# Steensgaard's Analysis

## ► Function Calls

$$A \vdash x : \tau$$
$$A \vdash p : (\tau_1 \dots \tau_n) \rightarrow \tau'$$
$$\tau = (\varphi, \alpha)$$
$$\tau_i = (\varphi_i, \alpha_i)$$

# Steensgaard's Analysis

## ► Function Calls

$$A \vdash x : \tau$$
$$A \vdash p : (\tau_1 \dots \tau_n) \rightarrow \tau'$$
$$\forall i \in \{1 \dots n\}. A \vdash y_i : \tau'_i$$
$$\tau = (\varphi, \alpha)$$
$$\tau_i = (\varphi_i, \alpha_i)$$
$$\tau'_i = (\varphi'_i, \alpha'_i)$$

# Steensgaard's Analysis

## ► Function Calls

$$A \vdash x : \tau$$
$$A \vdash p : (\tau_1 \dots \tau_n) \rightarrow \tau'$$
$$\forall i \in \{1 \dots n\}. A \vdash y_i : \tau'_i$$
$$\alpha'_i \sqsubseteq \alpha_i$$
$$\tau = (\varphi, \alpha)$$
$$\tau_i = (\varphi_i, \alpha_i)$$
$$\tau'_i = (\varphi'_i, \alpha'_i)$$
$$\alpha' \sqsubseteq \alpha$$

# Steensgaard's Analysis

## ► Function Calls

$$\frac{\begin{array}{l} A \vdash x : \tau \\ A \vdash p : (\tau_1 \dots \tau_n) \rightarrow \tau' \\ \forall i \in \{1 \dots n\}. A \vdash y_i : \tau'_i \\ \alpha'_i \sqsubseteq \alpha_i \end{array} \quad \begin{array}{l} \tau = (\varphi, \alpha) \\ \tau_i = (\varphi_i, \alpha_i) \\ \tau'_i = (\varphi'_i, \alpha'_i) \\ \alpha' \sqsubseteq \alpha \end{array}}{A \vdash \text{welltyped}(x = p(y_1, \dots, y_n))}$$

# Manuvir Das's *One-level Flow-based Analysis*

$$\alpha_1 \leq \alpha_2 \Leftrightarrow \text{ptr}(\tau_1) \leq \text{ptr}(\tau_2)$$

# Manuvir Das's *One-level Flow-based Analysis*

$$\begin{aligned}\alpha_1 \leq \alpha_2 &\Leftrightarrow \text{ptr}(\tau_1) \leq \text{ptr}(\tau_2) \\ &\Leftrightarrow \text{ptr}((\varphi', \alpha')) \leq \text{ptr}((\varphi, \alpha))\end{aligned}$$

# Manuvir Das's *One-level Flow-based Analysis*

$$\begin{aligned}\alpha_1 \leq \alpha_2 &\Leftrightarrow \text{ptr}(\tau_1) \leq \text{ptr}(\tau_2) \\ &\Leftrightarrow \text{ptr}((\varphi', \alpha')) \leq \text{ptr}((\varphi, \alpha)) \\ &\Leftrightarrow (\varphi' \subseteq \varphi) \wedge (\alpha' = \alpha)\end{aligned}$$

# One-level Flow-based Analysis

- ▶ Replace  $\trianglelefteq$  by  $\leq$  in Steensgaard's analysis



# One-level Flow-based Analysis

- ▶ Replace  $\trianglelefteq$  by  $\leq$  in Steensgaard's analysis
- ▶ Keeps “top” level pointees separate!