

CS738: Advanced Compiler Optimizations

Types and Program Analysis

Amey Karkare

karkare@cse.iitk.ac.in

<http://www.cse.iitk.ac.in/~karkare/cs738>

Department of CSE, IIT Kanpur



Reference Book

Types and Programming Languages by Benjamin C. Pierce

Type: Definition

type

/tʌɪp/ 

noun

1. a category of people or things having common characteristics.
"this type of heather grows better in a drier habitat"
synonyms: kind, sort, variety, class, category, classification, group, set, bracket, genre, genus, species, family, order, breed, race, strain; More
2. a person or thing exemplifying the ideal or defining characteristics of something.
"she characterized his witty sayings as the type of modern wisdom"
synonyms: epitome, quintessence, essence, perfect example, archetype, model, pattern, paradigm, exemplar, embodiment, personification, avatar, prototype
"she characterized his witty sayings as the type of modern wisdom"

Types in Programming

- ▶ A collection of *values*



Types in Programming

- ▶ A collection of *values*



- ▶ The operations that are permitted on these values

Type System

- ▶ A collection of rules for checking the correctness of usages of types

Type System

- ▶ A collection of rules for checking the correctness of usages of types
 - ▶ “Consistency” of programs

The World of Programming Languages

► Typed

The World of Programming Languages

- ▶ Typed
 - ▶ C, C++, Java, Python, ...

The World of Programming Languages

- ▶ Typed
 - ▶ C, C++, Java, Python, ...
- ▶ Untyped

The World of Programming Languages

- ▶ Typed
 - ▶ C, C++, Java, Python, ...
- ▶ Untyped
 - ▶ Assembly, *any other?*

The World of Programming Languages

	Statically Typed	Dynamically Typed
Strongly Typed		
Weakly Typed		

The World of Programming Languages

	Statically Typed	Dynamically Typed
Strongly Typed	ML, Haskell, Pascal (almost), Java (almost)	
Weakly Typed		

The World of Programming Languages

	Statically Typed	Dynamically Typed
Strongly Typed	ML, Haskell, Pascal (almost), Java (almost)	Lisp, Scheme
Weakly Typed		

The World of Programming Languages

	Statically Typed	Dynamically Typed
Strongly Typed	ML, Haskell, Pascal (almost), Java (almost)	Lisp, Scheme
Weakly Typed	C, C++	

The World of Programming Languages

	Statically Typed	Dynamically Typed
Strongly Typed	ML, Haskell, Pascal (almost), Java (almost)	Lisp, Scheme
Weakly Typed	C, C++	Perl

Applications of Type-based Analyses

- ▶ Error Detection

Applications of Type-based Analyses

- ▶ Error Detection
 - ▶ Language Safety

Applications of Type-based Analyses

- ▶ Error Detection
 - ▶ Language Safety
 - ▶ Verification

Applications of Type-based Analyses

- ▶ Error Detection
 - ▶ Language Safety
 - ▶ Verification
- ▶ Abstraction

Applications of Type-based Analyses

- ▶ Error Detection
 - ▶ Language Safety
 - ▶ Verification
- ▶ Abstraction
- ▶ Documentation

Applications of Type-based Analyses

- ▶ Error Detection
 - ▶ Language Safety
 - ▶ Verification
- ▶ Abstraction
- ▶ Documentation
- ▶ Maintenance

Applications of Type-based Analyses

- ▶ Error Detection
 - ▶ Language Safety
 - ▶ Verification
- ▶ Abstraction
- ▶ Documentation
- ▶ Maintenance
- ▶ Efficiency

Untyped Arithmetic Expression Language

$t :=$ *terms*

Untyped Arithmetic Expression Language

t :=

true

– *terms*

– *constant true*

Untyped Arithmetic Expression Language

t :=

true

false

– *terms*

– *constant true*

– *constant false*

Untyped Arithmetic Expression Language

t :=	– <i>terms</i>
true	– <i>constant true</i>
false	– <i>constant false</i>
if t then t else t	– <i>conditional</i>

Untyped Arithmetic Expression Language

$t :=$

true

false

if t then t else t

0

– *terms*

– *constant true*

– *constant false*

– *conditional*

– *constant zero*

Untyped Arithmetic Expression Language

$t :=$

true

false

if t then t else t

0

succ t

– *terms*

– *constant true*

– *constant false*

– *conditional*

– *constant zero*

– *successor*

Untyped Arithmetic Expression Language

$t :=$

true

false

if t then t else t

0

succ t

pred t

– *terms*

– *constant true*

– *constant false*

– *conditional*

– *constant zero*

– *successor*

– *predecessor*

Untyped Arithmetic Expression Language

t :=	– <i>terms</i>
true	– <i>constant true</i>
false	– <i>constant false</i>
if t then t else t	– <i>conditional</i>
0	– <i>constant zero</i>
succ t	– <i>successor</i>
pred t	– <i>predecessor</i>
iszero t	– <i>zero test</i>

Syntax: Inductive Definition

The set of *terms* is the smallest set \mathcal{T} such that

Syntax: Inductive Definition

The set of *terms* is the smallest set \mathcal{T} such that

1. $\{\text{true}, \text{false}, 0\} \subseteq \mathcal{T}$

Syntax: Inductive Definition

The set of *terms* is the smallest set \mathcal{T} such that

1. $\{\text{true}, \text{false}, 0\} \subseteq \mathcal{T}$
2. if $t_1 \in \mathcal{T}$, then $\{\text{succ } t_1, \text{pred } t_1, \text{iszero } t_1\} \subseteq \mathcal{T}$

Syntax: Inductive Definition

The set of *terms* is the smallest set \mathcal{T} such that

1. $\{\text{true}, \text{false}, 0\} \subseteq \mathcal{T}$
2. if $t_1 \in \mathcal{T}$, then $\{\text{succ } t_1, \text{pred } t_1, \text{iszero } t_1\} \subseteq \mathcal{T}$
3. if $t_1 \in \mathcal{T}$, $t_2 \in \mathcal{T}$, and $t_3 \in \mathcal{T}$ then $\text{if } t_1 \text{ then } t_2 \text{ else } t_3 \in \mathcal{T}$

Syntax: Inference Rules

The set of *terms*, \mathcal{T} is defined by the following rules:

Syntax: Inference Rules

The set of *terms*, \mathcal{T} is defined by the following rules:

$$\text{true} \in \mathcal{T}$$

$$\text{false} \in \mathcal{T}$$

$$0 \in \mathcal{T}$$

Syntax: Inference Rules

The set of *terms*, \mathcal{T} is defined by the following rules:

$$\text{true} \in \mathcal{T}$$

$$\text{false} \in \mathcal{T}$$

$$0 \in \mathcal{T}$$

$$\frac{t_1 \in \mathcal{T}}{\text{succ } t_1 \in \mathcal{T}}$$

$$\frac{t_1 \in \mathcal{T}}{\text{pred } t_1 \in \mathcal{T}}$$

$$\frac{t_1 \in \mathcal{T}}{\text{iszero } t_1 \in \mathcal{T}}$$

Syntax: Inference Rules

The set of *terms*, \mathcal{T} is defined by the following rules:

$$\text{true} \in \mathcal{T}$$

$$\text{false} \in \mathcal{T}$$

$$0 \in \mathcal{T}$$

$$\frac{t_1 \in \mathcal{T}}{\text{succ } t_1 \in \mathcal{T}}$$

$$\frac{t_1 \in \mathcal{T}}{\text{pred } t_1 \in \mathcal{T}}$$

$$\frac{t_1 \in \mathcal{T}}{\text{iszero } t_1 \in \mathcal{T}}$$

$$\frac{t_1 \in \mathcal{T} \quad t_2 \in \mathcal{T} \quad t_3 \in \mathcal{T}}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 \in \mathcal{T}}$$

Concrete Syntax

$$\mathcal{S}_0 = \emptyset$$

Concrete Syntax

$$\begin{aligned}\mathcal{S}_0 &= \emptyset \\ \mathcal{S}_{i+1} &= \{\text{true}, \text{false}, \mathbf{0}\}\end{aligned}$$

Concrete Syntax

$$\begin{aligned}\mathcal{S}_0 &= \emptyset \\ \mathcal{S}_{i+1} &= \{\text{true}, \text{false}, \mathbf{0}\} \\ &\quad \cup \{\text{succ } t_1, \text{pred } t_1, \text{iszero } t_1 \mid t_1 \in \mathcal{S}_i\}\end{aligned}$$

Concrete Syntax

$$\begin{aligned}\mathcal{S}_0 &= \emptyset \\ \mathcal{S}_{i+1} &= \{\text{true}, \text{false}, \mathbf{0}\} \\ &\quad \cup \{\text{succ } t_1, \text{pred } t_1, \text{iszero } t_1 \mid t_1 \in \mathcal{S}_i\} \\ &\quad \cup \{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 \mid t_1, t_2, t_3 \in \mathcal{S}_i\}\end{aligned}$$

Concrete Syntax

$$\begin{aligned}\mathcal{S}_0 &= \emptyset \\ \mathcal{S}_{i+1} &= \{\text{true}, \text{false}, \mathbf{0}\} \\ &\quad \cup \{\text{succ } t_1, \text{pred } t_1, \text{iszero } t_1 \mid t_1 \in \mathcal{S}_i\} \\ &\quad \cup \{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 \mid t_1, t_2, t_3 \in \mathcal{S}_i\}\end{aligned}$$

Let $\mathcal{S} = \bigcup_i \mathcal{S}_i$.

Concrete Syntax

$$\begin{aligned}\mathcal{S}_0 &= \emptyset \\ \mathcal{S}_{i+1} &= \{\text{true}, \text{false}, \mathbf{0}\} \\ &\quad \cup \{\text{succ } \mathbf{t}_1, \text{pred } \mathbf{t}_1, \text{iszero } \mathbf{t}_1 \mid \mathbf{t}_1 \in \mathcal{S}_i\} \\ &\quad \cup \{\text{if } \mathbf{t}_1 \text{ then } \mathbf{t}_2 \text{ else } \mathbf{t}_3 \mid \mathbf{t}_1, \mathbf{t}_2, \mathbf{t}_3 \in \mathcal{S}_i\}\end{aligned}$$

Let $\mathcal{S} = \bigcup_i \mathcal{S}_i$.

Then, $\mathcal{T} = \mathcal{S}$.

Induction on Terms

- ▶ Any $t \in \mathcal{T}$

Induction on Terms

- ▶ Any $t \in \mathcal{T}$
 - ▶ Either a ground term, i.e. $\in \{\text{true}, \text{false}, 0\}$

Induction on Terms

- ▶ Any $t \in \mathcal{T}$
 - ▶ Either a ground term, i.e. $\in \{\text{true}, \text{false}, 0\}$
 - ▶ Or is created from some smaller terms $\in \mathcal{T}$

Induction on Terms

- ▶ Any $t \in \mathcal{T}$
 - ▶ Either a ground term, i.e. $\in \{\text{true}, \text{false}, 0\}$
 - ▶ Or is created from some smaller terms $\in \mathcal{T}$
- ▶ Allows for inductive definitions and inductive proofs.

Induction on Terms

- ▶ Any $t \in \mathcal{T}$
 - ▶ Either a ground term, i.e. $\in \{\text{true}, \text{false}, 0\}$
 - ▶ Or is created from some smaller terms $\in \mathcal{T}$
- ▶ Allows for inductive definitions and inductive proofs.
- ▶ Three sample inductive properties

Induction on Terms

- ▶ Any $t \in \mathcal{T}$
 - ▶ Either a ground term, i.e. $\in \{\text{true}, \text{false}, 0\}$
 - ▶ Or is created from some smaller terms $\in \mathcal{T}$
- ▶ Allows for inductive definitions and inductive proofs.
- ▶ Three sample inductive properties
 - ▶ $\text{Consts}(t)$

Induction on Terms

- ▶ Any $t \in \mathcal{T}$
 - ▶ Either a ground term, i.e. $\in \{\text{true}, \text{false}, 0\}$
 - ▶ Or is created from some smaller terms $\in \mathcal{T}$
- ▶ Allows for inductive definitions and inductive proofs.
- ▶ Three sample inductive properties
 - ▶ $\text{Consts}(t)$
 - ▶ $\text{size}(t)$

Induction on Terms

- ▶ Any $t \in \mathcal{T}$
 - ▶ Either a ground term, i.e. $\in \{\text{true}, \text{false}, 0\}$
 - ▶ Or is created from some smaller terms $\in \mathcal{T}$
- ▶ Allows for inductive definitions and inductive proofs.
- ▶ Three sample inductive properties
 - ▶ $\text{Consts}(t)$
 - ▶ $\text{size}(t)$
 - ▶ $\text{depth}(t)$

Consts

- ▶ The set of constants in a term t .

Consts

- The set of constants in a term t .

$$\mathit{Consts}(\mathit{true}) = \{\mathit{true}\}$$

Consts

- The set of constants in a term t .

$$\begin{aligned} \textit{Consts}(\text{true}) &= \{\text{true}\} \\ \textit{Consts}(\text{false}) &= \{\text{false}\} \end{aligned}$$

Consts

- The set of constants in a term t .

$$\mathit{Consts}(\mathit{true}) = \{\mathit{true}\}$$

$$\mathit{Consts}(\mathit{false}) = \{\mathit{false}\}$$

$$\mathit{Consts}(0) = \{0\}$$

Consts

- The set of constants in a term t .

$$\mathit{Consts}(\mathit{true}) = \{\mathit{true}\}$$

$$\mathit{Consts}(\mathit{false}) = \{\mathit{false}\}$$

$$\mathit{Consts}(0) = \{0\}$$

$$\mathit{Consts}(\mathit{succ } t) = \mathit{Consts}(t)$$

Consts

- The set of constants in a term t .

$$\mathit{Consts}(\mathit{true}) = \{\mathit{true}\}$$

$$\mathit{Consts}(\mathit{false}) = \{\mathit{false}\}$$

$$\mathit{Consts}(0) = \{0\}$$

$$\mathit{Consts}(\mathit{succ } t) = \mathit{Consts}(t)$$

$$\mathit{Consts}(\mathit{pred } t) = \mathit{Consts}(t)$$

Consts

- The set of constants in a term t .

$$\textit{Consts}(\text{true}) = \{\text{true}\}$$

$$\textit{Consts}(\text{false}) = \{\text{false}\}$$

$$\textit{Consts}(0) = \{0\}$$

$$\textit{Consts}(\text{succ } t) = \textit{Consts}(t)$$

$$\textit{Consts}(\text{pred } t) = \textit{Consts}(t)$$

$$\textit{Consts}(\text{iszero } t) = \textit{Consts}(t)$$

Consts

- The set of constants in a term t .

$$\text{Consts}(\text{true}) = \{\text{true}\}$$

$$\text{Consts}(\text{false}) = \{\text{false}\}$$

$$\text{Consts}(0) = \{0\}$$

$$\text{Consts}(\text{succ } t) = \text{Consts}(t)$$

$$\text{Consts}(\text{pred } t) = \text{Consts}(t)$$

$$\text{Consts}(\text{iszero } t) = \text{Consts}(t)$$

$$\begin{aligned}\text{Consts}(\text{if } t_1 \text{ then } t_2 \text{ else } t_3) &= \text{Consts}(t_1) \\ &\cup \text{Consts}(t_2) \\ &\cup \text{Consts}(t_3)\end{aligned}$$

size

- ▶ The number of nodes in the abstract syntax tree of a term t .

size

- ▶ The number of nodes in the abstract syntax tree of a term t .

$$\mathit{size}(\mathsf{true}) = 1$$

size

- ▶ The number of nodes in the abstract syntax tree of a term t .

$$\textit{size}(\text{true}) = 1$$

$$\textit{size}(\text{false}) = 1$$

size

- ▶ The number of nodes in the abstract syntax tree of a term t .

$$\textit{size}(\text{true}) = 1$$

$$\textit{size}(\text{false}) = 1$$

$$\textit{size}(0) = 1$$

size

- The number of nodes in the abstract syntax tree of a term t .

$$\mathit{size}(\mathsf{true}) = 1$$

$$\mathit{size}(\mathsf{false}) = 1$$

$$\mathit{size}(0) = 1$$

$$\mathit{size}(\mathsf{succ } t) = \mathit{size}(t) + 1$$

size

- ▶ The number of nodes in the abstract syntax tree of a term t .

$$\mathit{size}(\mathit{true}) = 1$$

$$\mathit{size}(\mathit{false}) = 1$$

$$\mathit{size}(0) = 1$$

$$\mathit{size}(\mathit{succ } t) = \mathit{size}(t) + 1$$

$$\mathit{size}(\mathit{pred } t) = \mathit{size}(t) + 1$$

size

- The number of nodes in the abstract syntax tree of a term t .

$$\textit{size}(\text{true}) = 1$$

$$\textit{size}(\text{false}) = 1$$

$$\textit{size}(0) = 1$$

$$\textit{size}(\text{succ } t) = \textit{size}(t) + 1$$

$$\textit{size}(\text{pred } t) = \textit{size}(t) + 1$$

$$\textit{size}(\text{iszero } t) = \textit{size}(t) + 1$$

size

- The number of nodes in the abstract syntax tree of a term t .

$$\text{size}(\text{true}) = 1$$

$$\text{size}(\text{false}) = 1$$

$$\text{size}(0) = 1$$

$$\text{size}(\text{succ } t) = \text{size}(t) + 1$$

$$\text{size}(\text{pred } t) = \text{size}(t) + 1$$

$$\text{size}(\text{iszero } t) = \text{size}(t) + 1$$

$$\text{size}(\text{if } t_1 \text{ then } t_2 \text{ else } t_3) = \text{size}(t_1) + \text{size}(t_2) + \text{size}(t_3)$$

depth

- ▶ The maximum depth of the abstract syntax tree of a term t .
- ▶ Equivalently, the smallest i such that $t \in \mathcal{S}_i$.

depth

- ▶ The maximum depth of the abstract syntax tree of a term t .
- ▶ Equivalently, the smallest i such that $t \in \mathcal{S}_i$.

$$\text{depth}(\text{true}) = 1$$

depth

- ▶ The maximum depth of the abstract syntax tree of a term t .
- ▶ Equivalently, the smallest i such that $t \in \mathcal{S}_i$.

$$\textit{depth}(\text{true}) = 1$$

$$\textit{depth}(\text{false}) = 1$$

depth

- ▶ The maximum depth of the abstract syntax tree of a term t .
- ▶ Equivalently, the smallest i such that $t \in \mathcal{S}_i$.

$$\textit{depth}(\text{true}) = 1$$

$$\textit{depth}(\text{false}) = 1$$

$$\textit{depth}(0) = 1$$

depth

- ▶ The maximum depth of the abstract syntax tree of a term t .
- ▶ Equivalently, the smallest i such that $t \in \mathcal{S}_i$.

$$\textit{depth}(\texttt{true}) = 1$$

$$\textit{depth}(\texttt{false}) = 1$$

$$\textit{depth}(0) = 1$$

$$\textit{depth}(\texttt{succ } t) = \textit{depth}(t) + 1$$

depth

- ▶ The maximum depth of the abstract syntax tree of a term t .
- ▶ Equivalently, the smallest i such that $t \in \mathcal{S}_i$.

$$\text{depth}(\text{true}) = 1$$

$$\text{depth}(\text{false}) = 1$$

$$\text{depth}(0) = 1$$

$$\text{depth}(\text{succ } t) = \text{depth}(t) + 1$$

$$\text{depth}(\text{pred } t) = \text{depth}(t) + 1$$

depth

- ▶ The maximum depth of the abstract syntax tree of a term t .
- ▶ Equivalently, the smallest i such that $t \in \mathcal{S}_i$.

$$\text{depth}(\text{true}) = 1$$

$$\text{depth}(\text{false}) = 1$$

$$\text{depth}(0) = 1$$

$$\text{depth}(\text{succ } t) = \text{depth}(t) + 1$$

$$\text{depth}(\text{pred } t) = \text{depth}(t) + 1$$

$$\text{depth}(\text{iszero } t) = \text{depth}(t) + 1$$

depth

- ▶ The maximum depth of the abstract syntax tree of a term t .
- ▶ Equivalently, the smallest i such that $t \in \mathcal{S}_i$.

$$\text{depth}(\text{true}) = 1$$

$$\text{depth}(\text{false}) = 1$$

$$\text{depth}(0) = 1$$

$$\text{depth}(\text{succ } t) = \text{depth}(t) + 1$$

$$\text{depth}(\text{pred } t) = \text{depth}(t) + 1$$

$$\text{depth}(\text{iszero } t) = \text{depth}(t) + 1$$

$$\text{depth}(\text{if } t_1 \text{ then } t_2 \text{ else } t_3) = \max(\text{depth}(t_1), \text{depth}(t_2), \text{depth}(t_3)) + 1$$

A Simple Property of Terms

- ▶ The number of distinct constants in a term t is no greater than the size of t .

$$|Consts(t)| \leq size(t)$$

A Simple Property of Terms

- ▶ The number of distinct constants in a term t is no greater than the size of t .

$$|Consts(t)| \leq size(t)$$

- ▶ **Proof:** Exercise.

The Set of Values

$V :=$

– *values*

The Set of Values

$V :=$

true

– *values*

– *value true*

The Set of Values

$V :=$

true

false

– *values*

– *value true*

– *value false*

The Set of Values

$V :=$

true

false

0

– *values*

– *value true*

– *value false*

– *value zero*

The Set of Values

$V :=$

true

false

0

succ V

– *values*

– *value true*

– *value false*

– *value zero*

– *successor value*

Small-step Operational Semantics

- ▶ $t \rightarrow t'$ denotes “t evaluates to t' in one step”

Small-step Operational Semantics

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

`if true then t_2 else $t_3 \rightarrow t_2$`

Small-step Operational Semantics

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

`if true then t_2 else $t_3 \rightarrow t_2$`

`if false then t_2 else $t_3 \rightarrow t_3$`

Small-step Operational Semantics

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

if true then t_2 else $t_3 \rightarrow t_2$

if false then t_2 else $t_3 \rightarrow t_3$

$$\frac{t_1 \rightarrow t'_1}{\text{if } t_1 \text{ then } t_2 \text{ else } t_3 \rightarrow \text{if } t'_1 \text{ then } t_2 \text{ else } t_3}$$

Small-step Operational Semantics (contd. . .)

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

$$\frac{t_1 \rightarrow t'_1}{\text{succ } t_1 \rightarrow \text{succ } t'_1}$$

Small-step Operational Semantics (contd. . .)

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

$$\frac{t_1 \rightarrow t'_1}{\text{succ } t_1 \rightarrow \text{succ } t'_1}$$

$$\text{pred } 0 \rightarrow 0$$

Small-step Operational Semantics (contd. . .)

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

$$\frac{t_1 \rightarrow t'_1}{\text{succ } t_1 \rightarrow \text{succ } t'_1}$$

$$\text{pred } 0 \rightarrow 0$$

$$\text{pred } (\text{succ } v) \rightarrow v$$

Small-step Operational Semantics (contd. . .)

- $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

$$\frac{t_1 \rightarrow t'_1}{\text{succ } t_1 \rightarrow \text{succ } t'_1}$$

$$\text{pred } 0 \rightarrow 0$$

$$\text{pred } (\text{succ } v) \rightarrow v$$

$$\frac{t_1 \rightarrow t'_1}{\text{pred } t_1 \rightarrow \text{pred } t'_1}$$

Small-step Operational Semantics (contd. . .)

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

`iszero 0` \rightarrow `true`

Small-step Operational Semantics (contd. . .)

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

`iszero 0 → true`

`iszero (succ v) → false`

Small-step Operational Semantics (contd. . .)

- ▶ $t \rightarrow t'$ denotes “ t evaluates to t' in one step”

`iszero 0` \rightarrow `true`

`iszero (succ v)` \rightarrow `false`

$$\frac{t_1 \rightarrow t'_1}{\text{iszero } t_1 \rightarrow \text{iszero } t'_1}$$

Normal Form

- ▶ A term is t in normal form if no evaluation rule applies to it.

Normal Form

- ▶ A term is t in normal form if no evaluation rule applies to it.
- ▶ In other words, there is no t' such that $t \rightarrow t'$.

Evaluation Sequence

- ▶ An evaluation sequence starting from a term t is a (finite or infinite) sequence of terms t_1, t_2, \dots , such that

$$t \rightarrow t_1$$

$$t_1 \rightarrow t_2$$

etc.

Stuck Term

- ▶ A term is said to be **stuck** if it is a normal form but not a value.

Stuck Term

- ▶ A term is said to be **stuck** if it is a normal form but not a value.
- ▶ A simple notion of “run-time type error”