

## Dear Author

Here are the proofs of your article.

- You can submit your corrections **online** or by **fax**.
- For **online** submission please insert your corrections in the online correction form. Always indicate the line number to which the correction refers.
- Please return your proof together with the permission to publish confirmation.
- For **fax** submission, please ensure that your corrections are clearly legible. Use a fine black pen and write the correction in the margin, not too close to the edge of the page.
- Remember to note the journal title, article number, and your name when sending your response via e-mail, fax or regular mail.
- **Check** the metadata sheet to make sure that the header information, especially author names and the corresponding affiliations are correctly shown.
- **Check** the questions that may have arisen during copy editing and insert your answers/corrections.
- **Check** that the text is complete and that all figures, tables and their legends are included. Also check the accuracy of special characters, equations, and electronic supplementary material if applicable. If necessary refer to the *Edited manuscript*.
- The publication of inaccurate data such as dosages and units can have serious consequences. Please take particular care that all such details are correct.
- Please **do not** make changes that involve only matters of style. We have generally introduced forms that follow the journal's style. Substantial changes in content, e.g., new results, corrected values, title and authorship are not allowed without the approval of the responsible editor. In such a case, please contact the Editorial Office and return his/her consent together with the proof.
- If we do not receive your corrections **within 48 hours**, we will send you a reminder.

### Please note

Your article will be published **Online First** approximately one week after receipt of your corrected proofs. This is the **official first publication** citable with the DOI.

**Further changes are, therefore, not possible.**

After online publication, subscribers (personal/institutional) to this journal will have access to the complete article via the DOI using the URL:

<http://dx.doi.org/10.1007/s10489-021-02597-8>

If you would like to know when your article has been published online, take advantage of our free alert service. For registration and further information, go to:

<http://www.springerlink.com>.

Due to the electronic nature of the procedure, the manuscript and the original figures will only be returned to you on special request. When you return your corrections, please inform us, if you would like to have these documents returned.

The **printed version** will follow in a forthcoming issue.

## Metadata of the article that will be visualized in OnlineFirst

1	Article Title	<b>Automated detection of cyclic alternating pattern and classification of sleep stages using deep neural network</b>	
2	Article Sub- Title		
3	Article Copyright - Year	<b>Springer Science+Business Media, LLC, part of Springer Nature 2021 (This will be the copyright line in the final PDF)</b>	
4	Journal Name	Applied Intelligence	
5	Corresponding Author	Family Name	<b>Acharya</b>
6		Particle	
7		Given Name	<b>U. Rajendra</b>
8		Suffix	
9		Organization	University of Southern Queensland
10		Division	School of Management and Enterprise
11		Address	Toowoomba, Australia
12		Organization	Singapore University of Social Sciences
13		Division	School of Science and Technology
14		Address	Singapore, Singapore
15		Organization	Ngee Ann Polytechnic
16		Division	School of Engineering
17	Author	Address	Ngee Ann, Singapore
18		Organization	Asia University
19		Division	Department of Bioinformatics and Medical Engineering
20		Address	Taichung, Taiwan
21		Organization	International Research Organization for Advanced Science and Technology (IROAST) Kumamoto University
22		Division	
23		Address	Kumamoto, Japan
24		e-mail	aru@np.edu.sg
25	Author	Family Name	<b>Loh</b>
26		Particle	
27		Given Name	<b>Hui Wen</b>
28		Suffix	
29		Organization	Singapore University of Social Sciences
30		Division	School of Science and Technology
31		Address	Singapore, Singapore
32	Author	e-mail	
33		Family Name	<b>Ooi</b>

34		Particle	
35		Given Name	<b>Chui Ping</b>
36		Suffix	
37		Organization	Singapore University of Social Sciences
38		Division	School of Science and Technology
39		Address	Singapore, Singapore
40		e-mail	
41		Family Name	<b>Dhok</b>
42		Particle	
43		Given Name	<b>Shivani G.</b>
44		Suffix	
45	Author	Organization	Indian Institute of Information Technology Nagpur (IIITN)
46		Division	Department of Electronics and Communication Engineering
47		Address	Nagpur, India
48		e-mail	
49		Family Name	<b>Sharma</b>
50		Particle	
51		Given Name	<b>Manish</b>
52		Suffix	
53	Author	Organization	Institute of Infrastructure, Technology, Research and Management (IITRAM)
54		Division	Department of Electrical and Computer Science Engineering
55		Address	Ahmedabad, India
56		e-mail	
57		Family Name	<b>Bhurane</b>
58		Particle	
59		Given Name	<b>Ankit A.</b>
60		Suffix	
61	Author	Organization	Visvesvaraya National Institute of Technology (VNIT)
62		Division	Department of Electronics and Communication
63		Address	Nagpur, India
64		e-mail	
65		Received	
66	Schedule	Revised	
67		Accepted	5 June 2021
68	Abstract	The visual sleep stages scoring by human experts is the current gold standard for sleep analysis. However, this method is tedious, time-consuming, prone to human errors, and unable to detect microstructure of sleep such as cyclic alternating pattern (CAP) which is an important diagnostic factor for the detection of sleep disorders such as insomnia and obstructive sleep apnea	

(OSA). The CAP is only observed as subtle changes in the electroencephalogram (EEG) signals during non-rapid eye movement (NREM) sleep, making it very difficult for human experts to discern. Hence, it is important to have an automated system developed using artificial intelligence for accurate and robust detection of CAP and sleep stages classification. In this study, a deep learning model based on 1-dimensional convolutional neural network (1D-CNN) is proposed for CAP detection and homogenous 3-class sleep stages classification, namely wakefulness (W), rapid eye movement (REM) and NREM sleep. The proposed model is developed using standardized EEG recordings. Our developed CNN network achieved good model performance for 3-class sleep stages classification with a classification accuracy of 90.46%. Our proposed model also yielded a classification accuracy of 73.64% using balanced CAP dataset, and sensitivity of 92.06% with unbalanced CAP dataset. Our proposed model correctly identified majority of A-phases which comprised of only 12.6% in the unbalanced dataset. The performance of the developed prototype is ready to be tested with more data before clinical application.

69	Keywords separated by ' - '	Sleep stages - Cyclic alternating pattern (CAP) - Classification - Electroencephalogram (EEG) - Deep learning - CAPSLPDB - CNN
70	Foot note information	Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.



# Automated detection of cyclic alternating pattern and classification of sleep stages using deep neural network

Hui Wen Loh<sup>1</sup> · Chui Ping Ooi<sup>1</sup> · Shivani G. Dhok<sup>2</sup> · Manish Sharma<sup>3</sup> · Ankit A. Bhurane<sup>4</sup> · U. Rajendra Acharya<sup>1,5,6,7,8</sup>

Accepted: 5 June 2021  
© Springer Science+Business Media, LLC, part of Springer Nature 2021

## Abstract

The visual sleep stages scoring by human experts is the current gold standard for sleep analysis. However, this method is tedious, time-consuming, prone to human errors, and unable to detect microstructure of sleep such as cyclic alternating pattern (CAP) which is an important diagnostic factor for the detection of sleep disorders such as insomnia and obstructive sleep apnea (OSA). The CAP is only observed as subtle changes in the electroencephalogram (EEG) signals during non-rapid eye movement (NREM) sleep, making it very difficult for human experts to discern. Hence, it is important to have an automated system developed using artificial intelligence for accurate and robust detection of CAP and sleep stages classification. In this study, a deep learning model based on 1-dimensional convolutional neural network (1D-CNN) is proposed for CAP detection and homogenous 3-class sleep stages classification, namely wakefulness (W), rapid eye movement (REM) and NREM sleep. The proposed model is developed using standardized EEG recordings. Our developed CNN network achieved good model performance for 3-class sleep stages classification with a classification accuracy of 90.46%. Our proposed model also yielded a classification accuracy of 73.64% using balanced CAP dataset, and sensitivity of 92.06% with unbalanced CAP dataset. Our proposed model correctly identified majority of A-phases which comprised of only 12.6% in the unbalanced dataset. The performance of the developed prototype is ready to be tested with more data before clinical application.

**Keywords** Sleep stages · Cyclic alternating pattern (CAP) · Classification · Electroencephalogram (EEG) · Deep learning · CAPSLPDB · CNN

## 1 Introduction

Sleep is often taken for granted, but it is crucial for our physical and mental health [1]. Approximately 50 to 70 million Americans are reported to have sleep disorders [2] and at least 25 million Americans have obstructive sleep apnea (OSA) [3]. Also, 30% of the adults in the United States of America are diagnosed with insomnia [4]. Sleep disorders like OSA and insomnia are also associated with numerous health problems such as stroke [5], cardiovascular disease [6], and obesity [7]. However, sleep problem is a global issue that is not just unique to America. In 2012, Stranges et al. [8] investigated the prevalence of sleep problem from 8 countries across Asia and Africa, using two publicly available datasets: International Network for the Demographic Evaluation of Populations and Their Health (INDEPTH) and the World Health Organization Study on Global Ageing and Adult Health (WHO-SAGE). They reported that 16.6% of the adults (≈150 million) included in their study had sleep problems and this number is expected to exceed 260 million by 2030

✉ U. Rajendra Acharya  
aru@np.edu.sg

- <sup>1</sup> School of Science and Technology, Singapore University of Social Sciences, Singapore, Singapore
- <sup>2</sup> Department of Electronics and Communication Engineering, Indian Institute of Information Technology Nagpur (IIITN), Nagpur, India
- <sup>3</sup> Department of Electrical and Computer Science Engineering, Institute of Infrastructure, Technology, Research and Management (IITRAM), Ahmedabad, India
- <sup>4</sup> Department of Electronics and Communication, Visvesvaraya National Institute of Technology (VNIT), Nagpur, India
- <sup>5</sup> School of Engineering, Ngee Ann Polytechnic, Ngee Ann, Singapore
- <sup>6</sup> Department of Bioinformatics and Medical Engineering, Asia University, Taichung, Taiwan
- <sup>7</sup> International Research Organization for Advanced Science and Technology (IROAST) Kumamoto University, Kumamoto, Japan
- <sup>8</sup> School of Management and Enterprise, University of Southern Queensland, Toowoomba, Australia

because adults, especially in low-income settings, are ignorant of the detrimental health effect of sleep problems. Another global sleep problem study by Konayagi et al. [9] had analyzed data from the World Health Organization's World Health Survey (WHS) across 70 countries. They reported that the odds of having sleep problems for an individual with a known psychotic symptom is 2.41 ( $p$  value  $<0.001$ ); more than two times increase in the risk of having sleep problems. Hence, sleep problem is becoming a serious public health issue on a global scale and an accurate diagnostic tool of sleep disorder is needed [10, 11].

Sleep stages are also known as the macrostructure of sleep and there are initially six stages according to Rechtschaffen and Kales (R&K) rules [12]: Wakefulness (W), Rapid Eye Movement (REM), and Non-REM which is divided into 4 stages (NREM S1- S4). Later, the American Academy of Sleep Medicine (AASM) guidelines [13] classified NREM S3 and NREM S4 together as Slow Wave Sleep (SWS) due to similarity in their characteristics, resulting in a total of five sleep stages. The five sleep stages can be described with electroencephalogram (EEG) characteristic rhythm and other physiological changes as follows:

- **Wakefulness:** The brain activity is in the most active stage and is represented by high frequency alpha rhythms and occasional beta rhythms [14].
- **NREM S1:** In this stage, an individual proceeds to fall asleep and alpha rhythms disappear while theta rhythms make their appearances [14]. This is the lightest sleep stage where individuals are easily awakened by disruptive noises [2]. Heart rate and breathing begin to slow down and muscle starts to relax as well [15].
- **NREM S2:** Sleep spindles and K-complex will occasionally appear for approximately 1 to 2 s [14]. High density sleep spindles are also observed in individuals who learn new tasks before sleep, hence indicating its relation to memory consolidation [16]. Body temperature begins to drop, and eye movement ceases at this stage [15].
- **SWS (NREM S3 and S4):** Low frequency delta rhythms will appear intermittently in NREM S3 and eventually dominates in NREM S4 [14]. An optimal amount of SWS allows individuals to feel refreshed when they wake up. Heart rate and breathing are the slowest at this stage and muscles are fully relaxed. This is the deepest sleep stage where individuals usually find it hard to wake up [15].
- **REM:** Proceeds immediately after SWS and it is represented by theta rhythms and flattening of EEG signals, accompanied by loss of muscle tone of the body core [14, 17]. Breathing patterns are fast and irregular during REM sleep and heart rate increases to near waking levels. Dreams are known to occur in this stage and REM sleep is accompanied by the loss of muscle tone to prevent individuals from acting out of their dreams [15].

Currently, the visual sleep stages scoring by human experts is the gold standard for sleep analysis [18]. According to the AASM guidelines [13], overnight polysomnogram (PSG) recordings are first segmented into 30s fragments (epochs). Next, each epoch is scored into different sleep stages. It is very often that an epoch may contain two or more sleep stages. Thus, human experts score each epoch based on the sleep stages, which appears predominantly. For instance, an epoch comprises 45% NREM S1 and 55% NREM S2 will be classified as NREM S2 sleep. However, this method results in heterogenous sleep stages scoring [18]. In fact, NREM S3 and S4 are heterogeneously combined as SWS for ease of classification because human experts are incapable of adapting to slow background EEG changes which makes the classification of NREM S3 and S4 challenging, as counting the delta rhythm occurrence is difficult [12, 18]. To address the limitation of heterogenous sleep stages scoring, Kemp et al. [19] and Pardey et al. [20] suggested that NREM sleep should be represented as a continuous function, rather than subdivisions of NREM sleep.

Another challenge regarding the current sleep stages scoring approach is the exclusion of microstructure of sleep which only appears for a few seconds, significantly shorter than an epoch of 30s duration [18]. The microstructure of sleep includes cyclic alternating pattern (CAP), elementary arousal (K-complexes) and micro-arousal [18, 21]. In particular, arousal instability is more evident in the CAP sequence rather than in micro-arousal events. Hence, CAP provides a global framework to measure sleep instability [21]. CAP only appears in periodic EEG activity of the NREM sleep and it is associated with sleep events such as falling asleep, transition in sleep stage, and awakenings [22, 23]. Thus, if there is an appearance of CAP in REM sleep, it could be a prognostic element of sleep disorder [24].

CAP can be described as recurrent transient electrocortical events that consist of two distinct phases: A-phase and B-phase [23]. A-phase is a transient phenomenon that has known association with brain activation [24, 25] and it is further broken down into three subtypes described as follows [24, 25]:

- **A1-phase** can be identified by an increase in amplitude to 3 times that of normal background activity and they are usually delta rhythms, K-complexes, and bursts.
- **A2-phase** is a combination of A1 and A3 phase, characterized by a mixture of slow and fast rhythms. This phase also indicated a drop in sleep stability.
- **A3-phase** can be identified by an increase in frequency compared to background activity and they are usually alpha and beta rhythms.

Hence, A-phase is characterized by having either low frequency with high amplitude EEG signals (A1-phase) or high frequency with low amplitude EEG signals (A3-phase) or a



combination of these two phenomena (A2-phase) [25]. A-phases can be distinguished from B-phases which are background EEG activities as shown in Fig. 1 [11].

A CAP cycle is formed when B-phase immediately follows after A-phase, otherwise, the A-phase is considered to be isolated [24]. A CAP sequence is formed when two or more CAP cycles occur in a sequence. The duration of each CAP phase can vary from 2 s to 60s and normally, young adults have a mean duration of two and half minutes of CAP sequence, which consists of six CAP cycles [24, 26]. On the other hand, individuals with sleep disorders such as OSA are found to have higher CAP rate, cycles, and duration. This phenomenon is evident when OSA patients are accompanied by excessive sleepiness as well [27]. Abnormal CAP rates are found in epilepsy [28], insomnia [29], obstructive sleep apnea (OSA) [27], and coma patients [30]. Therefore, CAP is an important marker for unstable sleep that is, unfortunately, not included in visual sleep analysis [18, 26].

As such, there is a need to resolve the limitations of visual sleep analysis, which are heterogenous sleep stages scoring and exclusion of CAP. This can be achieved with the aid of a computer aided diagnostic (CAD) tool that is superior to human counterparts in detecting the subtle changes in background EEG related to microstructure of sleep like CAP that is commonly left out in sleep stages scoring by human experts [18, 31–33]. Studies have also shown that CAD performed equally well, if not better, in sleep stages scoring as compared to the human experts [34–36]. In the recent past, numerous studies have attempted to develop CAD tools based on machine learning and deep learning methodology for automated classification of sleep stages and detection of CAP separately. Rahman et al. [37] used EEG signals from the expanded sleep-EDF database in their study for 3-class sleep stages classification (W, NREM & REM) and achieved an accuracy of 94.1% with discrete

wavelet transform (DWT) and support vector machine (SVM). Likewise, Yildirim et al. [38] proposed a 1-Dimensional Convolutional Neural Network (1D-CNN) model for 3-class sleep stages classification and achieved an overall accuracy of 94.2% using EEG signals in both Sleep-EDF and expanded sleep-EDF database. As for CAP detection, Mendez et al. [39] proposed k-nearest neighbor (KNN) classifier to distinguish A-phases in CAP and achieved 80% accuracy. Hartmann et al. [40] proposed long short-term memory (LSTM) model for A-phase detection in CAP and achieved an accuracy of 82.4%.


In this work, we have attempted to address the limitation of traditional sleep stages scoring and automatic CAP detection using a deep learning model based on 1-Dimensional Convolutional Neural Network (1D-CNN). To the best of our knowledge, this is the first automated model developed for both sleep stages classification and CAP detection. The main contributions of this work are given below:

- The proposed model is compatible for the classification of both macrostructure and microstructure of sleep.
- For CAP detection, the proposed model can be trained with a smaller dataset (Table 4: balanced CAP dataset) and evaluated with a bigger dataset (Table 3: unbalanced CAP dataset). Hence, higher classification efficiency is obtained with shorter training time.
- The proposed model has the potential to be further developed into a CAD tool for clinical applications.

## 2 Materials & methods

Section 2.1 describes the data preparation and preprocessing methods, Section 2.2 outlines the experiment setup of this

**Fig. 1** CAP waveform recorded from different EEG electrodes in CAPSLPDB, healthy subject N1



work, and Section 2.3 elaborates the architecture of the proposed 1D-CNN model.

## 2.1 Data acquisition

In this paper, we considered a publicly available CAP sleep database (CAPSLPDB), which was acquired from PhysioNet [23, 41]. The PSG recordings in CAPSLPDB were obtained from an experiment conducted in the Sleep Disorder Center of the Ospedale Maggiore of Parma, Italy [23]. A total of 108 overnight PSG recordings were collected from 16 healthy and 92 pathological subjects, for a duration of 9–10 h. The PSG recordings included at least 3 EEG channels, 2 EOG channels, 2 EMG channels, ECG, and respiratory signals, which were sampled over a range of sampling frequencies (100 Hz, 128 Hz, 200 Hz, and 512 Hz.).

In this paper, we used single-channel EEG recordings (C4-A1 or C3-A2) from 6 healthy subjects that were sampled at 512 Hz sampling frequency. For sleep stages classification, the dataset was prepared by first segmenting the EEG recordings into segments of 30 s duration. Then, the substages of NREM sleep (S1, S2, and SWS) were combined to obtain a single sleep stage, as shown in Table 1. Considering the minimum possible duration of occurrence of CAP, the EEG signals were segmented into segments of 2 s duration for CAP detection. Then, the subphases of A-phase were combined to obtain a single phase. However, there are two types of datasets

**Table 2** Summary of the total number of samples for unbalanced CAP dataset

Subject	A1	A2	A3	A-phase	B-phase	Total
N1	1013	354	548	1915	12,915	14,830
N2	550	327	597	1474	10,560	12,034
N3	285	284	494	1063	10,110	11,173
N5	1307	157	377	1841	11,460	13,301
N10	703	159	445	1307	8550	9857
N11	796	270	386	1452	9210	10,662
Total	4654	1551	2847	9052	62,805	71,857

created for CAP detection: unbalanced CAP dataset (Table 2), and balanced CAP dataset (Table 3). In the unbalanced dataset, all samples were considered, while in the balanced dataset, we have ensured equal number of samples in each CAP phase. This means that the number of samples is the same across the subphases of A-phases in Table 3, before ensuring that the number of samples are equal for A- & B-phases. The samples in the balanced datasets were chosen at random for consistency purposes [25].

## 2.2 Experiment setup

The workflow of the experimental setup is shown in Fig. 2. After segmentation of the raw EEG recordings, the dataset was preprocessed by standardization of EEG signals to mean

**Table 1** Summary of the total number of samples in sleep dataset for (a) 5-classes and (b) 3 -classes

(a)	Subjects	W	S1	S2	SWS	REM	Total
	N1	39	35	513	321	239	1147
	N2	143	141	369	197	151	1001
	N3	136	50	350	280	188	1004
	N5	10	50	413	305	232	1010
	N10	67	2	262	313	215	859
	N11	56	6	266	346	380	1054
	Total	451	284	2173	1762	1405	6075

(b)	Subjects	W	NREM	REM	Total
	N1	39	869	239	1147
	N2	143	707	151	1001
	N3	136	680	188	1004
	N5	10	768	232	1010
	N10	67	577	215	859
	N11	56	618	380	1054
	Total	451	4219	1405	6075



t3.1

**Table 3** Summary of the total number of samples for balanced CAP dataset

Subject	A1	A2	A3	A-phase	B-phase	Total
N1	354	354	354	1062	1062	2124
N2	327	327	327	981	981	1962
N3	284	284	284	852	852	1704
N5	157	157	157	471	471	942
N10	159	159	159	477	477	954
N11	270	270	270	810	810	1620
Total	1551	1551	1551	4653	4653	9306

t3.2

t3.3

t3.4

t3.5

t3.6

t3.7

t3.8

t3.9

of 0 and standard deviation of 1. Subsequently, the dataset was split into training set (70%), validation set (15%) and test set (15%). Training and validation were initially used during hyperparameter optimization to determine the layer parameters of proposed model. Once the model architecture was fixed, the proposed model was trained 50 times with the training set, and the best model was saved at highest validation accuracy obtained during model training. The test set was then used to evaluate the performance of the saved best model.

However, an exception was applied for unbalanced CAP dataset; the unbalanced CAP dataset was not used to train the model, hence it was not split into the respective train, validation, and test sets. Instead, the proposed model was trained with the training set of balanced CAP dataset, while the performance of the model was evaluated twice using the test set of balanced datasets and the entire unbalanced CAP dataset. In other words, the unbalanced CAP datasets served as a secondary test set to evaluate model performance for CAP detection.


2.3 Proposed deep learning model (1D-CNN)

A typical 1D-CNN model consists of convolutional and pooling layers that are responsible for feature extraction and the operation of the convolutional layer can be described by the following formula [38]:

$$(S*W)_n = \sum_{i=1}^{|W|} W(i)S(i+n-1)$$

where  $S$ ,  $W$  and  $*$  represent the 1D input signal, kernel and discrete convolution operation. The dimension of

Fig. 2 Workflow of experimental setup






Fig. 3 Proposed 1D-CNN model architecture

the kernel in 2D-CNN is denoted as  $W(i, j)$  but for 1D-CNN, only  $W(i)$  is concerned. The kernel ( $W$ ) is also the weights in any CNN model and the weights are updated every time the kernel slides over the input signals. The kernel output the feature maps once it runs through the input signals.

The output feature map ( $O$ ) can be described by the following formula:

$$O'_n = (S_{W(i)} * W(i))_n \quad (2)$$

The features maps are further processed by multiple convolutional and pooling layers to make the features more distinct, thereby increasing the recognition and classification ability of 1D-CNN models. The processed feature maps are then flattened into single list vectors before entering the fully connected layers where classification takes place. The model architecture for the proposed model is based on 1D-CNN and is illustrated in Fig. 3. The details of the layer parameters and hyperparameters are provided in Tables 4 and 5, respectively. The proposed model starts

Table 4 Detail of layers in proposed 1D-CNN model

No.	Layer	No. filter	Kernel size	Unit size	Parameter	Output (CAP)	Output (Sleep)
1	1DConv1	64	9	—	ReLu, Stride=3	64×339	64×5118
2	BatchNorm	—	—	—	—	64×339	64×5118
3	1DConv2	128	7	—	ReLu, Stride=1	128×333	128×5112
4	BatchNorm	—	—	—	—	128×333	128×5112
5	1DConv3	256	3	—	ReLu, Stride=1	256×331	256×5110
6	BatchNorm	—	—	—	—	256×331	256×5110
7	MaxPool	—	—	2	Stride=2	256×165	256×2555
8	1DConv4	128	13	—	ReLu, Stride=1	128×153	128×2543
9	BatchNorm	—	—	—	—	128×153	128×2543
10	MaxPool	—	—	2	Stride=2	128×76	128×1271
11	1DConv5	64	3	—	ReLu, Stride=1	64×74	64×1269
12	BatchNorm	—	—	—	—	64×74	64×1269
13	MaxPool	—	—	2	Stride=2	64×37	64×634
14	1DConv6	32	2	—	ReLu, Stride=1	32×36	32×633
15	BatchNorm	—	—	—	—	32×36	32×633
16	MaxPool	—	—	2	Stride=2	32×18	32×316
17	Dropout	—	—	—	Rate=0.7	32×18	32×316
18	Flatten	—	—	—	—	1×576	1×10,112
19	Dense	—	—	64	ReLu	1×64	1×64
20	Dropout	—	—	—	Rate=0.2	1×64	1×64
21	Dense	—	—	16	ReLu	1×16	1×16
22	Dropout	—	—	—	Rate=0.2	1×16	1×16
23	Dense	—	—	64	ReLu	1×64	1×64
24	Dense	—	—	num_class	Softmax	1 x num_class	1 x num_class

t5.1

Table 5 Details of hyperparameters in proposed 1D-CNN model		
Hyperparameters		
t5.3	Batch size	64
t5.4	Kernel regularizer (l2)	0.005
t5.5	Optimizer	Adam
t5.6	Learning rate	0.001
t5.7	Decay rate	0.01
t5.8	Loss function	Categorical crossentropy

t6.1

Table 6 Training time of proposed 1D-CNN model in each respective sleep and CAP dataset		
Datasets ( <i>EEG signals</i> )		Training time (hh:mm:ss)
Sleep dataset		05:40:02
Balanced CAP dataset		00:23:24

t6.2

t6.3

t6.4


with a series of 3 convolutional layers followed by another 3 convolutional layers with 4 pooling layers placed in between them. Consider the example of CAP detection, the input segment duration of 2 s with 1024 timesteps are convoluted into 64 feature maps with the length of 339 in the first convolutional layer. The example of the resulting feature maps generated by 6 convolutional layers in the proposed model, is illustrated in Fig. 4. By the time it reaches the last pooling layer, 32 feature maps with the length of 18 is generated. The flatten layer converts the 32 feature maps from the last pooling layer into single-list vectors with the length of 576, which is used to train the neurons in the fully connected layers.

To prevent overfitting of the proposed model, batch normalization is done after every convolutional layer and the regularizer (l2) of each kernel is set to 0.005. Dropout layers are also introduced in between the fully connected layers to prevent overfitting. Finally, the last layer of the proposed model is a SoftMax classifier which contains the same number of neurons as the number of classes for sleep stages (3 classes) and CAP (2 classes) respectively. SoftMax classifier generates probability scores which indicate the likelihood in which the

single list vectors are classified into. For instance, a single list vector may have a probability score of 0.85 for A-phase and 0.15 for B-phase, respectively. The sum of the probability score for all the classes will always equate to 1.0. Adam optimizer with 0.001 learning rate and 0.01 decay rate is used in the proposed model.

The proposed model is created using Keras (v2.3.1) with Tensorflow (v1.14.0) backend, and both are deep learning tools from Python programming language. The specification of the computer used to train and evaluate the model is as follows: Intel Core i7–10875H CPU, RTX 2070 Super 8GB, 32GB RAM, and 500GB NVMe SSD. The training time for each dataset is shown in Table 6.


The parameters in Tables 4 and 5 are decided through numerous trials and errors. An example of layer parameters and hyperparameters optimization is shown in Fig. 5, where the parameters of 64, 128, and 256 filter number for the 2nd convolutional layer is tested. For each filter number, the model is trained and evaluated for 5 rounds with training and validation set respectively. The box and whiskers plot summarizing the mean, median, and standard deviation for each parameter is summarised in Fig. 5. From the plot in Fig. 5, the filter number of 128 is chosen for the 2nd convolutional layer because it has the highest overall accuracy and lowest standard deviation.



**Fig. 4** Feature maps obtained from the convolutional layers in the proposed model during model training for CAP detection. **a** Input EEG signal, and feature map of the **b** 1st convolutional layer, **c** 2nd

convolutional layer, **d** 3rd convolutional layer, **e** 4th convolutional layer, **f** 5th convolutional layer, and **g** 6th convolutional layer

Fig. 5 Hyperparameter optimization for the 2nd convolutional layer in Table 4



## 3 Results

This section reports the major findings of the experiment. The experimental results for sleep stages classification is presented in Section 3.1. CAP detection results are described in Sections 3.2 and 3.3 summarizes the major findings of this work.

### 3.1 Sleep stages classification

The sleep dataset was split into training, validation, and test set with the ratio of 70:15:15, respectively. The proposed model was trained with training set for 50 epochs and the ‘best model’ was saved when highest validation accuracy is obtained during model training. The test set is unknown to the proposed model and was used to evaluate the performance of the ‘best model’.

The ‘best model’ was saved at validation accuracy of 90.34%, and the resulting test accuracy and performance parameters are shown in Table 7. It can be noted that the proposed model achieved high precision rate of 97.11% and sensitivity of 95.73% for NREM and REM sleep, respectively. Higher precision rate indicates that the proposed model can correctly predict NREM sleep more than the other two sleep stages. This can be observed from the confusion matrix in Fig. 6, where the proposed model correctly predicted 571 NREM sleep samples compared to W stage (52 samples) and REM sleep (202 samples). However, this is within expectation since NREM sleep has the largest number of samples compared to the other two sleep stages. On the other hand, higher sensitivity indicates that the proposed model can

correctly predict the majority of REM sleep within the same class. This can also be seen from the confusion matrix in Fig. 6, where the proposed model misclassified 9 out of 211 REM sleep samples, while the other sleep stages have large number of misclassifications.

### 3.2 CAP detection

The experiment for CAP detection differs from sleep stages classification as there are two different datasets: unbalanced and balanced CAP dataset. Likewise, the balanced CAP dataset is split into training, validation, and test set with the ratio of 70:15:15. However, the performance of the proposed model is evaluated twice with the test set of balanced CAP dataset and the entire unbalanced CAP dataset. Similarly, the ‘best model’ for CAP detection was obtained with validation accuracy of 74.43%, and the resulting performance parameters are shown in Table 8.

Unlike multiclass problem in sleep stages classification, CAP detection is a binary classification problem. The precision of the model is the ability to refrain from classifying the negative samples (B-phases) as positive samples (A-phases) [42]. The sensitivity of the model is the ability to correctly identify A-phases, while specificity of the model focuses on the ability to correctly identify B-phases [42]. From Table 8, high model sensitivity is observed in balanced CAP dataset (80.29%), hence highlighting the ability of the proposed model to identify A-phases. The model sensitivity was also consistently high when evaluated with unbalanced CAP dataset (92.06%). This is crucial because A-phases occupy only

**Table 7** Model accuracies (%) and various performance values (%) for sleep stages classification. Performance values corresponds to test accuracy

Accuracy		Sleep stages	Precision	Sensitivity	F1	Samples
Training	98.71	W	75.34	76.46	75.91	68
Validation	90.34	NREM	97.11	90.21	93.53	633
Test	<b>90.46</b>	REM	79.22	95.73	86.70	211






Fig. 6 Confusion matrix sleep stages classification

12.6% of the unbalanced CAP dataset; from the confusion matrix in Fig. 7, the proposed model is able to detect 8333 out of 9052 A-phase samples correctly.

However, the remaining B-phases occupy 87.4% of the unbalanced dataset generated large data noise that hindered the ability of the model to correctly distinguish B-phases from A-phase. Hence, the other performance parameters such as classification accuracy, precision, and specificity were compromised (Table 8).

### 3.3 Summary of results

The results for sleep stages classification and CAP detection are summarized in Table 9. The performance parameters obtained for sleep stages classification is shown in Table 9 are the average performance values of all three sleep stages presented in Table 7. Generally, there is a trade-off between model precision and sensitivity [43]; high sensitivity of 92.06% and low precision of 20.13% is obtained when the proposed model is evaluated with the unbalanced CAP dataset (Table 9). Hence, F1-score can be used to assess the ability of the model to achieve balance between precision and sensitivity [43]. F1-score is commonly used to evaluate unbalanced datasets due to the non-uniform distribution of class labels [43].

For sleep stages classification, the proposed model achieved high average F1-score of 85.38% (Table 9), indicating that the proposed model has managed to achieve equilibrium between precision and sensitivity. Hence, the model can effectively

capture the EEG characteristics rhythms for the three sleep stages. As for CAP detection, F1-score was moderately high in balanced CAP dataset (75.34%), however, low F1-score of 33.04% is observed when proposed model is evaluated with unbalanced CAP dataset (Table 9). This indicates that the proposed model was affected due to the presence of noise from the B-phases which comprised of 87.4% of the dataset.


The performance graph for sleep stages classification and CAP detection is shown in Fig. 8. Smaller gap between training and validation accuracy is observed for CAP detection as compared to sleep stages classification, indicating that the proposed model is more prone overfitting problem when training to classify sleep stages. This is may be due to the use of smaller dataset (6075 samples) for sleep stages classification. Nonetheless, the gap between training and validation accuracy for sleep stages classification remained the same and validation accuracy was stable at around 90%. Hence, the proposed model may be slightly overfitted for sleep stages classification without much compromising on the model performance.

## 4 Discussion

Many 3-class sleep stages classification studies have been reported based on machine learning and deep learning methods using two popular sleep databases: Sleep-EDF and Sleep-EDFX [19, 41]. To the best of our knowledge, this is the first study to use CAPSLPDB for 3-class sleep stages classification. Table 10 shows the novelty of this work compared to the other sleep stages classification studies. In this study 6075 samples of EEG signals were used which was lower than other reported studies using sleep-EDF database. However, it may be noted that the studies conducted using Sleep-EDF and Sleep-EDFX databases obtained the classification accuracy between 92% to 95%, while the classification accuracy obtained in this study for 3-class sleep stages classification was 90.46%. This might be due to the high sampling frequency (512 Hz) of the EEG signals used in this study which is five times higher than the other studies (100 Hz). Another reason may be the number of samples; 6075 samples were used in this study while other studies used 14,963 to 127,512 samples. Nonetheless, our proposed model was able to recognize the EEG characteristic rhythm of three sleep stages using EEG

Table 8 Model accuracies (%) and various performance values (%) for CAP detection. Performance values corresponds to test accuracy

Dataset	Accuracy (%)			Performance parameter (%)			
	Train	Validation	Test	Precision	Sensitivity	F1	Specificity
Balanced	75.93	74.43	73.64	70.96	80.29	75.34	66.95
Unbalanced	–	–	52.99	20.13	92.06	33.04	47.36



**Fig. 7** Confusion matrix for test set of balanced CAP dataset and complete unbalanced CAP dataset

**Table 9** Summary of results (%) obtained from sleep stages classification and CAP detection


Classifications	Dataset	Accuracy	Precision	Sensitivity	F1	Samples
Sleep stages	—	90.46	83.90	87.47	85.38	912
CAP	Balanced	73.64	70.96	80.29	75.34	1369
	Unbalanced	52.99	20.13	92.06	33.04	71,857

signals of higher sampling frequency (512 Hz) and achieved high model performance.

There are also numerous CAP detection studies which utilized EEG signals from CAPSLPDB, and they are summarized in Table 11. Our study used the same sampling frequency (512 Hz) and epoch duration (2 s) as Dhok et al. [25]. Hence, we have the same number of samples; 71,862 and 9306 for unbalanced and balanced data, respectively, as Dhok et al. [25]. Our proposed model performed marginally better in balanced dataset as compared to Dhok et al. [25]; our proposed model obtained classification accuracy of 73.64% and sensitivity of 80.29% while their proposed conventional machine learning model yielded the classification accuracy of

72.53% and sensitivity of 76.76%. However, developed model yielded higher classification accuracy of 87.45% using unbalanced dataset, as compared to our proposed deep learning model (52.99%). Despite having lower model accuracy, our proposed model obtained the highest sensitivity score of 92.06% using standardized EEG signals with unbalanced dataset. Our proposed model correctly identified the minority A-phases (12.6% of unbalanced dataset) better than the other studies as shown in Table 11.

To date, only Hartmann et al. [40] have proposed deep learning model based on LSTM using EEG signals sampled at 128 Hz sampling frequency. Hence, this study is the first to employ deep learning model based on 1D-CNN for



**Fig. 8** Performance graph (model accuracy) of sleep stages classification and CAP detection during model training



**Table 10** Summary of automated sleep stages classification studies that uses 3 classes (W, NREM, and REM)

Author	Database	Sampling frequency	Approach	No. of samples	Accuracy (%)
da Silveira et al. [44]	Sleep-EDFX	100 Hz	DWT+RF	106,376	93.90
Yildirim et al. [38]	Sleep-EDFX	100 Hz	1D-CNN	127,512	94.23
Hassan et al. [45]	Sleep-EDF	100 Hz	EEMD+RUSBoost	15,188	94.23
Hassan et al. [46]	Sleep-EDF	100 Hz	CEEMDAN+ Bagging	15,188	94.10
Zhu et al. [47]	Sleep-EDF	100 Hz	HVG+SVM	14,963	92.60
Sharma et al. [48]	Sleep-EDF	100 Hz	Wavelet filter+SVM	15,139	93.50
Yildirim et al. [38]	Sleep-EDF	100 Hz	1D-CNN	15,188	94.20
This work	CAPSLPDB	512 Hz	1D-CNN	6075	90.46

CAP detection using EEG signals of 512 Hz sampling frequency.

In addition, conventional machine learning models require features to be extracted from the PSG recordings, and the model may overfit if high dimensional PSG recordings are used to train the model [53, 54]. However, feature extraction may result in information loss as PSG recordings are converted to a lower-dimensional feature vector [53]. Also, the feature extraction procedure is done manually which is more tedious, subjective and laborious [55]. Therefore, our proposed deep learning model successfully addressed these limitations by eliminating the need for feature extraction.

The notable aspects of our proposed model are given as follows:

- The same layer parameters and hyperparameters were used for both 3-class sleep stages classification and CAP detection, and high model performance was achieved.
- The proposed model was able to capture the EEG characteristic rhythms of three sleep stages and CAP.

- The multifunctional CAD tool comprised of two stages. The first stage separates sleep EEG recordings into three sleep stages (W, NREM and REM) and acts as a filter to simultaneously remove W stage. Subsequently, the second stage detects CAP in NREM and REM sleep to obtain CAP rate, cycle and duration for sleep analysis.
- A completely automated system was successfully generated, thus removing the need for manual feature extraction.
- Large amount of data could be handled with minimal information loss [56].
- To the best of our knowledge, this is the first automated 3-class sleep stages classification study developed using EEG signals obtained from CAPSLPDB dataset. Furthermore, most of the automated CAP detection studies were done using lower sampling frequency as shown in Table 11. Hence, this is the first study to propose a deep learning model for both sleep stages classification and CAP detection using high sampling frequency of 512 Hz. There are no related papers in

**Table 11** Summary of CAP detection studies using CAPSLPDB database

Author	Approach	Sampling frequency	Datasets	Performance parameter (%)		
				Accuracy	Specificity	Sensitivity
Mendez et al. [39]	KNN classifier	100 Hz	Unbalanced	80.00	80.00	70.00
Navona et al. [49]	Thresholding	128 Hz	Unbalanced	77.00	90.00	84.00
Mariani et al. [50]	ANN classifier	100 Hz	Unbalanced 240,429	87.19	90.49	69.55
Mariani et al. [51]	SVM, LDA, AdaBoost and ANN	100 Hz	Unbalanced	84.90	86.60	72.50
Mendonça et al. [52]	Feed Forward Neural Network with Finite State Machine	—	Unbalanced ( $\approx 50,000$ )	79.00	80.00	76.00
Hartmann et al. [40]	Variable LSTM	128 Hz	Balanced and unbalanced	82.42	83.90	75.28
Dhok et al. [25]	Wigner-Ville based entropy features	512 Hz	Balanced A-phases: 4653 B-phases: 4653	72.53	69.19	76.76
			Unbalanced 71,862	87.45	52.09	87.75
This work	1D-CNN	512 Hz	Balanced A-phases: 700 B-phases: 696	73.64	66.95	80.29
			Tested with unbalanced data (71862)	52.99	47.36	92.06

this topic for us to do a fair comparison with due to the novelty of our work.

The limitations of this study are as follows:

- Elimination of noise is extremely challenging, especially in unbalanced CAP dataset as B-phases comprise of 87.4% of the dataset. For this reason, the proposed model was not trained with unbalanced CAP dataset because of the overwhelming number of samples in B-phases had generated data noise that causes our proposed model to predict every sample as B-phases, thus hindering the detection of A-phases.

## 5 Future work

Our proposed work can be extended in the following ways:

- Consider other physiological signals like electrooculogram (EOG) and electromyogram (EMG) recordings for 3-class sleep stages classification.
- Develop hybrid deep learning models such as the combination of CNN and LSTM for CAP detection since LSTM is known for its ability to learn and predict patterns in sequence.
- Build a cloud-compatible deep learning system so that the CAD tool can conveniently access the required data and apply it immediately.
- Real-time PSG recordings will also be considered for wearable devices that use real time data to track sleep.

## 6 Conclusion

In this study, we proposed a deep learning model based on 1D-CNN for 3-class sleep stages and CAP detection, using EEG recordings of a high sampling frequency (512 Hz). The proposed model consists of multiple 1D-convolutional and pooling layers which will extract the salient features from EEG signals of various sleep stages and CAP. Subsequently, the extracted features are used to train the neurons in the fully connected layers for the classification of sleep stages and CAP detection. The developed model achieved good model performance for sleep stages classification, yielding an accuracy of 90.46%, precision of 83.90%, sensitivity of 87.47, and F1-score of 85.38%. The model yielded the classification accuracy of 73.64% for balanced CAP dataset, and 52.99% for unbalanced CAP dataset. Our proposed system obtained a sensitivity score of 92.06% using unbalanced CAP dataset due to its ability to identify 11.6% out of 12.6% of A-phases in the entire unbalanced

CAP dataset. Hence, the proposed two-stage model is sensitive to the EEG characteristic rhythms of both macro-and micro signatures of sleep EEG signals. The first stage breaks down sleep EEG signals into 3 sleep stages and the second stage respective sleep stages are identified automatically. However, the proposed model need to be tested with more data before the clinical application. In future, we intend to improve the model performance by using electrooculogram (EOG) and electromyogram (EMG) recordings for sleep stages classification.

**Author contributions** All authors contributed to this article. The idea for the article was provided by HWL and URA. SGD provided MATLAB code for data preparation. HWL developed and the model and drafted the first manuscript. Subsequently, CPO, SGD, MS, AAB, and URA edited the manuscript and provided suggestions to improve the manuscript.

## Declarations

**Conflict of interest** The authors declare that they have no conflicts of interest.

## References

1. Cho JW, Duffy JF (2019) Sleep, sleep disorders, and sexual dysfunction. In world journal of men's health. Korean Society for Sexual Medicine and Andrology 37(3):261–275. <https://doi.org/10.5534/wjmh.180045>
2. Colten HR, Altevogt BM (2006) Institute of Medicine (US) committee on sleep medicine and research (ed) sleep disorders and sleep deprivation: an unmet public health problem. National Academies Press (US). <https://doi.org/10.17226/11617>
3. Peppard PE, Young T, Barnet JH, Palta M, Hagen EW, Hla KM (2013) Increased prevalence of sleep-disordered breathing in adults. Am J Epidemiol 177(9):1006–1014. <https://doi.org/10.1093/aje/kws342>
4. Roth T (2007) Insomnia: definition, prevalence, etiology, and consequences. J Clin Sleep Med 3(5 Suppl):S7–S10 <http://www.ncbi.nlm.nih.gov/pubmed/17824495>
5. Redline S, Yenokyan G, Gottlieb DJ, Shahar E, O'Connor GT, Resnick HE, Diener-West M, Sanders MH, Wolf PA, Geraghty EM, Ali T, Lebowitz M, Punjabi NM (2010) Obstructive sleep apnea-hypopnea and incident stroke. Am J Respir Crit Care Med 182(2):269–277. <https://doi.org/10.1164/rccm.200911-1746OC>
6. Khan MS, Aouad R (2017) The effects of insomnia and sleep loss on cardiovascular disease. Sleep Med Clin 12(2):167–177. <https://doi.org/10.1016/j.jsmc.2017.01.005>
7. Hargens TA, Kaleth AS, Edwards ES, Butner KL (2013) Association between sleep disorders, obesity, and exercise: a review. Nat Sci Sleep 1(5):27–35. <https://doi.org/10.2147/NSS.S34838>
8. Stranges S, Tigbe W, Gómez-Olivé FX, Thorogood M, Kandala NB (2012) Sleep problems: an emerging global epidemic? Findings from the INDEPTH WHO-SAGE study among more than 40,000 older adults from 8 countries across Africa and Asia. Sleep 35(8):1173–1181. <https://doi.org/10.5665/sleep.2012>
9. Koyanagi A, Stickley A (2015) The association between sleep problems and psychotic symptoms in the general population: a global perspective. Sleep 38(12):1875–1885. <https://doi.org/10.5665/sleep.5232>

- 630 10. Chattu VK, Manzar MD, Kumary S, Burman D, Spence DW, 695  
631 Pandi-Perumal SR (2018) The global problem of insufficient sleep 696  
632 and its serious public health implications. *Healthcare* 7(1):1. <https://doi.org/10.3390/healthcare7010001> 697
- 633 11. Loh HW, Ooi CP, Vignes J, Oh SL, Faust O, Gertych A, Acharya 698  
634 UR (2020) Automated detection of sleep stages using deep learning 699  
635 techniques: a systematic review of the last decade (2010–2020). 700  
636 *Appl Sci* 10(24):8963. <https://doi.org/10.3390/app10248963> 701
- 637 12. Hori T, Sugita Y, Koga E, Shirakawa S, Inoue K, Uchida S, 702  
638 Kuwahara H, Kousaka M, Kobayashi T, Tsuji Y, Terashima M, 703  
639 Fukuda K, Fukuda N, Sleep Computing Committee of the Japanese 704  
640 Society of Sleep Research Society (2001) Proposed supplements 705  
641 and amendments to “a manual of standardized terminology, tech- 706  
642 niques and scoring system for sleep stages of human subjects”, the 707  
643 Rechtschaffen & Kales (1968) standard. *Psychiatry Clin Neurosci* 708  
644 55(3):305–310. <https://doi.org/10.1046/j.1440-1819.2001.00810.x> 709
- 645 13. Iber C, Ancoli-Israel S, Chesson AL, Quan SF (2007) The AASM 710  
646 manual for the scoring of sleep and associated events: rules, termi- 711  
647 nology and technical specification. Darien, IL, USA, American 712  
648 Academy of Sleep Medicine 713
- 649 14. Carley DW, Farabi SS (2016) Physiology of sleep. *Diabetes Spectr* 714  
650 29(1):5–9. <https://doi.org/10.2337/diaspect.29.1.5> 715
- 651 15. Brain Basics: Understanding Sleep. National Institute of 716  
652 Neurological Disorders and Stroke. [https://www.ninds.nih.gov/](https://www.ninds.nih.gov/Disorders/patient-caregiver-education/Understanding-sleep) 717  
653 [Disorders/patient-caregiver-education/Understanding-sleep](https://www.ninds.nih.gov/Disorders/patient-caregiver-education/Understanding-sleep). 718  
654 Accessed 17-Oct-2020 719
- 655 16. Gais S, Mölle M, Helms K, Born J (2002) Learning-dependent 720  
656 increases in sleep spindle density. *J Neurosci* 22(15):6830–6834. 721  
657 <https://doi.org/10.1523/JNEUROSCI.22-15-06830.2002> 722
- 658 17. Takahara M, Kanayama S, Nittono H, Hori T (2006) REM sleep 723  
659 EEG pattern: examination by a new EEG scoring system for REM 724  
660 sleep period. *Sleep Biol Rhythms* 4(2):105–110. <https://doi.org/10.1111/j.1479-8425.2006.00201.x> 725
- 661 18. Schulz H (2008) Rethinking sleep analysis. *J Clin Sleep Med* 4(2): 726  
662 99–103 727
- 663 19. Kemp B, Zwiderman AH, Tuk B, Kamphuisen HA, Oberyé JJ 728  
664 (2000) Analysis of a sleep-dependent neuronal feedback loop: the 729  
665 slow-wave microcontinuity of the EEG. *IEEE Trans Biomed Eng* 730  
666 47(9):1185–1194. <https://doi.org/10.1109/10.867928> 731
- 667 20. Pardey J, Roberts S, Tarassenko L, Stradling J (1996) A new ap- 732  
668 proach to the analysis of the human sleep/wakefulness continuum. *J* 733  
669 *Sleep Res* 5(4):201–210. <https://doi.org/10.1111/j.1365-2869.1996.00201.x> 734
- 670 21. Halász P (1998) Hierarchy of micro-arousals and the microstructure 735  
671 of sleep. *Neurophysiol Clin Neurophysiol* 28(6):461–475. [https://doi.org/10.1016/S0987-7053\(99\)80016-1](https://doi.org/10.1016/S0987-7053(99)80016-1) 736
- 672 22. Terzano MG, Mancina D, Salati MR, Costani G, Decembrino A, 737  
673 Parrino L (1985) The cyclic alternating pattern as a physiologic 738  
674 component of normal NREM sleep. *Sleep* 8(2):137–145. <https://doi.org/10.1093/sleep/8.2.137> 739
- 675 23. Terzano MG, Parrino L, Sherieri A, Chervin R, Chokroverty S, 740  
676 Guillemineault C, Hirshkowitz M, Mahowald M, Moldofsky H, 741  
677 Rosa A, Thomas R, Walters A (2001) Atlas, rules, and recording 742  
678 techniques for the scoring of cyclic alternating pattern (CAP) in 743  
679 human sleep. *Sleep Med* 2(6):537–553. [https://doi.org/10.1016/S1389-9457\(01\)00149-6](https://doi.org/10.1016/S1389-9457(01)00149-6) 744
- 680 24. Machado F, Sales F, Santos C, Dourado A, Teixeira CA (2018) A 745  
681 knowledge discovery methodology from EEG data for cyclic alter- 746  
682 nating pattern detection. *Biomed Eng Online* 17(1):185. <https://doi.org/10.1186/s12938-018-0616-z> 747
- 683 25. Dhok S, Pimpalkhute V, Chandurkar A, Bhurane AA, Sharma M, 748  
684 Acharya UR (2020) Automated phase classification in cyclic alter- 749  
685 nating patterns in sleep stages using Wigner–Ville distribution 750  
686 based features. *Comput Biol Med* 119:103691. <https://doi.org/10.1016/j.compbiomed.2020.103691> 751
- 687 26. Parrino L, Ferri R, Bruni O, Terzano MG (2012) Cyclic alternating 752  
688 pattern (CAP): the marker of sleep instability. *Sleep Med Rev* 753  
689 16(1):27–45. <https://doi.org/10.1016/j.smrv.2011.02.003> 754
- 690 27. Korkmaz S, Bilecenoglu NT, Aksu M, Yoldas TK (2018) Cyclic 755  
691 alternating pattern in obstructive sleep apnea patients with versus 756  
692 without excessive sleepiness. *Sleep Disord* 2018:1–7. <https://doi.org/10.1155/2018/8713409> 757
- 693 28. Parrino L, Halasz P, Tassinari CA, Terzano MG (2006) CAP, epi- 758  
694 lepsy and motor events during sleep: the unifying role of arousal. 759  
695 *Sleep Med Rev* 10(4):267–285. <https://doi.org/10.1016/j.smrv.2005.12.004> 760
- 696 29. Thomas RJ (2003) Arousals in sleep-disordered breathing: patterns 761  
697 and implications. *Sleep* 26(8):1042–1047. <https://doi.org/10.1093/sleep/26.8.1042> 762
- 698 30. Kassab MY, Farooq MU, Diaz-Arrastia R, Van Ness PC (2007) 763  
699 The clinical significance of EEG cyclic alternating pattern during 764  
700 coma. *J Clin Neurophysiol* 24(6):425–428. <https://doi.org/10.1097/WNP.0b013e31815a028e> 765
- 701 31. Michielli N, Acharya UR, Molinari F (2019) Cascaded LSTM re- 766  
702 current neural network for automated sleep stage classification 767  
703 using single-channel EEG signals. *Comput Biol Med* 106:71–81. 768  
704 <https://doi.org/10.1016/j.compbiomed.2019.01.013> 769
- 705 32. Tripathy RK, Acharya UR (2018) Use of features from RR-time 770  
706 series and EEG signals for automated classification of sleep stages 771  
707 in deep neural network framework. *Biocybern Biomed Eng* 38(4): 772  
708 890–902. <https://doi.org/10.1016/j.bbe.2018.05.005> 773
- 709 33. Cimr D, Studnicka F, Fujita H, Cimler R, Slegr J (2021) 774  
710 Application of mechanical trigger for unobtrusive detection of re- 775  
711 spiratory disorders from body recoil micro-movements. *Comput* 776  
712 *Methods Prog Biomed* 106149:106149. <https://doi.org/10.1016/j.cmpb.2021.106149> 777
- 713 34. Svetnik V, Ma J, Soper KA, Doran S, Renger JJ, Deacon S, Koblan 778  
714 KS (2007) Evaluation of automated and semi-automated scoring of 779  
715 Polysomnographic recordings from a clinical trial using Zolpidem 780  
716 in the treatment of insomnia. *Sleep* 30(11):1562–1574. <https://doi.org/10.1093/sleep/30.11.1562> 781
- 717 35. Pittman SD, MacDonald MM, Fogel RB, Malhotra A, Todros K, 782  
718 Levy B, Geva AB, White DP (2004) Assessment of automated 783  
719 scoring of polysomnographic recordings in a population with 784  
720 suspected sleep-disordered breathing. *Sleep* 27(7):1394–1403. 785  
721 <https://doi.org/10.1093/sleep/27.7.1394> 786
- 722 36. Anderer P, Gruber G, Parapatics S, Woertz M, Miazhynskaia T, 787  
723 Klossch G, Saletu B, Zeithofer J, Barbanoj MJ, Danker-Hopfe H, 788  
724 Himanen SL, Kemp B, Penzel T, Grozinger M, Kunz D, 789  
725 Rappelsberger P, Schlogl A, Dorffner G (2005) An E-health solu- 790  
726 tion for automatic sleep classification according to Rechtschaffen 791  
727 and kales: validation study of the Somnolyzer 24 × 7 utilizing the 792  
728 siesta database. *Neuropsychobiology* 51(3):115–133. <https://doi.org/10.1159/000085205> 793
- 729 37. Rahman MM, Bhuiyan MIH, Hassan AR (2018) Sleep stage clas- 794  
730 sification using single-channel EOG. *Comput Biol Med* 102:211– 795  
731 220. <https://doi.org/10.1016/j.compbiomed.2018.08.022> 796
- 732 38. Yildirim O, Baloglu UB, Acharya UR (2019) A deep learning 797  
733 model for automated sleep stages classification using PSG signals. 798  
734 *Int J Environ Res Public Health* 16(4). <https://doi.org/10.3390/ijerph16040599> 799
- 735 39. Mendez MO, Chouvarda I, Alba A, Bianchi AM, Grassi A, Arce- 800  
736 Santana E, Milioli G, Terzano MG, Parrino L (2016) Analysis of A- 801  
737 phase transitions during the cyclic alternating pattern under normal 802  
738 sleep. *Med Biol Eng Comput* 54(1):133–148. <https://doi.org/10.1007/s11517-015-1349-9> 803
- 739 40. Hartmann S, Baumert M (2019) Automatic A-phase detection of 804  
740 cyclic alternating patterns in sleep using dynamic temporal infor- 805  
741 mation. *IEEE Trans Neural Syst Rehabil Eng* 27(9):1695–1703. 806  
742 <https://doi.org/10.1109/TNSRE.2019.2934828> 807

41. Goldberger AL, Amaral LA, Glass L, Hausdorff JM, Ivanov PC, Mark RG, Mietus JE, Moody GB, Peng CK, Stanley HE (2000) PhysioBank, PhysioToolkit, and PhysioNet: components of a new research resource for complex physiologic signals. *Circulation* 101(23):E215–E220. <https://doi.org/10.1161/01.cir.101.23.e215>
42. Sokolova M, Lapalme G (2009) A systematic analysis of performance measures for classification tasks. *Inf Process Manag* 45(4): 427–437. <https://doi.org/10.1016/j.ipm.2009.03.002>
43. Lipton ZC, Elkan C, Naryanaswamy B (2014) Optimal thresholding of classifiers to maximize F1 measure. *Mach Learn Knowl Discov Databases* 8725:225–239. [https://doi.org/10.1007/978-3-662-44851-9\\_15](https://doi.org/10.1007/978-3-662-44851-9_15)
44. da Silveira TL, Kozakevicius AJ, Rodrigues CR (2017) Single-channel EEG sleep stage classification based on a streamlined set of statistical features in wavelet domain. *Med Biol Eng Comput* 55(2):343–352. <https://doi.org/10.1007/s11517-016-1519-4>
45. Hassan AR, Bhuiyan MIH (2017) Automated identification of sleep states from EEG signals by means of ensemble empirical mode decomposition and random under sampling boosting. *Comput Methods Prog Biomed* 140:201–210. <https://doi.org/10.1016/j.cmpb.2016.12.015>
46. Hassan AR, Bhuiyan MIH (2016) Computer-aided sleep staging using complete ensemble empirical mode decomposition with adaptive noise and bootstrap aggregating. *Biomed Signal Process Control* 24:1–10. <https://doi.org/10.1016/j.bspc.2015.09.002>
47. Zhu G, Li Y, Wen P (2014) Analysis and classification of sleep stages based on difference visibility graphs from a single-channel EEG signal. *IEEE J Biomed Health Inform* 18(6):1813–1821. <https://doi.org/10.1109/JBHI.2014.2303991>
48. Sharma M, Goyal D, Achuth PV, Acharya UR (2018) An accurate sleep stages classification system using a new class of optimally time-frequency localized three-band wavelet filter bank. *Comput Biol Med* 98:58–75. <https://doi.org/10.1016/j.compbiomed.2018.04.025>
49. Navona C, Barcaro U, Bonanni E, Di Martino F, Maestri M, Murri L (2002) An automatic method for the recognition and classification of the A-phases of the cyclic alternating pattern. *Clin Neurophysiol* 113(11):1826–1831. [https://doi.org/10.1016/S1388-2457\(02\)00284-5](https://doi.org/10.1016/S1388-2457(02)00284-5)
50. Mariani S, Grassi A, Mendez MO, Milioli G, Parrino L, Terzano MG, Bianchi AM (2013) EEG segmentation for improving automatic CAP detection. *Clin Neurophysiol* 124(9):1815–1823. <https://doi.org/10.1016/j.clinph.2013.04.005>
51. Mariani S, Manfredini E, Rosso V, Grassi A, Mendez MO, Alba A, Matteucci M, Parrino L, Terzano MG, Cerutti S, Bianchi AM (2012) Efficient automatic classifiers for the detection of a phases of the cyclic alternating pattern in sleep. *Med Biol Eng Comput* 50(4):359–372. <https://doi.org/10.1007/s11517-012-0881-0>
52. Mendonça F, Fred A, Mostafa SS, Morgado-Dias F, Ravelo-García AG (2018) Automatic detection of cyclic alternating pattern. *Neural Comput Appl*. <https://doi.org/10.1007/s00521-018-3474-5>
53. Faust O, Hagiwara Y, Hong TJ, Lih OS, Acharya UR (2018) Deep learning for healthcare applications based on physiological signals: a review. *Comput Methods Prog Biomed* 161:1–13. <https://doi.org/10.1016/j.cmpb.2018.04.005>
54. Faust O, Razaghi H, Barika R, Ciaccio EJ, Acharya UR (2019) A review of automated sleep stage scoring based on physiological signals for the new millennia. *Comput Methods Prog Biomed* 176:81–91. <https://doi.org/10.1016/j.cmpb.2019.04.032>
55. Mirza B, Wang W, Wang J, Choi H, Chung NC, Ping P (2019) Machine learning and integrative analysis of biomedical big data. *Genes (Basel)* 10(2):87. <https://doi.org/10.3390/genes10020087>
56. Shoeibi A, Ghassemi N, Khodatars M, Jafari M, Hussain S, Alizadehsani R, Moridian P, Khosravi A, Hosseini-Nejad H, Rouhani M, Zare A, Khadem A, Nahavandi S, Atiya AF, Acharya UR (2020) Epileptic seizure detection using deep learning techniques: A Review. <http://arxiv.org/abs/2007.01276>

**Publisher's note** Springer Nature remains neutral with regard to jurisdictional claims in published maps and institutional affiliations.



## AUTHOR QUERIES

**AUTHOR PLEASE ANSWER ALL QUERIES.**

- Q1. Biography and photo are desired. Please provide if necessary.
- Q2. Please check if the provided cities are correct and presented correctly.
- Q3. Please check if all tables are correctly presented.

UNCORRECTED PROOF