ENVIROFLOW

TECHNICAL DATA SHEET

Car wash mat

Mobile, inflatable mat for washing vehicles



Description	The car wash mat prevents water with detergents from spilling and makes it easy to collect that water in suitable containers. It is also useful in a garage, to limit the spread of mud and snow. The walls of the mat are filled with air through the built-in two-way valve (Boston type). Thanks to the inflatable walls, a vehicle can drive on and off freely. For extra protection against mechanical damage, the mat can be fitted with drive-on strips.
Construction	The mat has a tray shape and is made of waterproof, multi-layer technical fabric with a PVC coating and a lacquer layer, in black. When filled with air, the walls take the shape of a cylinder, so the mat can hold more liquid. Filling and deflating is done through the two-way valve. The mat can have additional drive-on strips between its shorter walls. Their position matches the standard wheelbase of passenger cars.
Installation and inflation	Unfold the mat to its full size and remove the transport protection from the valves. Fill the mat with air through the Boston valve. This two-way valve keeps the air in the walls; a non-return flap prevents air from escaping if you pause filling. To fill, only unscrew the top cap. The air is released when the valve is fully unscrewed. An air pump is not included. **Note:** before a vehicle drives over a wall, make sure that wall is only half filled with air. Driving over a fully filled wall will damage the mat. The fabric withstands temperatures from −30 °C to +70 °C. Avoid unfolding or folding the mat in freezing temperatures: the fabric becomes stiff and is more easily damaged. The mat can be folded and moved many times, but this is when most damage occurs. During folding or maintenance, you may walk on the mat in shoes with soft soles.
Equipment	The car wash mat is made in one piece and has a Boston valve. Additional equipment is stated on the quotation or invoice.
Ground	Place the mat on a level, smooth surface without sharp edges. Clear the area beforehand.
Material	Polyester fabric (PES) with PVC coating and lacquer, black.

Technical data of the fabric

PROPERTY	VALUE	ACCORDING TO
Weight	900 g/m²	ISO 2286-2:1998
Tensile strength (warp / weft)	4,000 / 4,000 N per 5 cm	EN ISO 1421-1:1998
Tear strength (warp / weft)	600 / 500 N	DIN 53363
Cold resistance	−30 °C	DIN EN 1876-2:1998
Heat resistance	+70 °C	

Warranty	24 months from the date of delivery (as stated on the invoice), under the manufacturer's warranty conditions.
Service life	5 years or more. The actual service life depends on years of use, mechanical load, UV radiation, physical and chemical influences (substances other than those the mat is intended for) and how often and how carefully the mat is set up.
Repair in case of damage	Depending on the damage, there are several options: • wet, small damage (up to a few centimetres): repair clamp for tanks; • dry: a patch of the same PVC fabric with PVC adhesive; • dry, larger damage: welding with the correct PVC fabric (do not use substitutes).
Storage and cleaning	1. Avoid condensation: rinse the mat with clean water before folding it. 2. Let the water drain and let the mat air dry. 3. Do not store the mat where rodents can reach it. Clean the outside with soft means, such as a cloth or broom. Do not use a high-pressure cleaner.
Disposal	If the mat is worn or so damaged that repair is not worthwhile, clean it and take it to an industrial waste collection point as plastic waste (waste code 17 02 03). This is the responsibility of the buyer.

Standard sizes

LENGTH	WIDTH	WALL HEIGHT
6.00 m	3.00 m	0.10 m
8.00 m	4.00 m	0.10 m

The final dimensions and equipment are stated on the quotation or invoice. Other sizes or versions are available on request.

> Data from the manufacturer. Do you have a question about the car wash mat? Feel free to contact us.