ENVIROFLOW

TECHNICAL DATA SHEET

Vehicle decontamination mat

Mobile mat with inflatable walls for decontaminating vehicles



Description	The mobile decontamination mat has been designed for operations under chemical, biological, radiological and nuclear (CBRN) threats. It is intended for uniformed services (military, fire service, police, rescue services) and for organisations carrying out chemical rescue operations and critical infrastructure protection. The mat lets you quickly set up a vehicle decontamination station. It contains the decontamination liquid and the contaminated run-off generated when washing or neutralising contaminants.
Construction	The lightweight, mobile construction can be set up quickly without tools. The mat has inflatable walls 20 cm high. They keep the decontamination liquid and contaminants inside the mat, so you can work safely. The construction allows: • entry and exit of wheeled vehicles; • integration with mobile decontamination points.
Material	Durable EVA fabric of 1,000 to 1,365 g/m² (depending on the intended use), with high chemical and mechanical resistance, significantly exceeding typical PVC materials. A special lacquer extends its service life under UV exposure.
Installation and inflation	The walls are filled with air through the Boston valve. This two-way valve keeps the air in the walls; a non-return flap prevents air from escaping if you pause filling. To fill, only unscrew the top cap. The air is released when the valve is fully unscrewed. An air pump is not included. **Note:** about 24 hours after inflation, some air may naturally escape from the walls. Top up the air so the mat keeps its shape and function.
Siting	The fabric withstands temperatures from −30 °C to +70 °C. Avoid unfolding or folding the mat in freezing temperatures: the fabric becomes stiff and is more easily damaged. The mat can be folded and moved many times, but this is when most damage occurs. During folding, maintenance and operation, you may walk on the mat in footwear with soft plastic soles. Place the mat on a level surface without sharp edges and clear the area beforehand. On uneven surfaces (road slabs, paving stones) we recommend an additional underlay beneath the mat to limit mechanical damage.

Cleaning and storage	Avoid prolonged contact of substances with the fabric, as this may shorten its service life. If the mat is soiled with dust and sand, clean it the same way as when preparing it for storage. 1. Avoid condensation: before folding, clean the mat with a cleaning agent for plastic surfaces and rinse it with clean water. 2. Let the water drain and let the mat air dry. 3. Do not store the mat where rodents can reach it. Clean the mat with soft means, such as a cloth or broom. Do not use a high-pressure cleaner. Store the folded mat dry, after removing chemicals and drying it. Mats may be stacked, as long as no more than 200 kg/m² rests on the bottom mat. Take care that the valves are not damaged under pressure.
Inspection and maintenance	In doubt whether the mat is still tight, for example after the warranty period or after heavy use? Test the mat: fill it with water to 90% of the wall height and check for leaks. If you find a leak, have the mat repaired or take it out of service. Mark a damaged mat so nobody uses it.

Technical data of the fabric

Polyester (PES) fabric 1670 dtex (500 g/m²) coated with EVA.

PROPERTY	VALUE	ACCORDING TO
Weight	1,000 / 1,365 g/m²	ASTM D 751
Tensile strength (warp / weft)	7,300 / 7,000 N per 5 cm	ASTM D 751, method B
Cold resistance (cold crack)	−40 °C	
Heat resistance	+70 °C	DIN 53361

Warranty	2 years from the date of delivery (as stated on the invoice), under the manufacturer's warranty conditions for tightness.
Repair in case of damage	Mechanical damage to the mat can always be repaired: • dry, gluing: a patch of technical fabric with a special adhesive (provided adhesive residue does not react with the substances used); • dry, welding: for larger damage, a patch applied by hot-air welding (do not use substitutes).
Disposal	If the mat is worn or so damaged that repair is not worthwhile, clean it (according to the safety data sheet of the substance used) and take it to an industrial waste collection point as plastic waste (waste code 17 02 03). This is the responsibility of the buyer.

Standard sizes

LENGTH	WIDTH	WALL HEIGHT	CAPACITY*
9.62 m	3.66 m	0.20 m	6,690 l
12.66 m	5.20 m	0.20 m	12,508 l

* Capacity when empty, at 95% of the wall height. The final dimensions and equipment are stated on the quotation or invoice. Other sizes or versions are available on request.

> Data from the manufacturer. Do you have a question about the decontamination mat? Feel free to contact us.