HTML CONTENT MODELS

Content Model İçin Örnek HTML Dosyası

```html
1  <!doctype html>
2  <html>
3  <head>
4    <meta charset="utf-8">
5    <title>div and span elements</title>
6  </head>
7  <body>
8    <div>*** DIV 1: Some content here ***</div>
9    <div>*** DIV 2: Following right after div 1 ***</div>
10   <span>*** SPAN 1: Following right after div 2 ***</span>
11   <div>
12     *** DIV 3: Following right after span 1
13     <span>*** SPAN 2: INSIDE div 3 ***</span>
14     Continue content of div 3 ***
15   </div>
16 </body>
17 </html>
```

Block Level & Inline Element Örnekleri

+ <div> ➡ block level element
  + Her blok level element kendi satırında yer alır
  + Tüm block level element'ler gibi kendinden önce gelen html tag'inin üst satırda, kendinden sonra gelen html tag'inin de alt satırda olmasını garanti eder
+ <span> ➡ inline element
  + Her inline element kendinden önce gelen block level element'in belirlediği satırda yer alır.

Örnek HTML Dosyasının Görüntülenmesi

*** DIV 1: Some content here ***
*** DIV 2: Following right after div 1 ***
*** SPAN 1: Following right after div 2 ***
*** DIV 3: Following right after span 1 *** SPAN 2: INSIDE div 3 *** Continue content of div 3 ***

Hatalı Content Sonucu

Checker Input

Show ☑ source ☐ outline ☐ image report Options…

Check by [text input ▾]

```
<!doctype html>
<html>
<head>
  <meta charset="utf-8">
  <title>div and span elements</title>
</head>
<body>
  <div>*** DIV 1: Some content here ***</div>
  <div>*** DIV 2: Following right after div 1 ***</div>
  <span>*** SPAN 1: Following right after div 2 ***</span>
  <div>
    *** DIV 3: Following right after span 1
    <span>*** SPAN 2: INSIDE div 3 *** <div>some div content</div></span>
    Continue content of div 3 ***
  </div>
```

[Check]

Use the Message Filtering button below to hide/show particular messages, and to see total counts of errors and warnings.

[Message Filtering]

1. **Error** Element `div` not allowed as child of element `span` in this context. (Suppressing further errors from this subtree.)

    From line 13, column 40; to line 13, column 44

    `div 3 *** <div>some d`

    Contexts in which element `div` may be used:

        Where flow content is expected.

        As a child of a `dl` element.

    Content model for element `span`:

        Phrasing content.

HTML5 Content Kategorileri

+ HTML5 tarafından belirlenen 7 content kategorisi
  + https://www.w3.org/TR/html5/dom.html#kinds-of-content