

# **Cascading Style Sheets**

## **CSS**

Asst. Prof. Dr. Özgü Can

# CSS

- Language for formatting and designing information on the web, including ASP.NET pages.
- Change the appearance of pages.
- CSS code → to style pages

# CSS

- In the early days of the Internet → Web pages consisted mostly of text and images.
- Web developers needed more power to format their pages.
- CSS was created to address HTML's styling shortcomings.

# Problem's of HTML Formatting

- Limited set of options to style pages.
  - Not rich enough to create attractive web pages.
- HTML forces you to embed your formatting in your HTML document, making it harder to reuse or change the design later.

```
<p><font face="Arial" color="red" size="+1">
```

```
    This is red text in an Arial type face and slightly larger than the default text.
```

```
</font></p>
```

# Problem's of HTML Formatting

```
<p><font face="Arial" color="red" size="+1">
```

This is red text in an Arial type face and slightly larger than the default text.

```
</font></p>
```

- You can't easily change the formatting at runtime in the user's browser.
  - No way to let your visitor change things like the font size or color.
- Additional Markup → increase in the size of the page → slower download & display and harder to maintain pages

# Problem's of HTML Formatting

- Limits the formatting possibilities.
- Data and presentation are mixed within the same file.
  - Harder to maintain your pages
- HTML doesn't allow you to easily switch formatting at runtime in the browser.
- Your page gets larger → Slower to load and display

# CSS

- Define all formatting information in external files.
  - Separation of mixed data and presentation
- With this separation;
  - HTML → **what** you want to display
  - CSS → **how** you want to display

# CSS

- It's easy to offer the user a choice between different styles.
  1. Create a copy of external style sheet
  2. Make the necessary changes
  3. Offer this alternative style sheet to the user




# CSS

- Separate style sheet file → Decrease in bandwidth
- Style sheets don't change with each request
  - Browser saves a local copy of the style sheet the first time it downloads it.
  - Browser uses a *Cached copy*
    - CTRL+F5 → Get a fresh copy!


# CSS

- Maintained by World Wide Web Consortium (W3C)
- For more information :  
<http://www.w3.org/Style/CSS/>


# CSS Example



# CSS Example



# CSS Example



# CSS Example

```
|<head runat="server">  
    <title></title>  
</head>
```



```
<head runat="server">  
    <title></title>  
    <style type="text/css">  
    </style>  
</head>
```



**<style> tag is used  
to wrap a style sheet that is  
embedded in the page**

# CSS Example

Heading at  
the first level

```
<head runat="server">
  <title></title>
  <style type="text/css">
    h1
    {
      font-size: 20px;
      color: Green;
    }
```

The look and  
feel for all  
<p>  
elements


```
    p
    {
      color: Blue;
      font-style: italic;
    }
```

Right-align  
some text in  
the page.

```
    .RightAligned
    {
      text-align: right;
    }
  </style>
</head>
```

# CSS Example

```
<body>  
  <form id="form1" runat="server">  
    <div>  
  
    </div>  
  </form>  
</body>  
</html>
```



```
<body>  
  <form id="form1" runat="server">  
    <div>  
      <h1>Welcome to this CSS Demo page</h1>  
      <p>CSS makes it easy to style your pages.</p>  
      <p class="RightAligned">With very little code, you can quickly change the looks of a page.</p>  
    </div>  
  </form>  
</body>  
</html>
```



# CSS Example

CssDemo.aspx ✕

body

Welcome to this CSS Demo page

*CSS makes it easy to style your pages.*

*With very little code, you can quickly change the looks of a page.*

- CSS → Case sensitive
  - RightAligned ≠ rightaligned
- Ctrl+F5


Welcome to this CSS Demo page

*CSS makes it easy to style your pages.*

*With very little code, you can quickly change the looks of a page.*

# CSS

What element the  
formatting should be  
applied.



# CSS

- A cascading style sheet is actually a collection of rules.
- A rule is a combination of a selector and one or more declarations, which in turn can be broken down to a property and a value.
- In its simplest form, a style sheet looks like this:

```
h1
{
  color: Green;
}
```

# CSS

- A style sheet can also contain more than one rule. At the same time, each rule can contain multiple declarations, enabling you to group them under a single selector:

```
h1
{
    font-size: 20px;
    color: Green;
}
```

# CSS

- A style sheet can also contain more than one rule. At the same time, each rule can contain multiple declarations, enabling you to group them under a single selector:

```
h1
{
  font-size: 20px;
  color: Green;
}
```



```
h1
{
  font-size: 20px;
}
h1
{
  color: Green;
}
```

# CSS

- To be able to style an element on a page, a browser has to know three things:
  1. What element of the page must be styled?  
**Selectors**
  2. What part of that element must be styled?  
**Properties**
  3. How do you want that part of the selected element to look?  
**Values**

# Selectors

- ***What element of the page must be styled?***
  - The Universal Selector
  - The Type Selector
  - The ID Selector
  - The Class Selector

# The Universal Selector

- Indicated by an asterisk (\*)
- Applies to all elements in your page
- Can be used to set global settings
  - Font family
- Changing the font for all elements in the page to **Arial**:

```
*  
{  
  font-family: Arial;  
}
```



# The Type Selector

- Points to an HTML element of a specific type

```
h1
{
    color: Green;
}
```

- Not case sensitive!
  - H1 = h1

# The ID Selector

- Always prefixed by a hash symbol (#)
- Enables to refer to a single element in the page.
- Within an HTML or ASPX page, you can give an element a unique **ID** using the **id** attribute.
- ID Selectors are **case sensitive**!

# The ID Selector

- With the **ID** selector, you can change the behavior for a unique single element

```
#IntroText
{
    font-style: italic;
}
```

- Reuse the **ID** across multiple pages in the site

```
<p id="IntroText">I am italic because I have the right ID.</p>
<p id="BodyText">I am NOT italic because I have a different ID.</p>
```

# The Class Selector

- Enables to style multiple HTML elements through the `class` attribute.
- Handy when you want to give the same type of formatting to a number of unrelated HTML elements.

```
.Highlight  
{  
    font-weight: bold;  
    color: Red;  
}
```

# The Class Selector

- Uses a **period (.)** in its name!

```
.Highlight
{
    font-weight: bold;
    color: Red;
}
```

- Do **not** use period (.) is when referring to it!

This is normal text but <span class="Highlight">this is Red and Bold.</span>

This is also normal text but

<a href="CssDemo.aspx" class="Highlight">this link is Red and Bold as well.</a>

# Grouping Selectors


- Enables you to *group* multiple selectors by separating them with a comma.

```
h1, h2, h3, h4, h5, h6  
{  
    color: Red;  
}
```

- Handy if you want to apply the same styles to different elements.

# Combining Selectors

- Enables to target to a specific element in a page.
- Separate the selectors with a space



```
#MainContent p
{
  font-size: 18px;
}
```

**All <p> elements that fall within an element with an id of MainContent, leaving all other paragraphs unmodified.**

# Combining Selectors

- Also use it with the other selectors.

```
#MainContent p.Attention
{
    font-weight: bold;
}
```

This rule changes all paragraphs with the class **Attention** within the element with its id set to **MainContent** and leaves all others untouched.

```
<div id="MainContent">
  <p class="Attention">My class is Attention, so my text is bold.</p>
  <p>My text is not bold, as it lacks the Attention class.</p>
</div>
<p class="Attention">I am NOT bold because I don't fall within MainContent.</p>
```



# Grouping vs. Combining

- ***Grouping*** is just a shortcut to avoid typing the same declarations over and over again.
- ***Combining*** enables you to target specific elements in your document.

# Properties

*What part of that element must be styled?*

- The element that you want to change with your style sheet.
- You don't have to remember them all.

# Properties - 1

PROPERTY	DESCRIPTION	EXAMPLE
background-color background-image	Specifies the background color or image of an element.	background-color: White; background-image: url(Image.jpg);
border	Specifies the border of an element.	border: 3px solid black;
color	Changes the font color.	color: Green;
display	Changes the way elements are displayed, enabling you to hide or show them.	display: none; This causes the element to be hidden, and not take up any screen space.
float	Enables you to “float” an element in the page using a left or right float. Other content is then placed on the opposite side.	float: left; This setting causes other content following a float to be placed at the top-right corner of the element. You see how this works later in the chapter.
font-family font-size font-style font-weight	Changes the appearance of fonts used on your page.	font-family: Arial; font-size: 18px; font-style: italic; font-weight: bold;

# Properties - 2

PROPERTY	DESCRIPTION	EXAMPLE
height width	Sets the height or width of elements in your page.	<code>height: 100px;</code> <code>width: 200px;</code>
margin padding	Sets the amount of free space inside (padding) and outside (margin) of an element.	<code>padding: 0;</code> <code>margin: 20px;</code>
visibility	Controls whether an element is visible in the page. Invisible elements still take up screen space; you just don't see them.	<code>visibility: hidden;</code> This causes the element to be invisible. However, it still takes up its original space in the page. It's as if the element is still there, but completely transparent.

# Values

*How do you want that part of the selected element to look?*

- The available values depend on the property.

```
h1
{
  color: Red;
}
```

**Named color**

```
h1
{
  color: #FF0000;
}
```

**Hexadecimal Number**

```
h1
{
  color: rgb(100%, 0%, 0%);
}
```

**RGB Value**

# Shorthand

- Border property applies a border to all four sides of an HTML element.
- The border size will be 1px, the style will be solid and the border color will be set to Black.


```
border: 1px solid Black;
```



```
border-top-width: 1px;  
border-top-style: solid;  
border-top-color: Black;  
border-right-width: 1px;  
border-right-style: solid;  
border-right-color: Black;  
border-bottom-width: 1px;  
border-bottom-style: solid;  
border-bottom-color: Black;  
border-left-width: 1px;  
border-left-style: solid;  
border-left-color: Black;
```


# The CSS Box Model

- The CSS Box Model describes the way three important CSS properties are applied to HTML elements:
  - Padding
  - Border
  - Margin



# The CSS Box Model

```
.MyDiv
{
  width: 200px;
  padding: 10px;
  border: 2px solid black;
}
...
<div class="MyDiv">Element</div>
```



**When things end up wider or taller than you anticipated, check the width, height, padding, border, and margin properties in the CSS style sheet.**



# Example

- Open Default.aspx


```
<form id="form1" runat="server">
<div>
  <h1>
    Hi there visitor! Welcome to my Web Site :-)</h1>
  <p>
    I'm glad that you are visiting my web site <a href="http://www.mywebsite.com">
    http://www.mywebsite.com</a>
  </p>
  <p>
    <strong>Feel</strong> <span class="style1"><strong>free</strong></span> to have a look around.</p>
</div>
</form>
```

# Example



```
<form id="form1" runat="server">
  <div id="PageWrapper">
    <div id="Header">Header goes here.</div>
    <div id="MenuWrapper">Menu goes here.</div>
    <div id="MainContent">
      <h1>
        Hi there visitor! Welcome to my Web Site :-)</h1>
      <p>
        I'm glad that you are visiting my web site <a href="http://www.mywebsite.com">
          http://www.mywebsite.com</a>
      </p>
      <p>
        <strong>Feel</strong> <span class="style1"><strong>free</strong></span> to have a look around.</p>
    </div>
    <div id="Sidebar">Sidebar goes here.</div>
    <div id="Footer">Footer goes here.</div>
  </div>
</form>
```

# Example

- Open **Styles > Styles.css**



# Example



# Example

Modify Style

Category:

Font

Block

Background

Border

Box

Position

Layout

List

Table

font-family:

font-size:

px

font-weight:

font-style:

font-variant:

text-transform:

color:

text-decoration:

☐ underline

☐ overline

☐ line-through

☐ blink

☐ none

Preview:


AaBbYyGgLlJj

Description:

OK

Cancel

# Example



# Example

Modify Style

Category:

- Font
- Block
- Background**
- Border
- Box
- Position
- Layout
- List
- Table

background-color: #C0C0C0

background-image:  Browse...

background-repeat:

background-attachment:

(x) background-position:  px

(y) background-position:  px

Preview:

AaBbYyGgLIJj

Description:

background-color: #C0C0C0

OK Cancel

# Example

Modify Style

?

X

Category:

Font

Block

**Background**

Border

Box

**Position**

Layout

List

Table

position:

width: 

844

px

z-index:

height: 

86

px

top: 

px

right: 

px

bottom: 

px

left: 

px

Preview:

AaBbYyGgLIj

Description:

background-color: #C0C0C0; width: 844px

OK

Cancel



# Example

```
#Header
{
    background-color: #C0C0C0;
    width: 844px;
    height: 86px;
}
```

```
*
{
    font-family: Arial;
}

h1
{
    font-size: 20px;
}

#PageWrapper
{
    width: 844px;
}


#MenuWrapper
{
    width: 844px;
}

#MainContent
{
    width: 664px;
    float: left;
}

#Sidebar
{
    background-color: #808080;
    width: 180px;
    float: left;
}

#Footer
{
    background-color: #C0C0C0;
    width: 844px;
    clear: both;
}
```

# Example




```
<html xmlns="http://www.w3.org/1999/xhtml">  
<head runat="server">  
    <title></title>  
</head>
```

# Example

- From the Solution Explorer, drag the file **Styles.css** from the **Styles** folder onto the page.

# Example



```
<html xmlns="http://www.w3.org/1999/xhtml">
<head runat="server">
  <title></title>
  <style type="text/css">
    .style1
    {
      color: #FF00FF;
    }
  </style>
  <link href="Styles/Styles.css" rel="stylesheet" type="text/css" />
</head>
```

**Tells the browser to look in the Styles folder for a file called Styles.css and apply all rules in that file to the current document.**

# Adding CSS to Page

- External

```
<link href="StyleSheet.css" rel="Stylesheet" type="text/css" media="screen" />
```

- Embedded

```
<head runat="server">  
  <title></title>  
  <style type="text/css">  
    h1  
    {  
      color: Blue;  
    }  
  </style>  
</head>
```

The **<style>** element should be placed at the top of your ASPX or HTML page, between the **<head>** tags.

- Inline

```
<span style="color: White; background-color: Black;">  
  This is white text on a black background.  
</span>
```

You don't need a selector.

# Overriding

**External over Embedded over Inline**

# Overriding

- **External** style sheets enable you to **change** the appearance of the **entire site** through a single file.
- **Make one change** to your external style sheet file, and **all pages** that use this style sheet pick up the **change automatically**.

# Overriding

- If you want **to change the look of a single page**, without affecting other pages in your site, an **embedded** style sheet is your best choice.
- If you only want **to change the behavior of a single element in a single page**, and you're pretty sure you're not going to need the same declaration for other HTML elements, use an **inline** style.




# Overriding

If you have multiple identical selectors with different property values,  
**the one defined last takes precedence.**

# Overriding

```
h1
{
  color: Green;
}
```



**Styles.css**

```
<link href="Styles/Styles.css" rel="stylesheet" type="text/css" />
<style type="text/css">
  h1
  {
    color: Blue;
  }
</style>
```



*Embedded overrides External*

**Embedded**

```
<style type="text/css">
  h1
  {
    color: Blue;
  }
</style>
<link href="Styles/Styles.css" rel="stylesheet" type="text/css" />
```



*External overrides Embedded*

# Overriding

**Inline** style sheets **take precedence over** embedded and external style sheets.



**They're defined directly on the HTML elements.**



# CSS overrules attributes on HTML elements

```
img
{
  height: 100px;
  width: 100px;
}
...


```

100px 100px


# Example

- Open **Styles.css**
- At the end of the file:

```
#Footer  
{  
    background-color: #C0C0C0;  
    width: 844px;  
    clear: both;  
}
```



OR



# Example

Add Style Rule

?

X

Define a new style rule by adding at least one element, class, or ID'd element. Additional elements, classes, and ID'd elements can be combined to create a hierarchy.

☒ Element:

▼

☐ Class name:

>

☐ Optional element:

▼

☐ Element ID:

Style rule hierarchy:

Up

Down

Delete

Style rule preview:

OK

Cancel

# Example

- Select **E**lement ID

Add Style Rule

Define a new style rule by adding at least one element, class, or ID'd element. Additional elements, classes, and ID'd elements can be combined to create a hierarchy.

☐ Element:

☐ Class name:


☐ Optional element:

☒ Element ID:

Style rule hierarchy:

Style rule preview:

OK Cancel



# Example

?

X

Add Style Rule

Define a new style rule by adding at least one element, class, or ID'd element. Additional elements, classes, and ID'd elements can be combined to create a hierarchy.

☐ Element:

▼

☐ Class name:

>

☐ Optional element:

▼

☒ Element ID:

Style rule hierarchy:

#MainContent

Up

Down

Delete

Style rule preview:


#MainContent

OK

Cancel



# Example



# Example

Add Style Rule

?

X

Define a new style rule by adding at least one element, class, or ID'd element. Additional elements, classes, and ID'd elements can be combined to create a hierarchy.

☒ Element:

☐ Class name:

>

☐ Optional element:

☐ Element ID:

Style rule hierarchy:

#MainContent  
a


Up

Down

Delete

Style rule preview:

#MainContent a



OK

Cancel

# Example

Styles/Styles.css\* x Default.aspx

```
}
```

```
#Sidebar
```

```
{
```

```
    background-color: Gray;
```

```
    width: 180px;
```

```
    float: left;
```

```
}
```

```
#Footer
```

```
{
```

```
    background-color: #C0C0C0;
```

```
    width: 844px;
```

```
    clear: both;
```

```
}
```

```
#MainContent a
```


```
{
```

```
}
```

```
#MainContent a
```

```
{
```

```
}
```



# Example

Modify Style

?

X

Category:

Font

Block

Background

Border

Box

Position

Layout

List

Table

font-family:

font-size:

px

font-weight:

font-style:

font-variant:

text-transform:

color:

#008000

text-decoration:

☒ underline

☐ overline

☐ line-through

☐ blink

☐ none

Preview:

AaBbYyGgLlJj


Description:

color: #008000; text-decoration: underline

OK

Cancel

```
#MainContent a
{
    color: #008000;
    text-decoration: underline;
}
```

- Copy this rule set and paste it twice.
- Rename: `#MainContent a`  `#MainContent a:visited`

```
#MainContent a
{
    color: #008000;
    text-decoration: underline;
}
```


```
#MainContent a:visited
{
```



Build Style...

Add Style Rule...

Synchronize Document Outline




```
#MainContent a:visited
{
    color: #FF0000;
    text-decoration: underline;
}
```

# Example

- Rename the third selector:

#MainContent a      ➡      #MainContent a:hover



# Example

Modify Style

Category:

Font

Block

Background

Border

Box

Position

Layout

List

Table

font-family:

font-size:

px

font-weight:

font-style:

font-variant:

text-transform:

color:

#FFA500

text-decoration:

☒ underline

☐ overline

☐ line-through

☐ blink

☐ none

Preview:

AaBbYyGgLlJj

Description:

color: #008000; text-decoration: underline

OK

Cancel



# Example

```
#MainContent a
{
    color: #008000;
    text-decoration: underline;
}

#MainContent a:visited
{
    color: #FF0000;
    text-decoration: underline;
}

#MainContent a:hover
{
    color: #FFA500;
    text-decoration: underline;
}
```



# Example – Apply Style Sheet



- Open **Default.aspx** in Source View
- Remove **<link />** element

```
<head runat="server">
    <title></title>
    <style type="text/css">
        .style1
        {
            color: #FF00FF;
        }
    </style>
    <link href="Styles/Styles.css" rel="stylesheet" type="text/css" />
</head>
```


# Example – Apply Style Sheet

In Design View:






# Example – Apply Style Sheet






# Example – Apply Style Sheet


- Select “look around”




- Convert to hyperlink







**View in browser**





# Example – Apply Style Sheet

- Hover your mouse

Header goes here.

Menu goes here.

**Hi there visitor! Welcome to my Web Site :-)**

I'm glad that you are visiting my web site <http://www.mywebsite.com>



**Feel free** to have a [look around](#).

Footer goes here.

Sidebar goes here.

# NOTE


- Browse with different browsers




# Example

## Embedded & Inline Styles

- Open Default.aspx in Design View
- Click **h1** element





**New Style**

Selector:  ☐ Apply new style to document selection

Define in:  URL:

Category:

- Font
- Block
- Background
- Border
- Box
- Position
- Layout
- List
- Table

font-family:

font-size:

font-weight:

font-style:

font-variant:

text-transform:


color:

text-decoration:

- ☐ underline
- ☐ overline
- ☐ line-through
- ☐ blink
- ☐ none

Preview:

Description:



Choose inline style

## New Style



Selector: (inline style) ▼

☐ Apply new style to document selection

Define in: Current tag: <h1> ▼

URL: ▼

Browse...

### Category:

Font  
Block  
Background  
Border  
**Box**  
Position  
Layout  
List  
Table

padding: ☒ Same for all

top: ▼ ▲ px ▼

right: ▼ ▲ px ▼

bottom: ▼ ▲ px ▼

left: ▼ ▲ px ▼

margin: ☒ Same for all


top: ▼ ▲ px ▼

right: ▼ ▲ px ▼

bottom: ▼ ▲ px ▼

left: ▼ ▲ px ▼

CSS box model reference:



Preview:

AaBbYyGgLlJj

Description:

OK

Cancel

Apply

New Style

Selector: (inline style)

☐ Apply new style to document selection

Define in: Current tag: <h1>

URL:

Browse...

Category:

Font

Block

Background

Border

Box

Position

Layout

List

Table

padding: ☒ Same for all

margin: ☐ Same for all

top: 0px

right: 0px

bottom: 0px

left: 0px

top: 0px

right: 0px

bottom: 10px

left: 0px

CSS box model reference:

Top

Margin

Border

Padding

Left

Right

Bottom

Preview:

AaBbYyGgLIJj

Description:

padding: 0px; margin: 0px

OK



Cancel

Apply

```
<h1 style="padding: 0px; margin: 0px 0px 10px 0px">
  Hi there visitor! Welcome to my Web Site :-)</h1>
```









# Example

## Embedded & Inline Styles



# With the `<p>` tag still selected




# Example

## Embedded & Inline Styles

Show Alphabetized List

Show Set Properties on Top

Show Categorized List



# Example

## Embedded & Inline Styles

```
<head runat="server">
  <title></title>
  <style type="text/css">
    .style1
    {
      color: #FF00FF;
    }
    .Introduction
    {
      font-style: italic;
      color: #003399;
    }
  </style>
  <link href="Styles/Styles.css" rel="stylesheet" type="text/css" />
</head>
```

# Example

## Embedded & Inline Styles

- View in browser

Header goes here.

Menu goes here.

**Hi there visitor! Welcome to my Web Site :-)**

Sidebar goes here.


*I'm glad that you are visiting my web site <http://www.mywebsite.com>*

**Feel free** to have a [look around](#).



Footer goes here.

# Example – Applying Styles

- Open **Default.aspx** in Design View
- Select second paragraph




# Example – Applying Styles






# Example – Applying Styles

Click **Introduction** class



# Example – Applying Styles



**Clear Styles**  
removes existing  
classes and inline  
styles from a tag.



# Example – Managing Styles


- Open **Default.aspx** in Source View.
- Locate the **<h1>** element and click it once.

```
<h1 style="padding: 0px; margin: 0px 0px 10px 0px">  
    Hi there visitor! Welcome to my Web Site :-)</h1>
```



# Example – Managing Styles

- Right-click **Inline Style**



## New Style

Selector:

☐ Apply new style to document selection

Define in:

URL:

[Browse...](#)

### Category:

Font

Block

Background

Border

**Box**

Position

Layout

List

Table

font-family:

font-size:  px

font-weight:

font-style:

font-variant:

text-transform:

color:

text-decoration:

☐ underline

☐ overline

☐ line-through

☐ blink

☐ none

Preview:

AaBbYyGgLlJj

Description:


padding: 0px; margin: 0px 0px 10px 0px

OK


Cancel

Apply

Choose **h1** from the **Selector**



Choose **Existing Style Sheet** from **Define in**



# URL → Styles/Styles.css

New Style

Selector:  ☐ Apply new style to document selection

Define in:  URL:

Category:

- Font
- Block
- Background
- Border
- Box**
- Position
- Layout
- List
- Table

font-family:

font-size:

font-weight:

font-style:

font-variant:

text-transform:

color:

text-decoration:

- ☐ underline
- ☐ overline
- ☐ line-through
- ☐ blink
- ☐ none

Preview:

AaBbYyGgLlJj

Description:

padding: 0px; margin: 0px 0px 10px 0px




# Example – Managing Styles

- Check out `Styles.css`
  - A copy of `h1` style is created

```
h1
{
    padding: 0px;
    margin: 0px 0px 10px 0px;
}
```



# Example – Managing Styles

- In the **Apply Styles** window, right-click **Inline Style** again




**Removes the style attribute from the h1 element.**

# Example – Managing Styles



- Click the **.Introduction** selector and drag it into the area for **Styles.css**, for example after the **h1** selector.



# Example – Managing Styles

- View in browser

Header goes here.

Menu goes here.

**Hi there visitor! Welcome to my Web Site :-)**

Sidebar goes here.

*I'm glad that you are visiting my web site <http://www.mywebsite.com>*

**Feel free** to have a [look around](#).

Footer goes here.

# NOTE

- Try to create smaller and reusable rule sets that you can combine if required, rather than creating large, monolithic rules that can only be used on a single UI element.

```
.ImportantHeading
{
  font-size: 20px;
  font-weight: bold;
  color: red;
}
```



```
h1
{
  font-size: 20px;
}

.Attention
{
  font-weight: bold;
  color: red;
}
```

**<h1 class="Attention">**