SPEC® CPU2017 Floating Point Rate Result

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_fp_base = 5.75

SPECrate2017_fp_peak = Not Run

Copies		
503.bwaves_r		
507.cactuBSSN_r		
508.namd_r		
510.parest_r		
511.povray_r		
519.lbm_r		
521.wrf_r		
526.blender_r		
527.cam4_r		
538.imagick_r	1	5.75
544.nab_r		
549.fotonik3d_r		
554.roms_r		

SPECrate2017_fp_base (5.75)

Hardware

CPU Name: Intel Core i3-6100
Max MHz.:
Nominal:
Enabled: cores, 1 chip, threads/core
Orderable:
Cache L1:
L2:
L3:
Other:
Memory: 7.497 GB fixme: If using DDR3, format is: 'N GB (M x N GB nRxn PCn-nnnnnR-n, ECC)'
Storage: 230 GB add more disk info here
Other:

Software

OS: Ubuntu 16.04.3 LTS
4.4.0-97-generic
Compiler: C/C++: Version 3.9.0 of Clang, the LLVM Compiler Infrastructure
Fortran: Version 4.8.2 of GCC, the GNU Compiler Collection
DragonEgg: Version 3.5.2, the LLVM Compiler Infrastructure
Parallel: No
Firmware:
File System: ext4
System State: Run level 3 (add definition here)
Base Pointers: 64-bit
Peak Pointers: Not Applicable
Other:

Errors

'reportable' flag not set during run

507.cactuBSSN_r (base) did not have enough runs!

526.blender_r (base) did not have enough runs!

527.cam4_r (base) did not have enough runs!

554.roms_r (base) did not have enough runs!

(Continued on next page)

SPEC CPU2017 Floating Point Rate Result

My Corporation	
SPECrate2017_fp_base = 5.75	
SPECrate2017_fp_peak = Not Run	

CPU2017 License: nnn (Your SPEC license number)	**Test Date:** Nov-2017
Test Sponsor: My Corporation	**Hardware Availability:**
Tested by: My Corporation	**Software Availability:**

Errors (Continued)

503.bwaves_r (base) did not have enough runs!

544.nab_r (base) did not have enough runs!

510.parest_r (base) did not have enough runs!

508.namd_r (base) did not have enough runs!

549.fotonik3d_r (base) did not have enough runs!

519.lbm_r (base) did not have enough runs!

511.povray_r (base) did not have enough runs!

521.wrf_r (base) did not have enough runs!

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r														
507.cactuBSSN_r														
508.namd_r														
510.parest_r														
511.povray_r														
519.lbm_r														
521.wrf_r														
526.blender_r														
527.cam4_r														
538.imagick_r	1	**433**	**5.75**	433	5.75	433	5.75							
544.nab_r														
549.fotonik3d_r														
554.roms_r														

SPECrate2017_fp_base = 5.75

SPECrate2017_fp_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

General Notes

Environment variables set by runcpu before the start of the run:

LD_LIBRARY_PATH = "/mnt/freezedisk/llvm-intptr-br5.5-gvnnocast-release/lib"

LIBRARY_PATH = "/mnt/freezedisk/llvm-intptr-br5.5-gvnnocast-release/lib"

PATH = "/mnt/freezedisk/llvm-intptr-br5.5-gvnnocast-release/bin:/mnt/freezedisk/speccpu2017-intptr/bin:/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/local/games:/snap/bin:/snap/bin"

SPEC CPU2017 Floating Point Rate Result

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_fp_base =   5.75

SPECrate2017_fp_peak = Not Run

Platform Notes

```
Sysinfo program /mnt/freezedisk/speccpu2017-intptr/bin/sysinfo
Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f
running on freeze4 Tue Nov 14 07:58:51 2017

SUT (System Under Test) info as seen by some common utilities.
For more information on this section, see
   https://www.spec.org/cpu2017/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Core(TM) i3-6100 CPU @ 3.70GHz
      1  "physical id"s (chips)
      2 "processors"
   cores, siblings (Caution: counting these is hw and system dependent. The following
   excerpts from /proc/cpuinfo might not be reliable.  Use with caution.)
      cpu cores : 2
      siblings  : 2
      physical 0: cores 0 1

From lscpu:
   Architecture:          x86_64
   CPU op-mode(s):        32-bit, 64-bit
   Byte Order:            Little Endian
   CPU(s):                2
   On-line CPU(s) list:   0,1
   Thread(s) per core:    1
   Core(s) per socket:    2
   Socket(s):             1
   NUMA node(s):          1
   Vendor ID:             GenuineIntel
   CPU family:            6
   Model:                 94
   Model name:            Intel(R) Core(TM) i3-6100 CPU @ 3.70GHz
   Stepping:              3
   CPU MHz:               3700.000
   CPU max MHz:           3700.0000
   CPU min MHz:           800.0000
   BogoMIPS:              7392.16
   Virtualization:        VT-x
   L1d cache:             32K
   L1i cache:             32K
   L2 cache:              256K
   L3 cache:              3072K
   NUMA node0 CPU(s):     0,1
   Flags:                 fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov
   pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp
   lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc
   aperfmperf eagerfpu pni pclmulqdq dtes64 monitor ds_cpl vmx est tm2 ssse3 sdbg fma
```

(Continued on next page)

My Corporation

SPECrate2017_fp_base =	5.75
SPECrate2017_fp_peak =	Not Run

CPU2017 License: nnn (Your SPEC license number)　　**Test Date:** Nov-2017
Test Sponsor: My Corporation　　**Hardware Availability:**
Tested by: My Corporation　　**Software Availability:**

Platform Notes (Continued)

```
     cx16 xtpr pdcm pcid sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave
     avx f16c rdrand lahf_lm abm 3dnowprefetch epb intel_pt tpr_shadow vnmi flexpriority
     ept vpid fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms invpcid mpx rdseed adx smap
     clflushopt xsaveopt xsavec xgetbv1 dtherm arat pln pts hwp hwp_notify hwp_act_window
     hwp_epp


 /proc/cpuinfo cache data
    cache size : 3072 KB

 From numactl --hardware  WARNING: a numactl 'node' might or might not correspond to a
 physical chip.
   available: 1 nodes (0)
   node 0 cpus: 0 1
   node 0 size: 7676 MB
   node 0 free: 7253 MB
   node distances:
   node   0
     0:  10


 From /proc/meminfo
    MemTotal:        7860684 kB
    HugePages_Total:       0
    Hugepagesize:       2048 kB


 /usr/bin/lsb_release -d
    Ubuntu 16.04.3 LTS

 From /etc/*release* /etc/*version*
    debian_version: stretch/sid
    os-release:
      NAME="Ubuntu"
      VERSION="16.04.3 LTS (Xenial Xerus)"
      ID=ubuntu
      ID_LIKE=debian
      PRETTY_NAME="Ubuntu 16.04.3 LTS"
      VERSION_ID="16.04"
      HOME_URL="http://www.ubuntu.com/"
      SUPPORT_URL="http://help.ubuntu.com/"

 uname -a:
    Linux freeze4 4.4.0-97-generic #120-Ubuntu SMP Tue Sep 19 17:28:18 UTC 2017 x86_64
    x86_64 x86_64 GNU/Linux


 run-level 3 Oct 30 07:30


 SPEC is set to: /mnt/freezedisk/speccpu2017-intptr
    Filesystem      Type  Size  Used Avail Use% Mounted on
```

(Continued on next page)

SPEC CPU2017 Floating Point Rate Result

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_fp_base =   5.75

SPECrate2017_fp_peak = Not Run

Platform Notes (Continued)

```
   /dev/sda1      ext4  230G   67G  151G  31% /mnt/freezedisk

 Additional information from dmidecode follows.  WARNING: Use caution when you interpret
 this section. The 'dmidecode' program reads system data which is "intended to allow
 hardware to be accurately determined", but the intent may not be met, as there are
 frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

 (End of data from sysinfo program)
```

Compiler Version Notes

```
==============================================================================
  CC  538.imagick_r(base)
------------------------------------------------------------------------------
clang version 6.0.0 (https://github.com/aqjune/clang-intptr.git
  4c61e7d94696e3346da34031080891f5b176cbe3)
  (https://github.com/aqjune/llvm-intptr.git
  dc57902874362bda6a92afc0a30531112b9a1258)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /mnt/freezedisk/llvm-intptr-br5.5-gvnnocast-release/bin
Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5
Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5.4.0
Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/6
Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/6.0.0
Selected GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5.4.0
Candidate multilib: .;@m64
Selected multilib: .;@m64
------------------------------------------------------------------------------
```

Base Runtime Environment

C benchmarks:

 538.imagick_r: No flags used

Base Compiler Invocation

C benchmarks:

 538.imagick_r: clang

SPEC CPU2017 Floating Point Rate Result

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_fp_base = 5.75

SPECrate2017_fp_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)
Test Sponsor: My Corporation
Tested by: My Corporation

Test Date: Nov-2017
Hardware Availability:
Software Availability:

Base Portability Flags

538.imagick_r: -DSPEC_LP64

Base Optimization Flags

C benchmarks:

538.imagick_r: -m64 -O3 -mavx -z muldefs

Base Other Flags

C benchmarks:

538.imagick_r: No flags used

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.2 on 2017-11-14 07:58:50+0900.
Report generated on 2017-11-14 08:21:00 by CPU2017 PDF formatter v5748.