

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_fp_base = 5.1

SPECrate2017_fp_peak Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation **Tested by:** My Corporation

Test Date: Nov-2017

Hardware Availability: Software Availability:

Errors (Continued)

526.blender_r (base) did not have enough runs! 544.nab_r (base) did not have enough runs! 527.cam4_r (base) did not have enough runs! 503.bwaves_r (base) did not have enough runs! 508.namd_r (base) did not have enough runs! 521.wrf_r (base) did not have enough runs! 549.fotonik3d_r (base) did not have enough runs!

510.parest_r (base) did not have enough runs!

Results Table

	Base							Peak						
Benchmark	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r)/								
507.cactuBSSN_r						\n'\								
508.namd_r														
510.parest_r					N									
511.povray_r		<i>^</i>	\bigcup											
519.lbm_r				$\setminus \mathcal{A}$										
521.wrf_r		1//												
526.blender_r	\wedge	//)										
527.cam4_r	6		7/											
538.imagick_r	1	487	<u>5.11</u>	486	5.11	487	5.11							
544.nab_r			1											
549.fotonik3d_p														
54.roms_1		7												

SPECrate2017_fp_base = 5.11

SPECrate2017 fp_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option 'submit' was used.

General Notes

Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/mnt/freezedisk/llvm-intptr-br2-correct2-release/lib"
LIBRARY_PATH = "/mnt/freezedisk/llvm-intptr-br2-correct2-release/lib"

TRTS = '/min'(reseablish/live-intprt-in-2-correct2-release/hin/min/refshih/.com/rflah/.c

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

Test Sponsor:

Tested by:

SPECrate2017_fp_base = **5**.11

SPECrate2017_fp_peak **Y**ot Run

CPU2017 License: nnn (Your SPEC license number)

My Corporation My Corporation Test Date: Nov-2017

Hardware Availability: Software Availability:

Platform Notes

```
Sysinfo program /mnt/freezedisk/speccpu2017-intptr/bin/sysinfo
Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f
running on ubuntu-freeze2 Fri Nov 3 19:27:18 2017
```

```
SUT (System Under Test) info as seen by some common utilities
For more information on this section, see
```

https://www.spec.org/cpu2017/Docs/config.html#sysinfo

```
From /proc/cpuinfo
  model name : Intel(R) Core(TM) i5-660
                                          CPU @ 3.
      1 "physical id"s (chips)
```

4 "processors"

cores, siblings (Caution: counting these is hw and system dependent. The following excerpts from /proc/contacto might not be reliable. Use with caution.)

cpu cores : 4 siblings : 4 physical 0: cores 0 1 2 3

From lscpu:

Architecture: CPU op-mode(s): 32-bit, 64-bit Byte Order: ittle Endian CPU(s): On-line CPU(s) l

Thread(s) per core Core(s) per socket 1 Socket(s): 1 NUMA node(s):

Vendor ID GenuineIntel

CPU family Model:

Intel(R) Core(TM) i5-6600 CPU @ 3.30GHz Model name:

3237.867

Stepping: 3

NUMA node0 CPU(s):

CPU MHx:

CPU max MHz: 3900.0000 CPU min MHz: 800.0000 BogoMIPS: 6623.96 Virtualization: x-TV32K cache: Lli cache: 32K L2 cache: 256K L3 cache: 6144K 0 - 3

fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov Flags: pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good nop1 xtopology nonstop_tsc aperfmperf eagerfpu pni pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg

(Continued on next page)

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_fp_base =

SPECrate2017_fp_peak **Y**ot Run

CPU2017 License: nnn (Your SPEC license number)

Test Date: Nov-2017

Test Sponsor: My Corporation **Tested by:** My Corporation

Hardware Availability: Software Availability:

Platform Notes (Continued)

fma cx16 xtpr pdcm pcid sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm 3dnowprefetch intel_pt tpr_shadow vnmi flexpriority ept vpid fsgsbase tsc_adjust bmil hle avx2 smed bmi2 erms invpcid rtm mpx rdseed adx smap clflushopt xsaveopt xsavec xgetbyl dtherm arat pln pts hwp hwp_notify hwp_act_window hwp_epp/

```
/proc/cpuinfo cache data
  cache size : 6144 KB
```

'node' might or might not correspond to a From numactl --hardware WARNING) a numactl physical chip.

available: 1 nodes (0) node 0 cpus: 0 1 2 3 node 0 size: 7860 MB node 0 free: 7478 MB node distances: node Ω 0: 10

From /proc/meminfo

MemTotal:

HugePages_Total; Hugepagesize:

/usr/bin/lsb_release Ubuntu 16 04.1 LTS

From /etc/*release* /etc/*version* debian version: stretch/sid os-release NAME="Ubuntu

VERSION="16 04.1 LTS (Xenial Xerus)" ID=ubuntu

2048 ki

ID_LIKE=debian

PRETTY_NAME="Ubuntu 16.04.1 LTS"

VERSION ID="16.04"

HOME_VRL="http://www.ubuntu.com/"

SNPPORT_URL="http://help.ubuntu.com/"

Linux ubuntu-freeze2 4.4.0-31-generic #50-Ubuntu SMP Wed Jul 13 00:07:12 UTC 2016 x86_64 x86_64 x86_64 GNU/Linux

run-level 5 Oct 30 07:30

SPEC is set to: /mnt/freezedisk/speccpu2017-intptr

Type Size Used Avail Use% Mounted on

(Continued on next page)

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_fp_base = 5.1

SPECrate2017_fp_peak \to Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation **Tested by:** My Corporation

Test Date: Nov-2017

Hardware Availability: Software Availability:

Platform Notes (Continued)

/dev/sdb1 ext4 2.7T 1.7T 907G 66% /mnt/fxeezedisk

Additional information from dmidecode follows. WARNING: Use caudion when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

(End of data from sysinfo program)

Compiler Version Notes

CC 538.imagick_r(base)

clang version 6.0.0 (https://github.com/aqjune/clang-intptr.git

b099f9b86954800bcbdee427fc703eb8a30389da)

(https://github.com/aqjune/llvm-intptr.git

072bcfdd83ea02b321f72fg639d5a8384325de92)

Target: x86_64-unknown-linux-

Thread model: posix

InstalledDir: /mnt/freezedisk/llvmintptr-br2-correct2-release/bin

Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5

Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5.4.0

Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/6 Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/6.0.0

Selected GCC installation /usr/lib/gcc/x86_64-linux-gnu/5.4.0

Candidate multilib: .;@m64 Selected multilib: .;@m64

belected Multilib. ./@mo4

Base Runtime Environment

C benchmarks:

538.imagick_r: No flags used

Base Compiler Invocation

C benchmarks:

538.imagick_r: clang

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_fp_base = 5.

SPECrate2017_fp_peak Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation **Tested by:** My Corporation

Test Date: Nov-2017

Hardware Availability: Software Availability:

Base Portability Flags

538.imagick_r: -DSPEC LP64

Base Optimization Flags

C benchmarks:

538.imagick_r: -m64 -O3 -mavx -z muldefs

Base Other Flags

C benchmarks:

538.imagick_r: No flags used

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.2 on 2017-11-03 19:27:17+0900.

Report generated on 2017-11-03 19:52:06 by CPU2017 PDF formatter v5748.