SPEC® CPU2017 Floating Point Rate Result

My Corporation

SPECrate2017_fp_base = 4.60

SPECrate2017_fp_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)
Test Sponsor: My Corporation
Tested by: My Corporation

Test Date: Nov-2017
Hardware Availability:
Software Availability:



Hardware

CPU Name: Intel Core i3-6100
Max MHz.:
Nominal:
Enabled: cores, 1 chip, threads/core
Orderable:
Cache L1:
L2:
L3:
Other:
Memory: 7.497 GB fixme: If using DDR3, format is: 'N GB (M x N GB nRxn PCn-nnnnnR-n, ECC)'
Storage: 230 GB add more disk info here
Other:

Software

OS: Ubuntu 16.04.3 LTS 4.4.0-97-generic
Compiler: C/C++: Version 3.9.0 of Clang, the LLVM Compiler Infrastructure
Fortran: Version 4.8.2 of GCC, the GNU Compiler Collection
DragonEgg: Version 3.5.2, the LLVM Compiler Infrastructure
Parallel: No
Firmware:
File System: ext4
System State: Run level 3 (add definition here)
Base Pointers: 64-bit
Peak Pointers: Not Applicable
Other:

Errors

'reportable' flag not set during run
544.nab_r (base) did not have enough runs!
507.cactuBSSN_r (base) did not have enough runs!
503.bwaves_r (base) did not have enough runs!
527.cam4_r (base) did not have enough runs!

(Continued on next page)

SPEC CPU2017 Floating Point Rate Result

My Corporation

SPECrate2017_fp_base = 4.60

SPECrate2017_fp_peak = Not Run

CPU2017 License: nnn (Your SPEC license number)
Test Sponsor: My Corporation
Tested by: My Corporation

Test Date: Nov-2017
Hardware Availability:
Software Availability:

Errors (Continued)

538.imagick_r (base) did not have enough runs!
511.povray_r (base) did not have enough runs!
526.blender_r (base) did not have enough runs!
510.parest_r (base) did not have enough runs!
549.fotonik3d_r (base) did not have enough runs!
521.wrf_r (base) did not have enough runs!
519.lbm_r (base) did not have enough runs!
554.roms_r (base) did not have enough runs!

Results Table

Benchmark	Base							Peak						
	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
503.bwaves_r														
507.cactuBSSN_r														
508.namd_r	1	**206**	**4.60**	206	4.61	207	4.59							
510.parest_r														
511.povray_r														
519.lbm_r														
521.wrf_r														
526.blender_r														
527.cam4_r														
538.imagick_r														
544.nab_r														
549.fotonik3d_r														
554.roms_r														

SPECrate2017_fp_base = 4.60

SPECrate2017_fp_peak = Not Run

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

```
The config file option 'submit' was used.
```

General Notes

```
Environment variables set by runcpu before the start of the run:
LD_LIBRARY_PATH = "/mnt/freezedisk/llvm-intptr-br2-correct2-release/lib"
LIBRARY_PATH = "/mnt/freezedisk/llvm-intptr-br2-correct2-release/lib"

PATH = "/mnt/freezedisk/llvm-intptr-br2-correct2-release/bin:/mnt/freezedisk/speccpu2017-intptr/bin:/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games:/usr/local/games:/snap/bin:/snap/bin"
```

Platform Notes

```
Sysinfo program /mnt/freezedisk/speccpu2017-intptr/bin/sysinfo
Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f
running on freeze4 Fri Nov  3 18:01:19 2017

SUT (System Under Test) info as seen by some common utilities.
For more information on this section, see
   https://www.spec.org/cpu2017/Docs/config.html#sysinfo

From /proc/cpuinfo
   model name : Intel(R) Core(TM) i3-6100 CPU @ 3.70GHz
      1  "physical id"s (chips)
      2 "processors"
   cores, siblings (Caution: counting these is hw and system dependent. The following
   excerpts from /proc/cpuinfo might not be reliable.  Use with caution.)
      cpu cores : 2
      siblings  : 2
      physical 0: cores 0 1

From lscpu:
     Architecture:          x86_64
     CPU op-mode(s):        32-bit, 64-bit
     Byte Order:            Little Endian
     CPU(s):                2
     On-line CPU(s) list:   0,1
     Thread(s) per core:    1
     Core(s) per socket:    2
     Socket(s):             1
     NUMA node(s):          1
     Vendor ID:             GenuineIntel
     CPU family:            6
     Model:                 94
     Model name:            Intel(R) Core(TM) i3-6100 CPU @ 3.70GHz
     Stepping:              3
     CPU MHz:               3700.000
     CPU max MHz:           3700.0000
     CPU min MHz:           800.0000
     BogoMIPS:              7392.16
     Virtualization:        VT-x
     L1d cache:             32K
     L1i cache:             32K
     L2 cache:              256K
     L3 cache:              3072K
     NUMA node0 CPU(s):     0,1
     Flags:                 fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov
     pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp
     lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc
     aperfmperf eagerfpu pni pclmulqdq dtes64 monitor ds_cpl vmx est tm2 ssse3 sdbg fma
```

(Continued on next page)

Platform Notes (Continued)

```
      cx16 xtpr pdcm pcid sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave
      avx f16c rdrand lahf_lm abm 3dnowprefetch epb intel_pt tpr_shadow vnmi flexpriority
      ept vpid fsgsbase tsc_adjust bmi1 avx2 smep bmi2 erms invpcid mpx rdseed adx smap
      clflushopt xsaveopt xsavec xgetbv1 dtherm arat pln pts hwp hwp_notify hwp_act_window
      hwp_epp

 /proc/cpuinfo cache data
    cache size : 3072 KB

 From numactl --hardware  WARNING: a numactl 'node' might or might not correspond to a
 physical chip.
   available: 1 nodes (0)
   node 0 cpus: 0 1
   node 0 size: 7676 MB
   node 0 free: 7226 MB
   node distances:
   node   0
     0:  10

 From /proc/meminfo
    MemTotal:        7860684 kB
    HugePages_Total:       0
    Hugepagesize:       2048 kB

 /usr/bin/lsb_release -d
    Ubuntu 16.04.3 LTS

 From /etc/*release* /etc/*version*
    debian_version: stretch/sid
    os-release:
       NAME="Ubuntu"
       VERSION="16.04.3 LTS (Xenial Xerus)"
       ID=ubuntu
       ID_LIKE=debian
       PRETTY_NAME="Ubuntu 16.04.3 LTS"
       VERSION_ID="16.04"
       HOME_URL="http://www.ubuntu.com/"
       SUPPORT_URL="http://help.ubuntu.com/"

 uname -a:
    Linux freeze4 4.4.0-97-generic #120-Ubuntu SMP Tue Sep 19 17:28:18 UTC 2017 x86_64
    x86_64 x86_64 GNU/Linux

 run-level 3 Oct 30 07:30

 SPEC is set to: /mnt/freezedisk/speccpu2017-intptr
    Filesystem     Type  Size  Used Avail Use% Mounted on
```

(Continued on next page)

Platform Notes (Continued)

```
    /dev/sda1       ext4  230G   59G  159G  27% /mnt/freezedisk

 Additional information from dmidecode follows.  WARNING: Use caution when you interpret
 this section. The 'dmidecode' program reads system data which is "intended to allow
 hardware to be accurately determined", but the intent may not be met, as there are
 frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

 (End of data from sysinfo program)
```

Compiler Version Notes

```
==============================================================================
 CXXC 508.namd_r(base)
------------------------------------------------------------------------------
clang version 6.0.0 (https://github.com/aqjune/clang-intptr.git
  b099f9b86954800bcbdee427fc703eb8a30389da)
  (https://github.com/aqjune/llvm-intptr.git
  072bcfdd83ea02b321f72fca30d5a8384325de92)
Target: x86_64-unknown-linux-gnu
Thread model: posix
InstalledDir: /mnt/freezedisk/llvm-intptr-br2-correct2-release/bin
Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5
Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5.4.0
Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/6
Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/6.0.0
Selected GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5.4.0
Candidate multilib: .;@m64
Selected multilib: .;@m64
------------------------------------------------------------------------------
```

Base Runtime Environment

C++ benchmarks:

508.namd_r: No flags used

Base Compiler Invocation

C++ benchmarks:

508.namd_r: clang++

CPU2017 License: nnn (Your SPEC license number)
Test Sponsor: My Corporation
Tested by: My Corporation

Test Date: Nov-2017
Hardware Availability:
Software Availability:

Base Portability Flags

508.namd_r: `-DSPEC_LP64`

Base Optimization Flags

C++ benchmarks:

508.namd_r: `-m64 -O3 -mavx -z muldefs`

Base Other Flags

C++ benchmarks:

508.namd_r: `No flags used`

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.2 on 2017-11-03 18:01:19+0900.
Report generated on 2017-11-03 18:11:54 by CPU2017 PDF formatter v5748.