SPEC® CPU2017 Integer Rate Result Copyright 2017 Standard Performance Evaluation Corporation My Corporation SPECrate2017_int_base = SPECrate2017 int peak Yot Run Test Date: Nov-2017 CPU2017 License: nnn (Your SPEC license number) Hardware Availability: **Test Sponsor:** My Corporation Tested by: Software Availability: My Corporation **Copies** 0 1.00 2.00 6.00 500.perlbench_r 502.gcc_r 505.mcf r 520.omnetpp_r 523.xalancbmk_r 7.22 525.x264 r 531.deepsjeng_r 541.leela r 548.exchange2_r 557.xz_r SPECrate2017 int base (7.22) Hardware Software CPU Name: Intel Core i7-7700 OS: Ubuntu 16.04.3 LTS Max MHz.: 4.4.0-97-generic C/C++: Version 3.9.0 of Clang, the Nominal: Compiler: Enabled: cores, 1 chip, threads/core LLVM Compiler Infrastructure Orderable: Fortran: Version 4.8.2 of GCC, the Cache L1: **GNU Compiler Collection** DragonEgg: Version 3.5.2, the L2: LLVM Compiler Infrastructure L3: Other: Parallel: No 7.507 GB fixme: If using DDR3, format is: Firmware: Memory: 'N GB (M x N GB nRxn PCn-nnnnnR-n, ECC)' File System: ext4 39 GB add more disk info here System State: Run level 3 (add definition here) Storage: **Ø**ther: Base Pointers: 64-bit Peak Pointers: Not Applicable Other: **Errors**

'reportable' flag not set during run

505.mcf_r (base) did not have enough runs!

520.omnetper (base) did not have enough runs!

500.perlbench_r (base) did not have enough runs!

541.leela r (base) did not have enough runs!

502.gcc_r (base) did not have enough runs!

523.xalancbmk_r (base) did not have enough runs!

557.xz_r (base) did not have enough runs!

548.exchange2_r (base) did not have enough runs!

(Continued on next page)

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_int_base =

SPECrate2017_int_peak **∜**ot Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation Tested by: My Corporation Test Date: Nov-2017

> Hardware Availability: Software Availability:

Errors (Continued)

531.deepsjeng r (base) did not have enough runs!

Results Table

	Base							Peak						
Benchmark	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio	Copies	Seconds	Ratio	Seconds	Ratio	Seconds	Ratio
500.perlbench_r								\						
502.gcc_r														
505.mcf_r								\mathcal{N}						
520.omnetpp_r			>											
523.xalancbmk_r														
525.x264_r	1	<u>243</u>	<u>7.22</u>	243	7.22	243	7.22							
531.deepsjeng_r														
541.leela_r						1/								
548.exchange2_r				/		\searrow								
557.xz_r														

SPECrate2017_int_base = SPECrate2017_int_peak/7

Results appear in the order in which they were run. Bold underlined text indicates a median measurement.

Submit Notes

The config file option ubmit' was used.

General Notes

Environment variables set by runcpu before the start of the run: LD_LIBKARY_RATH = \"/mnt/freezedisk/llvm-intptr-br5.5-gvnnocast-release/lib" LIBRARY_PATH = "/mat/freezedisk/llvm-intptr-br5.5-gvnnocast-release/lib"

Platform Notes

Sysinfo program /mnt/freezedisk/speccpu2017-intptr/bin/sysinfo Rev: r5797 of 2017-06-14 96c45e4568ad54c135fd618bcc091c0f running on freeze3 Mon Nov 13 15:13:05 2017

SUT (System Under Test) info as seen by some common utilities. For more information on this section, see https://www.spec.org/cpu2017/Docs/config.html#sysinfo

(Continued on next page)

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

Test Sponsor:

Tested by:

SPECrate2017_int_base = 7.2

SPECrate2017_int_peak Not Run

CPU2017 License: nnn (Your SPEC license number)

My Corporation
My Corporation

Test Date: Nov-2017

Hardware Availability: Software Availability:

Platform Notes (Continued)

```
From /proc/cpuinfo
   model name : Intel(R) Core(TM) i7-7700 CPU @ 3.60GHz
      1 "physical id"s (chips)
      4 "processors"
   cores, siblings (Caution: counting these is hw and system dependent. The following
   excerpts from /proc/cpuinfo might not be reliable. Use with caution.)
      cpu cores : 4
      siblings : 4
      physical 0: cores 0 1 2
From lscpu:
     Architecture:
                              %2-bit<mark>/</mark>/
     CPU op-mode(s):
     Byte Order:
                              Little Endian
     CPU(s):
     On-line CPU(s) list:
                              0
     Thread(s) per core:
                              1
     Core(s) per socket:
     Socket(s):
     NUMA node(s):
     Vendor ID:
                              GenuineIntel
     CPU family:
     Model:
     Model name;
                              Intel(R) Core(TM) i7-7700 CPU @ 3.60GHz
     Stepping:
                              3561.609
     CPU MHz;
                              4200.0000
     CPU max MHz:
                              800.0000
     CPU min MHz:
     BogOMIPS:
                              7199.62
     Virtualization:
                              VT-x
     1/1d cache:
                              32K
     Zi cache:
                              32K
     L2 cache:
                              256K
```

8192K

0 - 3

fpu vme de pse tsc msr pae mce cx8 apic sep mtrr pge mca cmov pat pse36 clflush dts acpi mmx fxsr sse sse2 ss ht tm pbe syscall nx pdpe1gb rdtscp lm constant_tsc art arch_perfmon pebs bts rep_good nopl xtopology nonstop_tsc aperfmperf eagerfpu pni pclmulqdq dtes64 monitor ds_cpl vmx smx est tm2 ssse3 sdbg fma cx16 xtpr pdcm pcid sse4_1 sse4_2 x2apic movbe popcnt tsc_deadline_timer aes xsave avx f16c rdrand lahf_lm abm 3dnowprefetch epb intel_pt tpr_shadow vnmi flexpriority ept vpid fsgsbase tsc_adjust bmi1 hle avx2 smep bmi2 erms invpcid rtm mpx rdseed adx smap clflushopt xsaveopt xsavec xgetbv1 dtherm arat pln pts hwp hwp_notify hwp_act_window hwp_epp

/proc/cpuinfo cache data
 cache size : 8192 KB

L3 cache:

NUMA node CPU(s):

(Continued on next page)

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

Test Sponsor:

Tested by:

SPECrate2017_int_base = 7.2

SPECrate2017_int_peak Not Run

CPU2017 License: nnn (Your SPEC license number)

My Corporation
My Corporation

Test Date: Nov-2017

Hardware Availability: Software Availability:

Platform Notes (Continued)

```
From numactl --hardware WARNING: a numactl 'node' might or might not correspond to a
physical chip.
  available: 1 nodes (0)
  node 0 cpus: 0 1 2 3
  node 0 size: 7687 MB
  node 0 free: 7252 MB
  node distances:
 node
       Ω
    0: 10
From /proc/meminfo
   MemTotal:
   HugePages_Total:
                       2048 k
   Hugepagesize:
/usr/bin/lsb_release -d
   Ubuntu 16.04.3 LTS
From /etc/*release* /etc/*version*
   debian_version: stretch/sid
   os-release:
      NAME="Ubuntu
      VERSION="16.04.3 LTS (Xenial Xerus)"
      ID=ubuntx
      ID_LIKE debian
      PRETTY_NAME="Ubuntu 16.04.3 LTS"
      VERSION_ID="16.04"
      HOME_URL="http://www.ubuntu.com/"
      SUPPORT_URL="http://help.ubuntu.com/"
uname/~a:
   Linux freeze3 4.4.0-97-generic #120-Ubuntu SMP Tue Sep 19 17:28:18 UTC 2017 x86_64
   x86_64 x86_64 GNU/Linux
run level 3 Oct 29 18:30
SPEC is set to: /mnt/freezedisk/speccpu2017-intptr
                  Type Size Used Avail Use% Mounted on
   Filesystem
                        939G 727G 165G 82% /mnt/freezedisk
   /dev/sdb1
                  ext4
```

Additional information from dmidecode follows. WARNING: Use caution when you interpret this section. The 'dmidecode' program reads system data which is "intended to allow hardware to be accurately determined", but the intent may not be met, as there are frequent changes to hardware, firmware, and the "DMTF SMBIOS" standard.

(End of data from sysinfo program)

SPEC CPU2017 Integer Rate Result Copyright 2017 Standard Performance Evaluation Corporation My Corporation SPECrate2017_int_base = SPECrate2017_int_peak **∜**ot Run CPU2017 License: nnn (Your SPEC license number) Test Date: Nov-2017 **Test Sponsor:** My Corporation Hardware Availability: Software Availability: **Tested by:** My Corporation **Compiler Version Notes** CC 525.x264_r(base) clang version 6.0.0 (https://github.com/agjune/clang-intptr. 4c61e7d94696e3346da34031080891f5b176cbe3) (https://github.com/aqjune/llvm-intptr.git dc57902874362bda6a92afc0a30531112b9a1258) Target: x86_64-unknown-linux-gnu Thread model: posix InstalledDir: /mnt/freezedisk/llvm-intptr/bx5.5-gvmmqast-release/bin Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/5 Found candidate GCC installation: /usr lib/gcc/x86_64-linux-gnu/5.4.0 Found candidate GCC installation: /wsx/lbb/gcc/x86_64-linux-gnu/6 Found candidate GCC installation: /usr/lib/gcc/x86_64-linux-gnu/6.0.0 Selected GCC installation: /usx/llb/gcc/x86_64/linux-gnu/5.4.0 Candidate multilib: .;@m64 Selected multilib: .;@m64 **Base Runtime Environment** C benchmarks: 525.x264_r: No flags used **Base Compiler Invocation** C benchmarks 525.x264_r: clang **Base Portability Flags** 525.x264_r.-DSPEC LP64 **Base Optimization Flags** C benchmarks: (Continued on next page) Page 5 https://www.spec.org/ Standard Performance Evaluation Corporation (info@spec.org)

Copyright 2017 Standard Performance Evaluation Corporation

My Corporation

SPECrate2017_int_base = 7.22

SPECrate2017_int_peak Not Run

CPU2017 License: nnn (Your SPEC license number)

Test Sponsor: My Corporation **Tested by:** My Corporation

Test Date: Nov-2017

Hardware Availability: Software Availability:

Base Optimization Flags (Continued)

 $525.x264_r: -m64 -z$ muldefs -03 -mavx

Base Other Flags

C benchmarks:

 $525.x264_r$: No flags used

SPEC is a registered trademark of the Standard Performance Evaluation Corporation. All other brand and product names appearing in this result are trademarks or registered trademarks of their respective holders.

For questions about this result, please contact the tester. For other inquiries, please contact info@spec.org.

Tested with SPEC CPU2017 v1.0.2 on 2017-11-13 15:13:04-0500.

Report generated on 2017-11-13 15:26:00 by CPU2017 PDF formatter v5748.