

# Finite Automata

204213 Theory of Computation

Jittat Fakcharoenphol

Kasetsart University

November 5, 2008

# Outline

- 1 Examples
- 2 Formal definitions
- 3 Designing finite automata
- 4 Regular operations


# An automatic door

- Recall our automatic door example from last time?


# An automatic door

- Recall our automatic door example from last time?
- Let's see a simulation.

# What did you see?




# What did you see?




- There are two **states**:

# What did you see?



- There are two **states**: **closed** and **open**


# What did you see?



- There are two **states**: **closed** and **open**
- There are 4 possible inputs, and the state of the machine changes (or remains) after each input.




# What did you see?



- There are two **states**: **closed** and **open**
- There are 4 possible inputs, and the state of the machine changes (or remains) after each input.
- See that in table form:


	neither	front	rear	both
closed	closed	open	closed	closed
open	closed	open	open	open

# Another automaton: $M_1$




- This is the **state diagram** of  $M_1$ .

# Another automaton: $M_1$




- This is the **state diagram** of  $M_1$ .
- There are 3 states:  $q_1, q_2, q_3$ .

## Another automaton: $M_1$




- This is the **state diagram** of  $M_1$ .
- There are 3 states:  $q_1, q_2, q_3$ .
- $q_1$  is the **start state**. (see the arrow?)

## Another automaton: $M_1$



- This is the **state diagram** of  $M_1$ .
- There are 3 states:  $q_1, q_2, q_3$ .
- $q_1$  is the **start state**. (see the arrow?)
- $q_2$  is the **accept state**. (see the double circle)

# Another automaton: $M_1$



- This is the **state diagram** of  $M_1$ .
- There are 3 states:  $q_1, q_2, q_3$ .
- $q_1$  is the **start state**. (see the arrow?)
- $q_2$  is the **accept state**. (see the double circle)
- Arrows are **transitions**.

# Formal definition: why?

# Formal definition: why?

Formal definition gives

- Precision



# Formal definition: why?

Formal definition gives

- Precision
- Notation

# Transition function: $\delta$

- The rule for moving.

# Transition function: $\delta$

- The rule for moving.
- If you are in state  $q$ , after receiving 1 as an input, go to state  $p$ :

# Transition function: $\delta$

- The rule for moving.
- If you are in state  $q$ , after receiving 1 as an input, go to state  $p$ :

$$\delta(q, 1) = p$$

# Transition function: $\delta$

- The rule for moving.
- If you are in state  $q$ , after receiving 1 as an input, go to state  $p$ :

$$\delta(q, 1) = p$$

- $\delta$  is a function from

# Transition function: $\delta$

- The rule for moving.
- If you are in state  $q$ , after receiving 1 as an input, go to state  $p$ :

$$\delta(q, 1) = p$$

- $\delta$  is a function from **the set of states** and

# Transition function: $\delta$

- The rule for moving.
- If you are in state  $q$ , after receiving 1 as an input, go to state  $p$ :

$$\delta(q, 1) = p$$

- $\delta$  is a function from the set of states and the set of possible inputs to

# Transition function: $\delta$

- The rule for moving.
- If you are in state  $q$ , after receiving 1 as an input, go to state  $p$ :

$$\delta(q, 1) = p$$

- $\delta$  is a function from the set of states and the set of possible inputs to the set of states.




# Definition [finite automaton]


A **finite automaton** is a 5-tuple  $(Q, \Sigma, \delta, q_0, F)$  where

- 1  $Q$  is a finite set called the *states*,
- 2  $\Sigma$  is a finite set called the *alphabet*,
- 3  $\delta : Q \times \Sigma \longrightarrow Q$  is the *transition function*,
- 4  $q_0 \in Q$  is the *start state*, and
- 5  $F \subseteq Q$  is the *set of accept states*.

# Formal definition of $M_1$



# Formal definition of $M_1$




$M_1 = (Q, \Sigma, \delta, q_1, F)$ , where

- ①  $Q = \{q_1, q_2, q_3\}$ ,
- ②  $\Sigma = \{0, 1\}$ ,
- ③  $\delta$  can be described as

	0	1
$q_1$	$q_1$	$q_2$
$q_2$	$q_3$	$q_2$
$q_3$	$q_2$	$q_2$

- ④  $q_1$  is the start state, and
- ⑤  $F = \{q_2\}$ .

# Finite automaton $M_2$



# Language of a machine

- A set  $A$  of strings is called the **language of machine  $M$**  if  $A$  is the set of all strings that  $M$  accepts.

# Language of a machine

- A set  $A$  of strings is called the **language of machine  $M$**  if  $A$  is the set of all strings that  $M$  accepts.
- We write  $L(M) = A$ .
- We also say that  **$M$  recognizes  $A$** .

# Language of machine $M_1$


- Let  $A = \{w \mid w \text{ contains at least one 1 and an even number of 0's follow the last 1}\}$ .
- $L(M_1) = A$

# Language of machine $M_1$

- Let  $A = \{w \mid w \text{ contains at least one 1 and an even number of 0's follow the last 1}\}$ .
- $L(M_1) = A$
- Or, we can say that  $M_1$  recognizes  $A$ .




# Finite automaton $M_2$




What is the language that  $M_2$  recognizes?

# Finite automaton $M_3$




What is the language that  $M_3$  recognizes?

# Finite automaton $M_4$



What is the language that  $M_4$  recognizes?

# Finite automaton $M_5$



What is the language that  $M_5$  recognizes?

# Formal definition of computation

Let  $M = (Q, \Sigma, \delta, q_0, F)$  be a finite automaton and let  $w = w_1 w_2 \cdots w_n$  be a string over alphabet  $\Sigma$ .  **$M$  accepts  $w$**  if

# Formal definition of computation

Let  $M = (Q, \Sigma, \delta, q_0, F)$  be a finite automaton and let  $w = w_1 w_2 \cdots w_n$  be a string over alphabet  $\Sigma$ .  **$M$  accepts  $w$**  if there exists a sequence of states  $r_0, r_1, \dots, r_n$  in  $Q$  such that

# Formal definition of computation

Let  $M = (Q, \Sigma, \delta, q_0, F)$  be a finite automaton and let  $w = w_1 w_2 \cdots w_n$  be a string over alphabet  $\Sigma$ .  **$M$  accepts  $w$**  if there exists a sequence of states  $r_0, r_1, \dots, r_n$  in  $Q$  such that

- ①  $r_0 = q_0$ ,
- ②  $\delta(r_i, w_{i+1}) = r_{i+1}$  for  $i = 0, \dots, n-1$ , and
- ③  $r_n \in F$ .

# Definition [regular language]

- **$M$  recognizes language  $A$**  if  $A = \{w \mid M \text{ accepts } w\}$ .



# Definition [regular language]

- **$M$  recognizes language  $A$**  if  $A = \{w \mid M \text{ accepts } w\}$ .
- A language is called a **regular language** if some finite automaton recognizes it.

# Designing finite automata

Tips:

- Pretending that you are the automaton.

# Designing finite automata

Tips:

- Pretending that you are the automaton.
- You get one input at a time.

# Designing finite automata

## Tips:

- Pretending that you are the automaton.
- You get one input at a time.
- Think about what you have to **remember** to make decision correctly. (That would be a set of states.)

# Practice

Language consisting of all strings with an odd number of 1's.

# Building more complex finite automata

- Let  $\Sigma = \{0, 1, 2\}$ .
- Can you build a finite automaton  $M_3$  that accepts all strings whose sums are divisible by 3?

# Building more complex finite automata

- Let  $\Sigma = \{0, 1, 2\}$ .
- Can you build a finite automaton  $M_3$  that accepts all strings whose sums are divisible by 3?
- Can you build a finite automaton  $M_5$  that accepts all strings whose sums are divisible by 5?

# Building more complex finite automata

- Let  $\Sigma = \{0, 1, 2\}$ .
- Can you build a finite automaton  $M_3$  that accepts all strings whose sums are divisible by 3?
- Can you build a finite automaton  $M_5$  that accepts all strings whose sums are divisible by 5?
- Can you build a finite automaton  $M_5$  that accepts all strings whose sums are divisible by 3 or 5?



# Construction from smaller building boxes

This is one of important ideas in computer science.

# Regular operations

- Operations for “manipulating” languages.
- A toolbox for

# Regular operations

- Operations for “manipulating” languages.
- A toolbox for
  - building more complex machines.

# Regular operations

- Operations for “manipulating” languages.
- A toolbox for
  - building more complex machines.
  - reasoning about larger (?) classes of machines.

# Regular operations

- Operations for “manipulating” languages.
- A toolbox for
  - building more complex machines.
  - reasoning about larger (?) classes of machines.
  - some fun (?)

# A set and operations

- A collection of objects is **closed under some operation** if applying that operation to objects in that set only result in object in that set.

# A set and operations

- A collection of objects is **closed under some operation** if applying that operation to objects in that set only result in object in that set.
- E.g., a set of natural number  $\mathcal{N}$  is closed under multiplication.

# Definition [regular operations]

For a language  $A$  and  $B$ , the regular operations **union**, **concatenation**, and **star** can be defined as follows.

- **Union**:  $A \cup B = \{x \mid x \in A \text{ or } x \in B\}$
- **Concatenation**:  $A \circ B = \{xy \mid x \in A \text{ and } y \in B\}$
- **Star**:  $A^* = \{x_1 x_2 \cdots x_k \mid k \geq 0 \text{ and each } x_i \in A\}$



# Can regular operations make regular languages irregular?

- Irregular languages?

# Can regular operations make regular languages irregular?

- Irregular languages?
  - A language is irregular if there is no finite automaton recognizing it.

# Can regular operations make regular languages irregular?

- Irregular languages?
  - A language is irregular if there is no finite automaton recognizing it.
- Look at each regular operation, starting with union.

# Can regular operations make regular languages irregular?

- Irregular languages?
  - A language is irregular if there is no finite automaton recognizing it.
- Look at each regular operation, starting with union.
- If  $A_1$  and  $A_2$  are regular, is  $A_1 \cup A_2$  regular?

# Can regular operations make regular languages irregular?

- Irregular languages?
  - A language is irregular if there is no finite automaton recognizing it.
- Look at each regular operation, starting with union.
- If  $A_1$  and  $A_2$  are regular, is  $A_1 \cup A_2$  regular?
- How can we answer that?

# Can regular operations make regular languages irregular?

- Irregular languages?
  - A language is irregular if there is no finite automaton recognizing it.
- Look at each regular operation, starting with union.
- If  $A_1$  and  $A_2$  are regular, is  $A_1 \cup A_2$  regular?
- How can we answer that?
- Go back to the definition of regular languages.
  - **Goal:** to show that there exists a finite automaton recognizing  $A_1 \cup A_2$ ,

# Can regular operations make regular languages irregular?

- Irregular languages?
  - A language is irregular if there is no finite automaton recognizing it.
- Look at each regular operation, starting with union.
- If  $A_1$  and  $A_2$  are regular, is  $A_1 \cup A_2$  regular?
- How can we answer that?
- Go back to the definition of regular languages.
  - **Goal:** to show that there exists a finite automaton recognizing  $A_1 \cup A_2$ ,
  - **Given that:** there are finite automata  $M_1$  and  $M_2$  such that  $M_1$  recognizes  $A_1$  and  $M_2$  that recognizes  $A_2$ .

# Union operation

## Theorem

*The class of regular languages is closed under the union operation*



# Union operation

## Theorem

*The class of regular languages is closed under the union operation*

## Approach for proving it.

- Proof by construction.

# Union operation

## Theorem

*The class of regular languages is closed under the union operation*

### Approach for proving it.

- Proof by construction.
- We know that there are finite automata  $M_1$  that recognizes  $A_1$  and  $M_2$  that recognizes  $A_2$ .

# Union operation

## Theorem

*The class of regular languages is closed under the union operation*

### Approach for proving it.

- Proof by construction.
- We know that there are finite automata  $M_1$  that recognizes  $A_1$  and  $M_2$  that recognizes  $A_2$ .
- We shall construct  $M$  that recognizes  $A_1 \cup A_2$ .

# How can we show that?

- Again, pretend that you are a finite automaton trying to recognizes  $A_1 \cup A_2$ .

# How can we show that?

- Again, pretend that you are a finite automaton trying to recognize  $A_1 \cup A_2$ .
  - Arrh.. doesn't seem to help.

# How can we show that?

- Again, pretend that you are a finite automaton trying to recognize  $A_1 \cup A_2$ .
  - Arrh.. doesn't seem to help.
- Let's try again:

# How can we show that?

- Again, pretend that you are a finite automaton trying to recognize  $A_1 \cup A_2$ .
  - Arrh.. doesn't seem to help.
- Let's try again: suppose that we want to recognize  $A_1 \cup A_2$  and also have  $M_1$  and  $M_2$  standing in front of us.

# How can we show that?

- Again, pretend that you are a finite automaton trying to recognize  $A_1 \cup A_2$ .
  - Arrh.. doesn't seem to help.
- Let's try again: suppose that we want to recognize  $A_1 \cup A_2$  and also have  $M_1$  and  $M_2$  standing in front of us.
  - Can we use them to recognize  $A_1 \cup A_2$ ?



# Given

We have to be formal:

# Given

We have to be formal:

- Machine  $M_1 = (Q_1, \Sigma, \delta_1, q_1, F_1)$  recognizing  $A_1$
- Machine  $M_2 = (Q_2, \Sigma, \delta_2, q_2, F_2)$  recognizing  $A_2$

# Machine $M$ recognizing $A_1 \cup A_2$

Machine  $M = (Q, \Sigma, \delta, q_0, F)$ , such that

- $Q = Q_1 \times Q_2$ ,

# Machine $M$ recognizing $A_1 \cup A_2$

Machine  $M = (Q, \Sigma, \delta, q_0, F)$ , such that

- $Q = Q_1 \times Q_2$ ,
- $\Sigma$  remains the same,

# Machine $M$ recognizing $A_1 \cup A_2$

Machine  $M = (Q, \Sigma, \delta, q_0, F)$ , such that

- $Q = Q_1 \times Q_2$ ,
- $\Sigma$  remains the same,
- $\delta$  is defined as

$$\delta((r_1, r_2), a) = (\delta_1(r_1, a), \delta_2(r_2, a)),$$

# Machine $M$ recognizing $A_1 \cup A_2$

Machine  $M = (Q, \Sigma, \delta, q_0, F)$ , such that

- $Q = Q_1 \times Q_2$ ,
- $\Sigma$  remains the same,
- $\delta$  is defined as

$$\delta((r_1, r_2), a) = (\delta_1(r_1, a), \delta_2(r_2, a)),$$

- $q_0 = (q_1, q_2)$ ,

# Machine $M$ recognizing $A_1 \cup A_2$

Machine  $M = (Q, \Sigma, \delta, q_0, F)$ , such that

- $Q = Q_1 \times Q_2$ ,
- $\Sigma$  remains the same,
- $\delta$  is defined as

$$\delta((r_1, r_2), a) = (\delta_1(r_1, a), \delta_2(r_2, a)),$$

- $q_0 = (q_1, q_2)$ ,
- $F = \{(r_1, r_2) \mid r_1 \in F_1 \text{ or } r_2 \in F_2\}$

# Other regular operations

- Can we use the same technique to prove that  $A_1 \circ A_2$  is regular?