

# Turing Machines and their variants

204213 Theory of Computation

Jittat Fakcharoenphol

Kasetsart University

January 6, 2009


# Outline

- 1 Review: Turing Machines
- 2 How TM's compute
- 3 More example
- 4 Variants of TM's

# Turing Machines: Components

- An infinite **tape**.
- A tape head that can
  - **read and write** to the tape, and
  - **move** around the tape.

# Schematic



# How Turing machines work

- The tape initially contains an input string.

# How Turing machines work

- The tape initially contains an input string.
- The rest of the tape is blank (denoted by  $\sqcup$ ).

# How Turing machines work

- The tape initially contains an input string.
- The rest of the tape is blank (denoted by  $\sqcup$ ).
- The machine reads a symbol from of the tape where its head is at.

# How Turing machines work

- The tape initially contains an input string.
- The rest of the tape is blank (denoted by  $\sqcup$ ).
- The machine reads a symbol from the tape where its head is at.
- It can write a symbol back and move **left** or **right**.



# How Turing machines work

- The tape initially contains an input string.
- The rest of the tape is blank (denoted by  $\sqcup$ ).
- The machine reads a symbol from of the tape where its head is at.
- It can write a symbol back and move **left** or **right**.
- At the end of the computation, the machine outputs **accept** or **reject**, by entering accept state of reject state. (After changing, it halts.)

# How Turing machines work

- The tape initially contains an input string.
- The rest of the tape is blank (denoted by  $\sqcup$ ).
- The machine reads a symbol from the tape where its head is at.
- It can write a symbol back and move **left** or **right**.
- At the end of the computation, the machine outputs **accept** or **reject**, by entering accept state or reject state. (After changing, it halts.)
- It can go on forever (not entering any accept or reject states).

# Definition

## Definition (Turing Machine)

A **Turing machine** is a 7-tuple,  $(Q, \Sigma, \Gamma, \delta, q_0, q_{accept}, q_{reject})$ , where  $Q, \Sigma, \Gamma$  are finite sets and

- ①  $Q$  is the set of states,
- ②  $\Sigma$  is the input alphabet not containing the **blank symbol**  $\sqcup$ ,
- ③  $\Gamma$  is the tape alphabet, where  $\sqcup \in \Gamma$  and  $\Sigma \subset \Gamma$ ,
- ④  $\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R\}$  is the transition function,
- ⑤  $q_0 \in Q$  is the start state,
- ⑥  $q_{accept} \in Q$  is the accept state, and
- ⑦  $q_{reject} \in Q$  is the reject state, where  $q_{accept} \neq q_{reject}$ .

# Defining how TM computes

We need two key concepts:

- Configurations: the “states” of the TM
- Transition: how the TM moves.

# Configuration

- At any point of the computation, the TM can be in some state, and at some position on the tape.


# Configuration

- At any point of the computation, the TM can be in some state, and at some position on the tape.
- A **configuration** of the Turing machine, “the current computing status” can be defined with the current state, the current position of the tape head, and the content of the tape.

# Configuration

- At any point of the computation, the TM can be in some state, and at some position on the tape.
- A **configuration** of the Turing machine, “the current computing status” can be defined with the current state, the current position of the tape head, and the content of the tape.
- We usually write configuration as:  $u q v$ , where  $q$  is the state,  $uv$  is the current content of the tape, and the TM is at the first symbol of  $v$ .

# Configuration: $10101q_71101$





# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.

# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.
- Let  $a, b, c \in \Gamma$ , and  $u, v \in \Gamma^*$ .

# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.
- Let  $a, b, c \in \Gamma$ , and  $u, v \in \Gamma^*$ . If  $\delta(q_i, b) = (q_j, c, L)$ , then  $ua \text{ } q_i \text{ } bv$  yields

# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.
- Let  $a, b, c \in \Gamma$ , and  $u, v \in \Gamma^*$ . If  $\delta(q_i, b) = (q_j, c, L)$ , then  $ua\ q_i\ bv$  yields  $u\ q_j\ acv$ .

# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.
- Let  $a, b, c \in \Gamma$ , and  $u, v \in \Gamma^*$ . If  $\delta(q_i, b) = (q_j, c, L)$ , then  $ua\ q_i\ bv$  yields  $u\ q_j\ acv$ . (This is a left-move.)

# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.
- Let  $a, b, c \in \Gamma$ , and  $u, v \in \Gamma^*$ . If  $\delta(q_i, b) = (q_j, c, L)$ , then  $ua\ q_i\ bv$  yields  $u\ q_j\ acv$ . (This is a left-move.)
- If  $\delta(q_i, b) = (q_j, c, R)$ , then  $ua\ q_i\ bv$  yields

# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.
- Let  $a, b, c \in \Gamma$ , and  $u, v \in \Gamma^*$ . If  $\delta(q_i, b) = (q_j, c, L)$ , then  $ua\ q_i\ bv$  yields  $u\ q_j\ acv$ . (This is a left-move.)
- If  $\delta(q_i, b) = (q_j, c, R)$ , then  $ua\ q_i\ bv$  yields  $uac\ q_j\ v$ .

# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.
- Let  $a, b, c \in \Gamma$ , and  $u, v \in \Gamma^*$ . If  $\delta(q_i, b) = (q_j, c, L)$ , then  $ua\ q_i\ bv$  yields  $u\ q_j\ acv$ . (This is a left-move.)
- If  $\delta(q_i, b) = (q_j, c, R)$ , then  $ua\ q_i\ bv$  yields  $uac\ q_j\ v$ .
- Are these all case?



# One-step move

- Configuration  $C_1$  **yields** configuration  $C_2$  if the Turing machine can move from  $C_1$  to  $C_2$  in one step.
- Let  $a, b, c \in \Gamma$ , and  $u, v \in \Gamma^*$ . If  $\delta(q_i, b) = (q_j, c, L)$ , then  $ua q_i bv$  yields  $u q_j acv$ . (This is a left-move.)
- If  $\delta(q_i, b) = (q_j, c, R)$ , then  $ua q_i bv$  yields  $uac q_j v$ .
- Are these all case? No. We'll have to deal with the case when the head are a the end of the tape on both sides.

# One-step move: at the ends of the tape

- When at the left end, trying to move left:

# One-step move: at the ends of the tape

- When at the left end, trying to move left: the TM must stay at the same place.

# One-step move: at the ends of the tape

- When at the left end, trying to move left: the TM must stay at the same place.
  - If  $\delta(q_i, b) = (q_j, c, L)$ , then  $q_i$   $bv$  yields

# One-step move: at the ends of the tape

- When at the left end, trying to move left: the TM must stay at the same place.
  - If  $\delta(q_i, b) = (q_j, c, L)$ , then  $q_i \text{ } b\text{v}$  yields  $q_j \text{ } c\text{v}$ .

# One-step move: at the ends of the tape

- When at the left end, trying to move left: the TM must stay at the same place.
  - If  $\delta(q_i, b) = (q_j, c, L)$ , then  $q_i \text{ } bv$  yields  $q_j \text{ } cv$ .
- When at the right end, trying to move right:

# One-step move: at the ends of the tape

- When at the left end, trying to move left: the TM must stay at the same place.
  - If  $\delta(q_i, b) = (q_j, c, L)$ , then  $q_i \text{ } bv$  yields  $q_j \text{ } cv$ .
- When at the right end, trying to move right: just goes over the empty symble.

# One-step move: at the ends of the tape

- When at the left end, trying to move left: the TM must stay at the same place.
  - If  $\delta(q_i, b) = (q_j, c, L)$ , then  $q_i \text{ } bv$  yields  $q_j \text{ } cv$ .
- When at the right end, trying to move right: just goes over the empty symbol.
  - We can treat the configuration  $ua \text{ } q_i$  as  $ua \text{ } q_i \sqcup$ , and this case is not a special case anymore.



# One-step move: at the ends of the tape

- When at the left end, trying to move left: the TM must stay at the same place.
  - If  $\delta(q_i, b) = (q_j, c, L)$ , then  $q_i \text{ } bv$  yields  $q_j \text{ } cv$ .
- When at the right end, trying to move right: just goes over the empty symbol.
  - We can treat the configuration  $ua \text{ } q_i$  as  $ua \text{ } q_i \sqcup$ , and this case is not a special case anymore.

# Configurations

3 types of special configurations:

- the start configuration,

# Configurations

3 types of special configurations:

- the start configuration,
- the accepting configurations, and

# Configurations

3 types of special configurations:

- the start configuration,
- the accepting configurations, and
- the rejecting configurations.

# Configurations

3 types of special configurations:

- the start configuration,
- the accepting configurations, and
- the rejecting configurations.
- The accepting and rejecting configurations are called halting configurations.

# Computation with TM

A Turing machine  $M$  accepts input  $w$  if a sequence of configurations  $C_1, C_2, \dots, C_k$  exists, where

- 1  $C_1$  is the start configuration of  $M$  on input  $w$ ,
- 2 each  $C_i$  yields  $C_{i+1}$ , and
- 3  $C_k$  is an accepting configuration.

- A collection of strings that a Turing machine  $M$  accepts is the language of  $M$ , denoted by  $L(M)$ .

- A collection of strings that a Turing machine  $M$  accepts is the language of  $M$ , denoted by  $L(M)$ .
- We say that  $M$  **recognizes**  $L(M)$ .



- A collection of strings that a Turing machine  $M$  accepts is the language of  $M$ , denoted by  $L(M)$ .
- We say that  $M$  **recognizes**  $L(M)$ .

### Definition

A language is called **Turing-recognizable** if some Turing machine recognizes it.

# Output of a TM

- The output of a TM can be **accept**, **reject**, or **loop**.

# Output of a TM

- The output of a TM can be **accept**, **reject**, or **loop**.
- A Turing machine may not accept or reject a string.

# Output of a TM

- The output of a TM can be **accept**, **reject**, or **loop**.
- A Turing machine may not accept or reject a string.
- We are interested particularly in TM that **halts** (does not loop).

# Output of a TM

- The output of a TM can be **accept**, **reject**, or **loop**.
- A Turing machine may not accept or reject a string.
- We are interested particularly in TM that **halts** (does not loop). We call them **decider**.

# Output of a TM

- The output of a TM can be **accept**, **reject**, or **loop**.
- A Turing machine may not accept or reject a string.
- We are interested particularly in TM that **halts** (does not loop). We call them **decider**.
- A decider that recognizes some language also is said to **decides** that language.

## Definition

A language is called **Turing-decidable** or **decidable** if some Turing machine decides it.

# Arithmetics

- Design a TM  $M_3$  that decides the language

$$C = \{a^i b^j c^k \mid i \times j = k \text{ and } i, j, k \geq 1\}.$$



# TM: $M_3$

$M_3$  = "On input string  $w$ :

- 1 Scan the input from left to right to check if it is  $a^+b^+c^+$  and **reject** if it isn't.

# TM: $M_3$

$M_3$  = "On input string  $w$ :

- 1 Scan the input from left to right to check if it is  $a^+b^+c^+$  and **reject** if it isn't.
- 2 Move the head back to the left-hand end of the tape.

# TM: $M_3$

$M_3$  = "On input string  $w$ :

- 1 Scan the input from left to right to check if it is  $a^+b^+c^+$  and **reject** if it isn't.
- 2 Move the head back to the left-hand end of the tape.
- 3 Cross off an  $a$  and scan to the right until  $b$  occurs. Cross each pair of  $b$ 's and  $c$ 's until all  $b$ 's are crossed off.

# TM: $M_3$

$M_3$  = "On input string  $w$ :

- ① Scan the input from left to right to check if it is  $a^+b^+c^+$  and **reject** if it isn't.
- ② Move the head back to the left-hand end of the tape.
- ③ Cross off an  $a$  and scan to the right until  $b$  occurs. Cross each pair of  $b$ 's and  $c$ 's until all  $b$ 's are crossed off.
  - If  $c$ 's are gone before  $b$ , **reject**.

# TM: $M_3$

$M_3$  = "On input string  $w$ :

- ① Scan the input from left to right to check if it is  $a^+b^+c^+$  and **reject** if it isn't.
- ② Move the head back to the left-hand end of the tape.
- ③ Cross off an  $a$  and scan to the right until  $b$  occurs. Cross each pair of  $b$ 's and  $c$ 's until all  $b$ 's are crossed off.
  - If  $c$ 's are gone before  $b$ , **reject**.
- ④ Restore all  $b$ 's and go back to step 3 if there're more  $a$ 's.

# TM: $M_3$

$M_3$  = "On input string  $w$ :

- ① Scan the input from left to right to check if it is  $a^+b^+c^+$  and **reject** if it isn't.
- ② Move the head back to the left-hand end of the tape.
- ③ Cross off an  $a$  and scan to the right until  $b$  occurs. Cross each pair of  $b$ 's and  $c$ 's until all  $b$ 's are crossed off.
  - If  $c$ 's are gone before  $b$ , **reject**.
- ④ Restore all  $b$ 's and go back to step 3 if there're more  $a$ 's.
  - If all  $a$ 's are crossed off, check if there is no  $c$ 's left. If that's the case, **accept**, otherwise **reject**."

# Element distinctness

- Given a list of strings over  $\{0, 1\}$  separated by #'s, design a TM that accepts if all strings in the list are different.

# Element distinctness

- Given a list of strings over  $\{0, 1\}$  separated by #'s, design a TM that accepts if all strings in the list are different.
- I.e., design a TM that decides the language

$$E = \{\#x_1\#x_2\#\cdots\#x_l \mid \text{each } x_i \in \{0, 1\}^* \text{ and } x_i \neq x_j \text{ for each } i \neq j\}$$



# Variants of Turing Machines

- There are many alternative definitions of TM's.

# Variants of Turing Machines

- There are many alternative definitions of TM's.
- They are called **variants** of TM's.

# Variants of Turing Machines

- There are many alternative definitions of TM's.
- They are called **variants** of TM's.
- We'll see that they all have the same power.

# Variants of Turing Machines

- There are many alternative definitions of TM's.
- They are called **variants** of TM's.
- We'll see that they all have the same power. This demonstrates the **robustness** in the definition of TM's.

# Variants of Turing Machines

- There are many alternative definitions of TM's.
- They are called **variants** of TM's.
- We'll see that they all have the same power. This demonstrates the **robustness** in the definition of TM's. Also, this is an evidence that TM's "capture" the idea of computation (because whatever computing machine we can think of they are all equivalent to TM's).

# TM with “stay put”

- Let's start with an easy variant. Suppose we allow additional head movement: “stay put (S)”.

# TM with “stay put”

- Let's start with an easy variant. Suppose we allow additional head movement: “stay put (S)”.
- The transition function will be of the form

$$\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R, S\}.$$

- Does this give TM's more power?

# TM with “stay put”

- Let's start with an easy variant. Suppose we allow additional head movement: “stay put (S)”.
- The transition function will be of the form

$$\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R, S\}.$$

- Does this give TM's more power?
- Not really. We can convert a TM with “stay put” to a standard TM as follows.



# TM with “stay put”

- Let's start with an easy variant. Suppose we allow additional head movement: “stay put (S)”.
- The transition function will be of the form

$$\delta : Q \times \Gamma \rightarrow Q \times \Gamma \times \{L, R, S\}.$$

- Does this give TM's more power?
- Not really. We can convert a TM with “stay put” to a standard TM as follows.
  - For any “stay put” transition, we replace with two transitions: “right” and “left”.

# Multitape Turing Machines

- A **multitape Turing machines** has many tapes.

# Multitape Turing Machines

- A **multitape Turing machines** has many tapes.
- For each tape, the machine has a head for reading and writing it.

# Multitape Turing Machines

- A **multitape Turing machines** has many tapes.
- For each tape, the machine has a head for reading and writing it.
- The input appears on tape 1; all other tapes contain blanks.

# Multitape Turing Machines

- A **multitape Turing machines** has many tapes.
- For each tape, the machine has a head for reading and writing it.
- The input appears on tape 1; all other tapes contain blanks.
- Let  $k$  be the number of tapes. The transition function can be defined as

$$\delta : Q \times \Gamma^k \rightarrow Q \times \Gamma^k \times \{L, R, S\}^k.$$

# Multitape Turing Machines

- A **multitape Turing machines** has many tapes.
- For each tape, the machine has a head for reading and writing it.
- The input appears on tape 1; all other tapes contain blanks.
- Let  $k$  be the number of tapes. The transition function can be defined as

$$\delta : Q \times \Gamma^k \rightarrow Q \times \Gamma^k \times \{L, R, S\}^k.$$

- E.g., if  $\delta(q_i, a_1, \dots, a_k) = (q_j, b_1, \dots, b_k, L, R, \dots, L)$  then if the machine is at state  $q_i$  and each head on tape  $i$  reads symbol  $a_i$ , it'll write  $b_i$  on each tape  $i$ , change state to  $q_j$  and move each head accordingly.

### Theorem 1 (equivalence between multitape TM's and TM's)

*Every multitape Turing machine has an equivalent single-tape Turing machine.*

# Proof (1)

- We'll simulate a multitape TM  $M$  to a single-tape TM  $S$ .



# Proof (1)

- We'll simulate a multitape TM  $M$  to a single-tape TM  $S$ .  
Suppose that  $M$  has  $k$  tapes.

# Proof (1)

- We'll simulate a multitape TM  $M$  to a single-tape TM  $S$ . Suppose that  $M$  has  $k$  tapes.
- We store all information on the  $k$  tapes on  $S$ 's tape. What should we keep?

# Proof (1)

- We'll simulate a multitape TM  $M$  to a single-tape TM  $S$ . Suppose that  $M$  has  $k$  tapes.
- We store all information on the  $k$  tapes on  $S$ 's tape. What should we keep?
  - The contents of the tapes.

# Proof (1)

- We'll simulate a multitape TM  $M$  to a single-tape TM  $S$ . Suppose that  $M$  has  $k$  tapes.
- We store all information on the  $k$  tapes on  $S$ 's tape. What should we keep?
  - The contents of the tapes.
  - The position of the heads

# Proof (1)

- We'll simulate a multitape TM  $M$  to a single-tape TM  $S$ . Suppose that  $M$  has  $k$  tapes.
- We store all information on the  $k$  tapes on  $S$ 's tape. What should we keep?
  - The contents of the tapes.
  - The position of the heads
- How?

# Proof (2)

- Combine all tapes into one tape, using # as delimiters.
- Use “marked” symbols to identify the head position on each tape.
- Example:

## Multitape TM:

- Tape 1: 10101**1**10
- Tape 2: 00**0**01
- Tape 3: 011**1**111

# Proof (2)

- Combine all tapes into one tape, using # as delimiters.
- Use “marked” symbols to identify the head position on each tape.
- Example:

## Multitape TM:

- Tape 1: 10101**1**10
- Tape 2: 00**0**01
- Tape 3: 011**1**111

## Simulated TM:

- Tape: #10101**1**10#00**0**01#011**1**111#

## Proof (3): Definign $S$

$S =$  "On input  $w = w_1 \cdots w_n$ :

- 1 Put all tape into the format defined previously:

$$\#w_1w_2\cdots w_n\#\dot{\square}\#\dot{\square}\#\cdots\#$$



# Proof (3): Definign $S$

$S =$  "On input  $w = w_1 \cdots w_n$ :

- 1 Put all tape into the format defined previously:

$$\#w_1w_2\cdots w_n\#\square\square\#\cdots\#$$

- 2 For each move,  $S$  scans its tape once to determine the symbols under all  $M$ 's heads. It than proceeds to do the update according to  $M$ 's transition function.

# Proof (3): Definign $S$

$S =$  "On input  $w = w_1 \cdots w_n$ :

- 1 Put all tape into the format defined previously:

$$\#w_1w_2\cdots w_n\#\sqcup\#\sqcup\#\cdots\#$$

- 2 For each move,  $S$  scans its tape once to determine the symbols under all  $M$ 's heads. It than proceeds to do the update according to  $M$ 's transition function.
- 3 If the content of any simulated tape is overflow (i.e.,  $S$  has to write over some  $\#$  on the right),  $S$  writes a blank symbol to that delimiter, and shifts all the tape contents to the right."

## Corollary 2

*A language is Turing-recognizable if and only if some multitape Turing machine recognizes it.*

# Nondeterministic Turing Machines

- A nondeterministic Turing machine can make “nondeterministic” move.

# Nondeterministic Turing Machines

- A nondeterministic Turing machine can make “nondeterministic” move.
- As expected, its transition function has the form

$$\delta : Q \times \Gamma \rightarrow \mathcal{P}(Q \times \Gamma \times \{L, R\}).$$

# Nondeterministic Turing Machines

- A nondeterministic Turing machine can make “nondeterministic” move.
- As expected, its transition function has the form

$$\delta : Q \times \Gamma \rightarrow \mathcal{P}(Q \times \Gamma \times \{L, R\}).$$

- Again, we view the computation of a nondeterministic Turing machine as a tree, where each branching corresponds to the place where the TM can make different moves.

# Nondeterministic Turing Machines

- A nondeterministic Turing machine can make “nondeterministic” move.
- As expected, its transition function has the form

$$\delta : Q \times \Gamma \rightarrow \mathcal{P}(Q \times \Gamma \times \{L, R\}).$$

- Again, we view the computation of a nondeterministic Turing machine as a tree, where each branching corresponds to the place where the TM can make different moves.
- Can nondeterminism help?

### Theorem 3

*Every nondeterministic Turing machine has an equivalent deterministic Turing machine.*



# Proof idea

- We will simulate a nondeterministic TM  $N$  with a deterministic TM  $D$ .
- We can try having  $D$  visit all the branches in the computation tree of  $N$

# Proof idea

- We will simulate a nondeterministic TM  $N$  with a deterministic TM  $D$ .
- We can try having  $D$  visit all the branches in the computation tree of  $N$   
What's wrong with that?

# Proof idea

- We will simulate a nondeterministic TM  $N$  with a deterministic TM  $D$ .
- We can try having  $D$  visit all the branches in the computation tree of  $N$   
What's wrong with that? (hint: halting?)

# Proof idea

- We will simulate a nondeterministic TM  $N$  with a deterministic TM  $D$ .
- We can try having  $D$  visit all the branches in the computation tree of  $N$

What's wrong with that? (hint: halting?)

- If on some branch  $N$  loops forever,  $D$  will get stuck in that branch and will never find the accept state.

# Proof idea

- We will simulate a nondeterministic TM  $N$  with a deterministic TM  $D$ .
- We can try having  $D$  visit all the branches in the computation tree of  $N$   
What's wrong with that? (hint: halting?)
  - If on some branch  $N$  loops forever,  $D$  will get stuck in that branch and will never find the accept state.
- The idea is to let  $D$  explore the computation tree carefully.

# Proof idea

- We will simulate a nondeterministic TM  $N$  with a deterministic TM  $D$ .
- We can try having  $D$  visit all the branches in the computation tree of  $N$   
What's wrong with that? (hint: halting?)
  - If on some branch  $N$  loops forever,  $D$  will get stuck in that branch and will never find the accept state.
- The idea is to let  $D$  explore the computation tree carefully.
  - $D$  explore all branches at some fixed **depth**. After exploring all branches, it starts exploring at the next depth.

# Proof idea

- We will simulate a nondeterministic TM  $N$  with a deterministic TM  $D$ .
- We can try having  $D$  visit all the branches in the computation tree of  $N$   
What's wrong with that? (hint: halting?)
  - If on some branch  $N$  loops forever,  $D$  will get stuck in that branch and will never find the accept state.
- The idea is to let  $D$  explore the computation tree carefully.
  - $D$  explore all branches at some fixed **depth**. After exploring all branches, it starts exploring at the next depth.
  - This way of exploring the tree is called **breadth-first search**.