

ΣRGOCOMPREHENSIVE CRYPTOCURRENCY DESIGN

DMITRY MESHKOV 26 MAY 2017 GENESIS MOSCOW CONFERENCE

Structure

- Σrgo idea
- Blockchain problems
- **Srgo** solution

Σrgo idea

Motivation

Theory

- Provably secure
- New features
- Impractical




Practice

- 1000 currencies
- Ad-hoc solutions
- Security issues

Motivation: Scorex

Theory

- Provably secure
- New features
- Impractical




Practice

- 1000 currencies
- Ad-hoc solutions
- Security issues

Motivation: Σrgo

Theory

- Provably secure
- New features
- Impractical



Σrgo idea

Design scalable, user-friendly decentralized cryptocurrency by combining ideas complementing each other

Blockchain problems

Throughput

- Bitcoin throughput: 2-3 tx/sec ().
- Blocks are full
- UTX size: 200000 tx
- Transaction fees are high
- Not applicable for mass adaptation

Smart contracts


- Bitcoin script is limited
- Instructions are hard-coded

General-purpose smart contract languages:


- Limited with total cost of all the operations
- Cost estimations are hard (DoS attacks)
- A lot of possibilities => a lot of vulnerabilities

Blockchain and State

• Blockchain




State



Blockchain and State

Miners should validate transactions efficiently. They can: 1.Keep State in RAM => Mining centralization 2.Do not keep State => SPV mining








Blockchain and State

Problems for users:


- Can't validate blocks on low-end hardware
- Long validation on commodity hardware
- Users move to centralized services



Σrgo Solution

Blockchain size: Rollerchain


Rollerchain



- Miners are enforce to keep fixed number of last blocks and headers (~40 Mb)
- Static storage requirements
- Fast bootstrap

State size: Space-scarce economy


Space-scarce economy state



- Controllable State size with upper-bound
- Incentive for active users
- Return lost coins to economy
- Predictable miner reward


Header chain size: PoPoW

PoPoW



- Nodes should keep only sublinear subset of headers (~20 Kb)
- Extremely fast bootstrap
- Cross-chain proofs (e.g. sidechains)

Light node state size



Proofs verify balances and calculate new root hash

Reyzin, L., Meshkov, D, Chepurnoy, A. & Ivanov A. Improving Authenticated Dynamic Dictionaries, with Applications to Cryptocurrencies

Light node state size

Light node blockchain: (~20 Kb)



Light node state: 32 byte




- Full node security guarantees with few Kb of data
- Decentralized user-friendly light wallet

Smart contracts support


- Rich authenticated transaction language (Σlang)
- Environment propositions + Crypto propositions
- For free: threshold signatures, ring signatures
- Ahead-of-time cost analysis
- Protocols-friendly blockchain

Σrqo as database

- State as database
- Aspen blockchain structure



Sidechains – data chain and money chain



Throughput

- Bitcoin-ng for maximum on-chain thoughput (100 tx/s)
- Off-chain protocols on top of flexible transactional language (10K tx/s)
- Multiple blockchains with sidechain token transfer between them for further research


I. Eyal, et al. Bitcoin-ng: A scalable blockchain protocol

J. Poon, T. Dryja, The bitcoin lightning network: Scalable off-chain instant payments

A. Miller, et al. Sprites: Payment channels that go faster than lightning

A. Back, et al., Enabling blockchain innovations with pegged sidechains

Status



Conclusion

- Constant storage requirements
- Controllable state size
- Full-node security guarantees on smartphones
- Smart-contracts including cryptography
- Efficient blockchain as database
- High throughput
- Decentralized network

Thank you!

Collaborations are welcomed!

- Site: http://ergoplatform.org
- Twitter: https://twitter.com/ergoplatformorg
- Email: ergoplatform@protonmail.com