Example of the QRCVDTAQ and QSNDDTAQ API in CL

Technote

Following is an example of a CL program that is calling the QRCVDTAQ and QSNDDTAQ APIs. Use the **CRTDTAQ** command to create a data queue if one does not currently exist. For this example, you would want the data queue name to be FILEINFO in library QGPL.

Example

PGM

DCL VAR(&DQNAME) TYPE(*CHAR) LEN(10) VALUE('FILEINFO')

DCL VAR(&DQLIB) TYPE(*CHAR) LÉN(10) VALUE('QGPL')

DCL VAR(&DQSNDLEN) TYPE(*DEC) LEN(5 0) VALUE(14)

DCL VAR(&DQLEN) TYPE(*DEC) LEN(5 0)

DCL VAR(&DQSNDDATA) TYPE(*CHAR) LEN(100)

DCL VAR(&DQDATA) TYPE(*CHAR) LEN(100)

DCL VAR(&DQWAIT) TYPE(*DEC) LEN(5 0) VALUE(0)

CHGVAR VAR(&DQSNDDATA) VALUE('THIS IS A TEST')

CALL QSNDDTAQ PARM(&DQNAME &DQLIB &DQSNDLEN &DQSNDDATA)

CALL QRCVDTAQ PARM(&DQNAME &DQLIB &DQLEN &DQDATA &DQWAIT)

SNDPGMMSG MSGID(CPF9898) MSGF(QCPFMSG) MSGDTA(&DQDATA)

ENDPGM

System i Support

IBM disclaims all warranties, whether express or implied, including, but not limited to, the implied warranties of merchantability and fitness for a particular purpose. By furnishing this document, IBM grants no licenses to any related patents or copyrights. Copyright © 1996,1997,1998, 1999, 2000, 2001, 2002, 2003, 2004, 2005, 2006, 2007, 2008, 2009, 2010, 2011, 2012, 2013 IBM Corporation. Any trademarks and product or brand names referenced in this document are the property of their respective owners. Consult the **Terms of use** link for trademark information.

Copyright and trademark information

IBM, the IBM logo and ibm.com are trademarks of International Business Machines Corp., registered in many jurisdictions worldwide. Other product and service names might be trademarks of IBM or other companies. A current list of IBM trademarks is available on the Web at "Copyright and trademark information" at www.ibm.com/legal/copytrade.shtml.

Document information

i family

Software version: V5R4M0, V5R4M5,

V6R1M0, V6R1M1,

V7R1M0

Operating system(s): OS/400

Reference #:

353981239

Modified date: 2012-12-29