


PH-107

# Explanation of Tunnelling and Examples

# Tunneling for Light waves


Total internal reflection of light waves at a glass – air boundary.



Light entering a right-angle prism is completely reflected at the hypotenuse face, even though an electro-magnetic wave, the evanescent wave, penetrates into the space beyond the reflecting surface.

# Tunneling for Light waves



Total internal reflection of light waves at a glass – air boundary.



When light is total-internally reflected, Maxwell's equations require that the tangential component of the electric field remains continuous across the boundary of the two media (**Evanescent Wave**).

# Tunneling for Light waves


Total internal reflection of light waves at a glass – air boundary.




A second prism brought into near contact with the first can “pick up” this evanescent wave, thereby transmitting and redirecting the original beam. The evanescent wave is “picked up” by a neighbouring surface, resulting in transmission across the gap. Notice that the light beam *does not* appear in the gap. This phenomenon, known as **frustrated total internal reflection**, is the optical analog of tunneling: In effect, photons have tunnelled across the gap separating the two prisms.

# Quantum Tunneling Through a Thin Potential Barrier

## Total Reflection at Boundary




## Frustrated Total Reflection (Tunneling)



# Continuity Equation

## *Equation of Continuity*



Mass flow rate  
at position 2  $= \frac{\Delta m_2}{\Delta t} = \rho_2 A_2 v_2$

Mass flow rate  
at position 1  $= \frac{\Delta m_1}{\Delta t} = \rho_1 A_1 v_1$

$$\rho_1 A_1 v_1 = \rho_2 A_2 v_2$$

# Continuity Equation

$$\frac{\partial \rho}{\partial t} + \frac{\partial j}{\partial x} = 0$$

This is known as quantum mechanical version of continuity equation.

$$\rho = \psi\psi^* \text{ and } j = \frac{\hbar}{2im} \left[ \psi^* \frac{\partial \psi}{\partial x} - \psi \frac{\partial \psi^*}{\partial x} \right]$$



**Probability Current Density**

**Probability Density**

The **equation** states that the time derivative of the probability of the particle being measured in  $V$  is equal to the rate at which probability flows into  $V$ .

Flow of probability in terms of probability per unit time per unit area.

# Continuity Equation

For a plane wave propagating in space:  $\Psi(x, t) = A e^{i(kx - \omega t)}$

The probability density is constant everywhere;

$$\rho(x, t) = |A|^2 \rightarrow \frac{\partial |\Psi|^2}{\partial t} = 0$$

(that is, plane waves are stationary states) but the probability current is nonzero – the square of the absolute amplitude of the wave times the particle's speed;

$$j(x, t) = |A|^2 \frac{\hbar k}{m} = \rho \frac{|p|}{m} = \rho |v|$$

Illustrating that the particle may be in motion even if its spatial probability density has no explicit time dependence.




# Continuity Equation

There's no energy transfer, but we can find the particle. How do we understand this ?

There is no transfer of probability density  $\rho(x) = |\varphi(x)|^2$  either. This is equivalent to saying that no particle crosses the potential step.

The Reflection and the Transmission coefficients are given as

$$R = \frac{j_R}{j_I} \quad \text{and} \quad T = \frac{j_T}{j_I}$$



# Continuity Equation


$$R = \frac{j_R}{j_I} \quad \text{and} \quad T = \frac{j_T}{j_I}$$

We know


$$j = \frac{\hbar}{2im} \left[ \psi^* \frac{\partial \psi}{\partial x} - \psi \frac{\partial \psi^*}{\partial x} \right]$$

$$\text{In region II} \quad j_{II} = \frac{\hbar}{2im} \left[ \psi^* \frac{\partial \psi}{\partial x} - \psi \frac{\partial \psi^*}{\partial x} \right] = 0$$

$$\text{As } \psi(x) = \psi^*(x) = C e^{-\alpha x}$$



## Energy in Region II



Wave function rapidly approaches zero beyond  $x = 1/\alpha$ . Therefore the probability density is appreciable only near  $x = 0$ , in the range

$$\Delta x = \frac{1}{\alpha} = \frac{\hbar}{\sqrt{2m(V_0 - E)}}$$

So one may say that the particle is predominantly localized within the length  $\Delta x$ .

## Energy in Region II

Uncertainty principle then requires that



$$\Delta p \simeq \frac{\hbar}{(2\Delta x)} = \sqrt{2m(V_0 - E)}$$

Uncertainty in the energy of the particle

$$\Delta E = \frac{(\Delta p)^2}{2m} \simeq (V_0 - E)$$

So, it is impossible to determine whether the energy of the particle is less than or greater than the barrier.

# Application I: Field Emission




Electrons are emitted from a metal under the action of a strong electric field.

# Application I: Field Emission

$$T(E) \simeq \exp \left( -\frac{2}{\hbar} \sqrt{2m} \int \sqrt{U(x) - E} \, dx \right)$$

$$T(E)_{\text{FE}} \simeq \exp \left( \left\{ -\frac{4}{3e\hbar} \sqrt{2m} |E|^{3/2} \right\} \frac{1}{\epsilon} \right)$$

$$\simeq \exp \left( -\frac{\epsilon_c}{\epsilon} \right)$$



Some numbers:  $|E| = \phi = 4.0 \text{ eV}$ .  $\epsilon_c = 5.5 \times 10^{10} \text{ V/m}$

Emission rate ( $10^9 \text{ e-/s}$ ) = collision frequency  $\times T(E)_{\text{FE}}$  can be realized for  $\epsilon = 10^9 \text{ V/m}$

### Example 7.1 from Serway:

Two conducting copper wires are separated by an insulating layer of copper-oxide. We model the oxide layer as a rectangular barrier of height 10 eV. Calculate the transmission coefficient for penetration by 7 eV electrons, if the layer thickness is (a) 5 nm and (b) 1 nm.

$$\kappa = \frac{\sqrt{2m(V_0 - E)}}{\hbar} == \sqrt{2 \times 511000 \times 31973} = 0.9(\text{Angstrom})^{-1}.$$

For  $L \gg 1$ ,  $\kappa L \approx 45 \implies \sinh(\kappa L) \approx \exp(\kappa L)/2$ .


Thus we  $T \approx 4 \exp(-2\kappa L)$  leading to

$$\frac{T(L = 50)}{T(L = 10)} = 4 \exp(-2 \times 0.9 \times 40) \approx 10^{-31}.$$

Because of the exponential factor, small changes of the barrier height or width lead to large changes in the tunnelling probability.

# Application II: Alpha-Decay

Nucleus ( $+Ze$ )



Alpha particle ( $+2e$ )



**Table 7.1 Characteristics of Some Common  $\alpha$  Emitters**



Element	$\alpha$ Energy	Half-Life*
$^{212}_{84}\text{Po}$	8.95 MeV	$2.98 \times 10^{-7} \text{ s}$
$^{240}_{96}\text{Cm}$	6.40 MeV	27 days
$^{226}_{88}\text{Ra}$	4.90 MeV	$1.60 \times 10^3 \text{ yr}$
$^{232}_{90}\text{Th}$	4.05 MeV	$1.41 \times 10^{10} \text{ yr}$

\*Note that half-lives range over 24 orders of magnitude when  $\alpha$  energy changes by a factor of 2.

Decay of radioactive elements with emission of  $\alpha$ -particles (helium nuclei) was puzzling until 1928 (Gamow and Gurney).



# Application II: Alpha-Decay



$$T(E)_\alpha \simeq \exp \left( -4\pi Z \sqrt{\frac{E}{E_0}} + 8 \sqrt{\frac{ZR}{r_0}} \right)$$




$r_0 = 7.25 \text{ fm}$  is like the “Bohr radius” of the  $\alpha$ -particle.

$E_0 = 0.0993 \text{ MeV}$  is analogous to the Rydberg constant.

$R \sim 10 \text{ fm}$ ;  $U(r) \sim 30 \text{ MeV}$

**Decay rate**  $\lambda \propto T(E)_\alpha = t_{1/2}^{-1}$

# Application III: Ammonia Inversion




$$U(x) = \frac{1}{2} M \omega^2 (|x| - a)^2$$



$$\frac{4}{A^2} \int_0^{a-A} \sqrt{(x-a)^2 - A^2} dx = \sinh(2y_0) - 2y_0$$

$$T = e^{-[\sinh(2y_0) - 2y_0]}$$

# Application IV: STM




Sodium atoms  
on metal:




# Flash Memory




Image is in the public domain



Erased  
"1"



Programmed  
"0"



Electrons tunnel preferentially when a voltage is applied

# MOSFET: Transistor in a Nutshell




Image courtesy of J. Hoyt Group, EECS, MIT.  
Photo by L. Gomez

Conduction electron flow




Image courtesy of J. Hoyt Group, EECS, MIT.  
Photo by L. Gomez



Image is in the public domain

Tunneling causes thin insulating layers to become leaky !