# pukRhelpers: A Personal Toolbox of R Helpers

## Small utilities for ArcGIS services, UGRC data, KML and sf that I reused across projects

Pukar Bhandari

pukar.bhandari@outlook.com

2025-05-23

## Table of contents

1 Install . . . . . 1
2 What is in it . . . . . 1

`pukRhelpers` is where the small functions I kept copying between projects ended up. It is a personal toolbox, not a polished library, and I only update it when my own work needs something. The package has continuous checks and test coverage set up, and documentation at ar-puuk.github.io/pukRhelpers.

Docs GitHub

## 1 Install

```
pak::pak("ar-puuk/pukRhelpers")
install.packages("pukRhelpers", repos = "https://ar-puuk.r-universe.dev")
```

**Line 1**

Straight from GitHub. `remotes::install_github()` and `devtools::install_github()` work too.

**Line 2**

Or from my personal R-universe.

## 2 What is in it

| Function | What it does |
|---|---|
| `load_esri()` | Load and query an ESRI Feature Service layer |

| Function | What it does |
|---|---|
| `arc_read_encode()` | `arcgislayers::arc_read()` with coded-value encoding built in, so no stray helper objects are left in the environment |
| `load_ugrc_data()`, `load_ugrc_vars()` | Load a dataset, or list the datasets, from Utah's SGID |
| `load_kml_sf()` | Convert KML to an `sf` object with attributes preserved |
| `st_aggregate()` | Aggregate `sf` objects |
| `geo_split_lines()`, `st_split_lines()` | Split lines by a maximum length |
| `convert_fgb_to_gdb()` | Convert FlatGeobuf files to geodatabase layers |
| `convert_xml_html()`, `extract_html_table()` | XML to HTML via XSLT, and pull a table out of an HTML page by its anchor |
| `load_packages()` | Load, installing first if needed |

Several of these build on other people's gists and are credited to them in the function documentation and the README.

The code is on GitHub under GPL-3.